

# CALRAD

## 65 Series - VOM Multimeters

### 65-263 DIGITAL MULTIMETER

3.5 digit DMM has 1/2" high LCD display. 20 position rotary switch sits in compact, shirt pocket size meter. Has diode, transistor and continuity tester. Has 10 amp DC current range and includes temperature probe good from -40 to 1000 C High impact yellow plastic case. Comes with fuse protection and 9 volt battery.

#### Specifications:

DC Volt.....0-200mv -2V-20V-200V-1000V	Test Leads.....(Red & Black) 24 "
AC Volt.....0-250V - 750V	Battery.....9V battery(included)
DC Current...0-2000uA -20ma-200ma-10A	Weight.....0.5 lbs
AC Current.....No AC Current function	Size....5" L x 2 5/8" W x 7/8" D
Case Color.....Yellow	
Resistance 0 - 200 ohms -2000 -20K-200K -2000K	



### 65-264 MINI DIGITAL MULTIMETER

Pocket portable multi-meter with 5 functions and 19 ranges. Each test position is quickly and easily selected with a simple turn of the selector switch. 3.5 digit, 7 segment, 0.5" high LCD display with polarity. Diode and transistor tester. Overload fuse protection and low battery indicator circuitry. 19 position rotary range switch. High impact resistant protective yellow case.

#### Specifications:

DC Volt:.....0-200Mv-2000Mv-20V-200V-1000V
AC Volt:.....100Mv-200V: 1V-750V Max 750V RMS Peak-Peak
DC Current:.....0-200uA-2000uA-20m-200m-10A
Resistance: .....0-200-2000-20K-200K-2000K
Test Leads: .....(Red & Black) 18" Long
Weight:.....6 oz.
Dimensions: .....25/8"(W) x 45/8"(L) x 15/16"(D)
Case Color/Material: .....Yellow and Plastic



### 65-266 DIGITAL MULTIMETER

3.5 digit adjustable-display DMM with 1" high contrast LCD display. Diode and 50 ohm continuity beeper, transistor tester. Overload fuse protection and low battery indicator circuitry. 30 position rotary range switch with separate data hold switch. High impact resistant protective yellow holster.

#### Specifications:

DC Volt..... 0-200mv-2V-20V-200V-1000V	Test Leads ..... (Red & Black) 38"
AC Volt..... 0-2V-20V-200V-700V	Battery ..... 9V battery (included)
DC Current ..... 0-2ma-20ma-200ma-20A	Weight..... 1.25 lbs.
AC Current ..... 0-20ma-200ma-20A	Size ..... 7.75"L x 3.75"W x 1.625"D
Case Color..... Black	Capacitance..... 0-2nf-20nf-200nf-2uf-20uf
Resistance 0-200ohms-2K-20K-200K-2M-20M-200M	



### 65-270 HDMI CABLE TESTER

Allows you to test your HDMI cables even if they are installed in the wall. Sold as a transmitter and receiver pair. The receiver unit has 9 easy to read L.E.D's. Provides automatic independent testing for TDMS Red, TDMS Green, TDMS Blue, TDMS Clock, CEC, 12C Clock, 12C Data, 5Vdc, and Hot Plug. Can be used to test DVI cables by using the optional Calrad 35-716 DVI to HDMI adapter, sold separately. Works with all formats of HDMI and DVI cables. Operates on one 9 volt battery (not included). Dimensions: Transmitter: H 5.3" X W 2.75" X D 1.1", Receiver: H 5.3" X W 2.75" X D 1.1".

**35-716**  
HDMI Male to DVI-D  
Female cable adapter.  
Gold plated contacts.  
6" Length.

