

TENSIONED CONFERENCE ELECTROL®

Concealed-In-The-Ceiling Electric Tensioned Video Conferencing Screen with Closure Doors



- Tensioning system provides an extra flat surface for optimum image quality.
- Allows the projection screen and video conferencing camera to be completely concealed when not in use.
- Designed to be recessed in the ceiling and includes a trim flange for a clean, finished installation.
- Shelf for the video conferencing camera lowers via arms behind the screen surface.
- When retracted, the screen surface and video conferencing shelf arms are completely concealed by closure doors, allowing the room aesthetics to remain undisturbed.

16:9 HDTV FORMAT DIMENSIONS


Viewing Area H x W		Nominal Diagonal		Overall Case Length	
in.	cm	in.	cm	in.	cm
45" x 80"	114 x 203	92"	234	120"	305
52" x 92"	132 x 234	106"	269	120"	305
54" x 96"	137 x 244	110"	279	143 ¹ / ₈ "	364
58" x 104"	147 x 264	119"	302	143 ¹ / ₈ "	364
65" x 116"	165 x 295	133"	338	143 ¹ / ₈ "	364

16:10 WIDE FORMAT DIMENSIONS

Viewing Area H x W		Nominal Diagonal		Overall Case Length	
in.	cm	in.	cm	in.	cm
50" x 80"	127 x 203	94"	239	120"	305
57 ¹ / ₂ " x 92"	146 x 234	109"	277	143 ¹ / ₈ "	364
60" x 96"	152 x 244	113"	287	143 ¹ / ₈ "	364
65" x 104"	165 x 264	123"	312	143 ¹ / ₈ "	364
69" x 110"	175 x 279	130"	330	143 ¹ / ₈ "	364
72 ¹ / ₂ " x 116"	184 x 295	137"	348	143 ¹ / ₈ "	364

Available Screen Surfaces: Da-Mat®, High Contrast Da-Mat®, Pearlescent, Cinema Vision and High Contrast Cinema Vision.

See pages 6-10 for surface descriptions.



For optional remote control operation, see options on pages 39-40.