Safety Blow Guns

O.S.H.A. Certification — All safety blow guns conform to the requirements of Compressed Air Standards as currently described in the U.S. Bureau of Labor Standards, paragraph 1910.242, when pressurized at the inlet to a maximum of 100 PSIG. Conform to current O.S.H.A. Directive No. 100-1.

Brass Nozzle Blow Guns

Contoured lever or button control both provide a natural, comfortable grip even when used with gloves. Finger guard and hang-up hook for finger protection and quick safe storage. Die cast zinc body, painted finish.

Lever Operated

Part	Inlet	SCFM
Number	Port	Rating*
00475 0010	1/4"	20

Button Operated

Relief & Exhaust Valves

Pressure Switches I

AirGuard Protection

Drain Valves

Part	Inlet	SCFM
Number	Port	Rating*
00470 0010	1/4"	20

*Based on 100 PSIG inlet pressure.



Vortec FLO-GAIN Blow Guns

A quiet Vortec FLO-GAIN nozzle is combined with a high performance blow gun. Compressed air attains sonic velocity through an adjustable slot and attaches to the exterior surface of the cone shaped nozzle. Settings are shown on a micrometer dial. Sound level of 80 dBA with 80 PSIG inlet. Finger guard and hang-up hook offers desirable finger protection and quick secure storage. Die cast zinc body, painted finish.

Lever Operated

Part	Inlet	SCFM
Number	Port	Rating*
00475 0900	1/4"	70+

Button Operated

Part Number	Inlet Port	SCFM Rating*	
00470 0900	1/4"	70+	

*Based on 100 PSIG inlet pressure.

