

# CALRAD

## 40 Series - Switches

### SPST ROCKER SWITCHES WITH L.E.D.

(Switch contacts rated 5 AMP-125 VAC) Easy Snap-in mounting. Hole size  $\frac{3}{4}$ " x  $\frac{1}{2}$ ". Dropping resistor required. DC voltage: 6 vdc-270 ohms, 12 vdc-680 ohms, 24 vdc-1.5k.

- 40-710 ..... Red LED
- 40-711 ..... Green LED
- 40-712 ..... Orange LED



### 40-600, SPST 40-601, DPDT TOGGLE SWITCH

SPST bakelite case, bat handle with chrome on/off plate. Solder-type terminals. Rated 3 Amp, 125 volt.

40-600 Size: 1" x  $\frac{3}{16}$ " x  $\frac{1}{8}$ " deep to top of  $\frac{7}{16}$ " bushing.

40-601 Size:  $\frac{1}{8}$ " x  $\frac{3}{4}$ " x  $\frac{1}{4}$ " deep to top of  $\frac{7}{16}$ " bushing.



### 40-635 SPDT ILLUMINATED ROCKER SWITCH

SPST switch. Rated 10 Amp, 125 volt. Neon bulb operates on 117 AC line. Has built-in resistor,  $\frac{1}{4}$ " x  $\frac{5}{8}$ " top dimensions.

- 40-635A  
12 volt DC version of 40-635.



### 40-602 HEAVY DUTY CENTER-OFF TOGGLE SWITCH

DPDT center-off, rated 6 Amp, 125 volt, bat handle, red and black on/off plate. Screw terminals.

Size:  $\frac{5}{16}$ " x  $\frac{3}{4}$ " x  $\frac{1}{8}$ " deep, mounts in  $\frac{7}{16}$ " hole.



### L.E.D. TOGGLE SWITCHES

3 Amp, 125 Vac, attractive, slim, cylindrical handle, with built-in L.E.D indicator light in the tip. Solder-type terminals. Body size:  $\frac{3}{4}$ " x  $\frac{1}{2}$ " x  $\frac{11}{16}$ " deep (including pins). Bushing size:  $\frac{7}{16}$ ". Dropping resistor required. DC voltage: 6 vdc-270 ohms, 12 vdc-680 ohms, 24 vdc-1.5k.

- 40-593 ..... SPDT Red L.E.D
- 40-594 ..... SPDT Green L.E.D



### 40-691 HEAVY DUTY TOGGLE SWITCH

SPST 6 Amp, 125 Vac. Body size:  $\frac{1}{8}$ " x  $\frac{5}{8}$ " x  $\frac{7}{8}$ " deep. Screw terminals. Mounts in  $\frac{1}{2}$ " hole.

40-692  
DPDT 6 Amp, 125 Vac. Body size:  $\frac{5}{16}$ " x  $\frac{3}{4}$ " x  $\frac{3}{4}$ ". Screw terminals. Mounts in  $\frac{1}{2}$ " hole.



### HEAVY DUTY 20 AMP (125V) SWITCHES

Mounts in  $\frac{1}{2}$ " hole. Bushing size:  $\frac{15}{32}$ " dia. x  $\frac{3}{8}$ " long. Body size:  $\frac{1}{8}$ " x  $\frac{5}{8}$ " x 1" deep.

- 40-560 ..... SPST (On-Off)
- 40-561 SPDT (On-Off-On) Center Off



### MINIATURE FLAT TOGGLE SWITCH SERIES

Specially designed for decorative appearance with ease in smooth switching operation in mind. Specify part number.

#### Specifications

Contact rating: 6 Amp-125 Vac, 3 Amp-250 Vac.  
Bushing:  $\frac{1}{4}$ ". Thread length:  $\frac{5}{16}$ ".  
All necessary mounting hardware included.

### HEAVY DUTY 20 AMP (125V) SWITCHES

Mounts in  $\frac{1}{2}$ " hole. Bushing size:  $\frac{15}{32}$ " dia x  $\frac{3}{8}$ " long. Body size:  $\frac{5}{16}$ " x  $\frac{3}{4}$ " x 1" deep.

- 40-562 ..... DPDT (On-On)
- 40-563 DPDT (On-Off-On) Center Off



- 40-580..... SPDT, On-On
  - 40-581.....SPDT, On-On Momentary
  - 40-582.....SPDT, On-Off-On
  - 40-583.....SPDT, On-Off-On, Mom.
  - 40-584.....SPDT,-On-Off-On, Mom.
- Body Size 40-580 thru 40-584:  
 $\frac{1}{2}$ " x  $\frac{5}{16}$ " x  $\frac{1}{2}$ " deep including terminals



### HEAVY DUTY TOGGLE SWITCHES

Fast snap action toggles. Extremely smooth operation. Flat chrome handle. Rate 6 Amps, 250 volts. Silver contacts. Specify type. Both mount in  $\frac{1}{2}$ " hole. Bushing size:  $\frac{15}{32}$ " dia x  $\frac{3}{8}$ " long.

- 40-605 ..... SPDT  $\frac{1}{8}$ " X  $\frac{5}{8}$ " X  $\frac{13}{16}$ "
- 40-606 ..... DPDT  $\frac{1}{8}$ " X  $\frac{3}{4}$ " X  $\frac{13}{16}$ "



- 40-585.....DPDT, On-On
  - 40-586.....DPDT, On-On Momentary
  - 40-587.....DPDT, On-Off-On
  - 40-588.....DPDT, On-Off-On Mom.
  - 40-589.....DPDT, On-Off-On Mom.
- Body Size 40-585 thru 40-589:  
 $\frac{1}{2}$ " x  $\frac{1}{2}$ " x  $\frac{1}{2}$ " deep including terminals.

