

CALRAD

95 Series - Alarms & Keypads

- 95-600 6 ZONE ALARM SYSTEM WITH L.E.D. KEYPAD**
- 95-800 8 ZONE ALARM SYSTEM WITH L.E.D. KEYPAD**

Burglar and Fire Alarm control panels are ideal for light residential and commercial use. The small keypad with its large, illuminated tactile buttons make entering commands easy in low lighting conditions. Removable front door on control panel for easy wiring and access. Built-in power supply and digital communicator. Unit comes with (1) control panel, (1) L.E.D. digital keypad, (1) AC power transformer. Can use up to seven (95-602) alpha-numeric keypads and four (95-601) L.E.D. keypads. All options are fully programmable thru the digital keypad. Programmable entry, exit, siren delay times. UL Compliance Alarm Panel.

Specifications

Power Requirements 16Vac, 40VA Transformer Supplied
 Battery Backup terminals provided for a 12V battery, rechargeable gel type, not supplied (Calrad part # 95-894)
 Regulated Switched Auxiliary Power Supply 500mA - 800mA max, with all devices.
 Siren Output: Current 2 Amps
 Zones Normally Closed and Normally Open
 System Capacity 7 alpha-numeric keypads and 4 L.E.D. keypads
 Transient & Lightning Protection Yes
 Wiring Knockouts 3/4"
 Cabinet Lock Knockout provided
 Dimensions 11"(H) x 11"(W) x 3 1/2"(D)
 Weight 4 lbs.



Easy Access
Barrier Terminal Strip

95-601 L.E.D. KEYPAD

Used with the Calrad 95-600 6 zone alarm system. 3 wire hookup. LED keypad size: 6 1/2"(W) x 4 1/2"(H) x 1 1/4"(D).



95-602 L.C.D. KEYPAD

Used with the Calrad 95-600 6 zone alarm system. 3 wire hookup. LCD keypad size: 6 1/2" (W) x 4 1/2"(H) x 1 1/4"(D).



95-801 L.E.D. KEYPAD

Used with the Calrad 95-800 8 zone alarm system. 3 wire hookup. LED keypad size: 6 1/2"(W) x 4 1/2"(H) x 1 1/4"(D).



95-802 L.C.D. KEYPAD

Used with the Calrad 95-800 8 zone alarm system. 3 wire hookup. LCD keypad size: 6 1/2"(W) x 4 1/2"(H) x 1 1/4"(D).



95-1601 L.E.D. KEYPAD

16 zone L.E.D. keypad 55-130mA nominal current draw. 3 wire hookup. Size: 6.5"(W) x 4"(H) x 1.3"(D)



95-470 SMOKE DETECTOR

Self diagnostic 4 wire photoelectric smoke detector with heat sensor, 12/24Vdc. Perfect for home or commercial use. Works with all Calrad 95-600, 95-800 series security panels. Alarm Current draw [Nominal] 15.0 mA. Size: Diameter 6.1", Depth 1.85". Approvals, UL 268, ULC, FM, CSFM, MEA.

