


95 Series - AC Plugs, Wall Adapters, Splitters

95-790

CHASSIS MOUNT AC RECEPTACLE

Solder type, 3-prong (grounding type) jack. Snap-in mounting. UL approved. 15A/125V. Mounts in 1.06"(W) x .87"(H) hole. Overall depth 1.28". Black plastic body.



95-771

FEMALE AC SOCKET

Solder type, recessed female AC panel jack. 10A at 250Vac. Black plastic body. US and CSA approved. Mounts in 1.27"(W) x .96"(H) hole. Overall depth 1.25" with 1.55" mounting centers. Black plastic body.



95-791

CHASSIS MOUNT AC RECEPTACLE

Solder type, 2-prong (polarized) jack. Snap-in mounting. UL approved. 15A/125V. Mounts in .95"(W) x .48"(H) hole. Overall depth 1.13". Black plastic body.



95-772

HEAVY DUTY INLINE MALE AC PLUG

Solder type, inline 3 conductor male AC connector. 10A at 250Vac. Black plastic body.



95-770

MALE AC SOCKET

Solder type, recessed male AC panel jack. 10A at 250Vac. Black plastic body. US and CSA approved. Mounts in 1.1"(W) x .74"(H) hole. Overall depth 1.25" with 1.55" mounting centers. Black plastic body.



95-773

HEAVY DUTY INLINE FEMALE AC PLUG

Solder type, inline 3 conductor female AC connector. 10A at 250Vac. Black plastic body.



95-770-SNAP

Snap-in version, US and CSA approved. Mounts in 1.025" (W) x .84"(H) hole. Overall depth .96". Black plastic body.



95-777

2 WAY AC SPLITTER

1 male AC 3 prong to 2 Females, Rubber Body, Color is Black.



95-776

2 WAY IEC/AC SPLITTER

1 IEC Male to 1 AC 3 prong and 1 IEC Females, rubber Body.



95-792-GN Green

95-792-OR Orange

3 Way AC Grounding Wall tap.

Available in either green or orange color options. 110/125Vac, 15 amp rating. UL listed, rubber Body.



95-796

SINGLE OUTLET SURGE PROTECTOR

1-mov, 90-joules. LED power indicator. 120 Vac, 15 amp, 1875 watt rating. UL listed.

