

CALRAD

55 Series - Component, S-Video Cables

55-617 LOW LOSS MULTI-CONDUCTOR (COMPONENT VIDEO, COMPOSITE VIDEO, STEREO ANALOG AUDIO, RF) SHIELDED COAX AUDIO/VIDEO CABLE. SUPPORTS STANDARD DEFINITION AND HDTV.

7 Individually molded, color coded cables. 1 x RCA composite video Male plug (Yellow). 3 x RCA component video Male plugs (Y=Green, Pb=Blue, Pr= Red). 2 x RCA stereo analog audio Male plugs (1 ea. Red & White), 1 x RCA Digital audio Male plug (Orange). 1 x "F" RF Male plug (Black). Overall cable O.D. .47", Individual cable O.D. .12", individual cable lengths from strain relief 8".

Lengths Available

55-617-5.....5 ft.	55-617-9.....9 ft.
55-617-7.....7 ft.	55-617-12.....12 ft.




55-771G High Quality Low Loss SVHS Cable With Gold SVHS 4 pin Connectors

8mm shielded high quality SVHS cable terminated with Calrad 30-608 4-pin SVHS gold plated connectors. Miniature shielded 75 ohm video coax cable, 1-RED, 1-YELLOW. Cable O.D. 8mm/.315". Multi-strand tension baring filler for superb strength. Flexible .042" thick rubber jacket. Individual coax cable diameter .122". Individual foamed PE cable dielectric insulation, O.D. .087". Center conductor 24 awg. Nominal capacitance 16.9pf/ft. Shielding 95% braided copper. Dark gray PVC jacket. Custom lengths also available, please ask your Calrad sales representative for your specific needs.

55-771G-3.....3 ft.
55-771G-6.....6 ft.
55-771G-12.....12 ft.
55-771G-25.....25 ft.
55-771G-330.....Bulk Cable 330 ft.

Custom Lengths Available



SVHS 4 Pin Mini Din Pinout



55-770GR Round Jacketed SVHS Cable.

Black jacketed, double shielded, non-molded, black anodized Male to Male molded SVHS video cable. 65% 'OFC' braided copper over 100% foil shield, 7mm O.D.

55-770GR-3.....3 ft.
55-770GR-6.....6 ft.
55-770GR-10.....10 ft.
55-770GR-12.....12 ft.
55-770GR-15.....15 ft.
55-770GR-25.....25 ft.
55-770GR-50.....50 ft.
55-770GR-100.....100 ft.
55-770GR-500.....Bulk Cable 500 ft.



55-770G

Super-VHS Flat Cables. 4-Pin to 4-Pin Plug – Gold

Flexible S-VHS Cable. Low loss pro style cable for running long lengths. 75 ohm dual flat coax cable. 27 awg wire, spiral copper shielded with black PVC black jacket. molded connectors with gold plated contacts. Capacitance is 55pf/m (16.8pf/ft). Attenuation is approx. .06db/m at 10mHz. Shielded.

55-770G-1.....1 ft. flat cable
55-770G-3.....3 ft. flat cable
55-770G-6.....6 ft. flat cable
55-770G-10.....10 ft. flat cable
55-770G-12.....12 ft. flat cable
55-770G-15.....15 ft. flat cable
55-770G-20.....20 ft. flat cable
55-770G-25.....25 ft. flat cable
55-770G-30.....30 ft. flat cable
55-770G-50.....50ft. flat cable
55-770G-75.....75 ft. flat cable
55-770G-100.....100 ft. flat cable
55-770G-1000 1000 ft., spool flat cable . w/ no ends.



55-772G High Quality, Low Loss SVHS Cable with Gold SVHS Connectors, Silver Colored

Silver jacketed, triple shielded, High Quality non-molded SVHS video cable Male to Male. Dual miniature spiral shielded coax cables with 65% 'OFC' braided copper over 100% foil shield coverage, 8mm O.D.

55-772G-3.....3 ft.
55-772G-6.....6 ft.
55-772G-10.....10 ft.
55-772G-12.....12 ft.
55-772G-15.....15 ft.
55-772G-20.....20 ft.
55-772G-25.....25 ft.
55-772G-50.....50 ft.
55-772G-75.....75 ft.
55-772G-100.....100 ft.
55-772G-250.....Bulk Cable 250 ft.

Metal Connectors with Gold Contacts & Silver Finish



55-740G

Gold Plated SVHS 4-Pin Plug To Blunt Cut End

6 foot flat, shielded flexible S-VHS cable. Low loss pros style cable for running long lengths. 75 ohm dual flat coax cable. 27 awg wire, spiral copper shielded with black PVC jacket. Capacitance is 55pf/m (16.6pf/ft). Attenuation is approx. .06db/m at 10mhz. Gold plated SVHS connector



Plenum SVHS Cables Available Upon Request. Call Calrad for Details