CALRAD

40 Series - VGA Converters

40-885

COMPOSITE VIDEO TO VGA CONVERTER \ SCALER

The 40-885 is a composite video and S-Video to VGA converter/scaler. Composite video and S-Video inputs are scaled up to PC or HDTV resolutions through the OSD menu. Supports NTSC 3.58, NTSC 4.43. Pal-M, Pal-N and Secam formats. Output resolutions for PC are 640X480, 800X600, 1024X768 and 1280X1024. HDTV resolutions are 480P, 720P and 1080i. 5Vdc power supply included. Size: Length 5.25" x Width 3" x Height 1.25".



40-886

VGA TO DVI-D CONVERTER \ SCALER

The Calrad 40-886 converts VGA or Y, Pb, Pr component video to DVI-D. can interface between analog VGA and digital DVI-D signals while scaling up or down. The default DVI output resolution is set for 1024 X 768. A backup memory system saves and recalls the previous settings when power is applied. 5Vdc power supply included. Size: Length 5.75° x Width 3° x Height 1.25° .



40-40VC01

VGA TO COMPOSITE VIDEO CONVERTER (PAL-NTSC SUPPORT)

VGA to composite video converter provides a simple method to view PC based video on any TV, projector, or any other viewing device that uses standard BNC (RCA) type composite video connectors. The converter also features a VGA output port that allows for VGA Loop-Thru. You can simultaneously view video on a VGA monitor while viewing the video on your CRT ,TV monitor. Simple to use push button controls for video setup. Includes DC power supply and 6" M-M vga pigtail cable.

 $\begin{tabular}{ll} \textbf{OSD Features}: H-Size, V-Size, Brightness, Contrast, Hue, Saturation, Flicker, Sharpness, OSD Background. \end{tabular}$

Specifications

Supported video standards: NTSC/NTSC-EIAJ/PAL/PAL-M/PAL-N/SECAM. Supports Resolutions: 640×480 (up to 85 Hz), 800×600 (up to 85 Hz) and 1024×768 (up to 75 Hz).

Image controls: Horizontal and vertical size, brightness, contrast, hue, saturation, sharpness and on screen display background.

Input Signal: VGA (HDDB15 Female Jack)

Output Signal VGA Loop-Thru (HDDB15 Female Jack)

Output Signal Converted: (BNC Female Jack, Composite Video)

DC Power Coax Jack: 5Vdc, 500ma

Size: Length 3.75" x Width 4.75" x Height 1.25"







75-547BNC Male to RCA Female adapter, Not Included.