

CALRAD


40 Series - Security Switches

PLASTIC BALL PLUNGER SWITCH

Completely environmental proof for window, door protection, etc. Mounts in 3/4" hole. Mounting centers 1 3/16". Rating 100mA-100 Vdc max., 1 Amp-10 Vdc max., 10 watts max. 30" wired leads. Overall mounting depth 1.7".

40-670 Normally Closed

40-671 Normally Open and Normally Closed contacts (Both with ball depressed.)



40-672 ALUMINUM Z-BRACKET

Needed for extending magnet greater distances when uneven surfaces exist. Used for 40-750, 751, 752. Over-all length is 8". Long tongue is 5.75" and short tongue is 2.5".



40-676 LOW PROFILE PLASTIC BALL PLUNGER SWITCH

Completely environmental proof for window, door protection, etc. Mounts in 3/4" hole. Mounting centers 1 5/16". Rating 100mA-100 Vdc max., 1 Amp-10 Vdc max., 10 watts max. Normally closed switch with 18" leads. Overall mounting depth 1". Includes .1" plastic spacer.



40-663A SPST DOUBLE SIDED KEY SWITCHES

Sometimes called a shunt lock. Complete with 2 keys and mounting hardware. Hook up using screw terminals. Used with most alarm equipment and with all Calrad Alarm Modules. 125Vac, 4Amp. 250Vac, 2A. Mounts in 1.8" deep hole. Bushing length to connectors 1.8", Mounts in .75" hole.



40-654 TAMPER SWITCH

SPST momentary contact. Use in conjunction with most security devices. Normally closed (with plunger depressed). Contact rating .5 Amp-50 Vdc. Size is 1.84" long x 1.09" wide.



ROUND HIGH SECURITY KEYLOCK SWITCHES

Mounts in 3/4" hole. 1 11/16" deep. 3 Amp - 125V.

40-682 SPST Momentary, Spring Return
40-683 SPST Shunt On/Off Solder Terminals




40-652 HOLD-UP UNIT

Double button operation virtually eliminates accidental triggering. Sturdy metal case, silver plated SPST contacts. Prewired for quick installation. Color beige, contacts rated for 1 Amp @25Vdc. Size is 1.99"(W) x .99"(H) x 1.74"(D).



40-768 3/8" STUBBY RECESSED CONTACT WITH SCREW TERMINALS

5/8" long switch for tight installations with short mounting areas. Switch/magnet case with ribs for securing in holes, 5/16" operating gap. Closed circuit with magnet in place. Available in white only. 100mA 100Vdc max., 1A 10Vdc. Contact length is .78".



Small Slotted Screw Driver Required

40-758 SURFACE MOUNT TOGGLE SWITCH

SPST toggle switch mounted in a white impact housing. Mounting centers 2.125". Overall height 2", 6" black flying leads, stripped. Chrome switch position ID label ON/OFF. Current rating 3Amps @125Vac, 50Vdc.



40-769 3/8" RECESSED CONTACT WITH SCREW TERMINALS

Switch/magnet case with ribs for securing in holes, 5/8" operating gap. Closed circuit with magnet in place. Available in white only. 100mA 100Vdc max., 1Amp 10Vdc. Contact length is 1.32".



40-650 EMERGENCY PANIC SWITCH

3" long, 7/8" wide, 2 5/8" mounting centers. Normally open circuit. Screw terminals on the rear of switch for connection.

40-650A

Same as 40-650 only with normally open and closed options available.



40-673 PLASTIC NYLON HOLDER

Used for recessed mounting of contacts and magnets on steel doors. Holds magnet or contact in place away from frame. For use with our 40-659 contact, magnet. Hole size 3/4". Color: grey.



Visit Calrad on the Web at: www.calrad.com