CALRA

55 Series - Speaker & Hook-Up Wire

55-846 FLAT SPEAKER WIRE

2 conductor speaker wire for under carpets and anywhere thickness is a problem. All lengths come in non-terminated spools.

16 Gauge

55-846-2.5-25	16 Gauge, 25 ft
55-846-2.5-50	16 Gauge, 50 ft
55-846-2.5-100	16 Gauge, 100 ft



STRANDED HOOKUP WIRE

Red and black multi-purpose 2 conductor hookup wire. 16 Gauge

18 Gauge

	•
55-848-50	50 ft. (1.28 lbs)
55-848-100	100 ft (2.64 lbs)

55-847-50	50 ft. (0.94 oz)
55-847-100	100 ft (1.84 lbs)



SPEAKER WIRE

Clear jacket copper speaker 2 conductor wire.

Z CONDUCTOR WIFE.		
18 Gauge		
55-840-25	25 ft. (0.38oz)	
55-840-50	50 ft. (0.86 oz)	
55-840-100	100 ft. (1.7lbs)	
	500 ft. (8.0lbs)	
55-840-1000	1000 ft. Spools	
16 Gauge		
55-841-25	25 ft. (0.48 oz)	
55-841-50	50 ft. (1.24 lbs)	
55-841-100	100 ft. (2.3 lbs)	
	500 ft.	
55-841-1000	1000 ft (23 lbs)	

55-841-50	50 ft. (1.24 lbs)	
55-841-100	100 ft. (2.3 lbs)	
55-841-500	500 ft.	
55-841-1000	1000 ft. (23 lbs)	
14 Gauge		
55-842-25	25 ft. (0.84 oz)	

JJ-04Z-ZJ	25 IL (0.04 02)	
55-842-50	50 ft. (2.06 lbs)	
55-842-100	100 ft. (3.8 lbs	
55-842-500	500 ft. (20 lbs)	
55-842-1000	1000 ft. (40lbs)	
12 Gauge		
55-843-50	50 ft. (3.6 lbs)	

55-843-50	50 π.	(3.6 IDS),
55-843-100	100 ft.	(5.4 lbs)
55-843-500	.500 ft	(26 lbs)



55-849-2 14 gauge, 2 conductor
55-849-4 14 gauge, 4 conductor
55-850-2 16 gauge, 2 conductor
55-850-4 16 gauge, 4 conductor
55-851-2 18 gauge, 2 conductor
55-851-4 18 gauge, 4 conductor
CL3 speaker wire, UL approved.
Excellent for home or commercial
speaker installations. 500 ft. pull box.
Specify 2 or 4 conductors when
ordering.



ULTRAFLEX SPEAKER WIRE

Heavy duty copper speaker 2 conductor wire, very flexible.

12	Gauge	ļ
----	-------	---

55-844-50	50 ft. (3.56 lbs)
55-844-100	100 ft. (9 lbs)
55-844-500	500 ft.
10 Gauge	

5-845-100	100 ft. (11 lbs)
5-845-500	500 ft.



55-655 12 GAUGE 'OFC' **SPEAKER CABLE**

This low inductance and capacitance speaker cable accurately delivers the full power and frequency range of your receiver. Its larger, Oxygen Free Copper conductors are twisted to retard signal loss. Dark blue PVC rubber jacket with heavy gauge gold plated spade lugs with .25" openings. Solderable spade lugs available

separately, Calrad part number 30-655.



Pull Box

Lengths Available	
55-655-12	12 ft.
55-655-15	15 ft.
55-655-25	25 ft.
55-655-35	35 ft.
55-655B-100100 ft. Spe	ool Bulk Cable

