

CALRAD

95 Series - Security Accessories

95-823 TRIPLE LATCHING DOOR/GATE ACCESS

DIGITAL KEY PAD

Indoor digital keypad for door entry and gate access. Stainless steel face plate. Operating voltage 12-14VDC. Triple latching relays.




20-312 SIREN HORN

Same unit as 20-310 except features built-in siren amplifier. 30 Watts, Operates on 6-12 Vdc, our most powerful siren horn, has wiring for both steady and yelp siren operation. 120 dB at 6ft. Horn Dimensions: 4³/₄" x 8" x 9¹/₄" (deep), Color: white.



95-824 Heavy Duty Sealed Environment Surface Mount Weatherproof Self Contained Access Control Key pad

IEI 232SE Sealed Environment Surface Mounted Weatherproof Stand Alone Access Control / Door Shunt / Timered Flush Mounted Keypad with Expanded Programming Features. Code flexibility: Codes can be 4-8 digits.



Illuminated Buttons

6 / 8 / 10 INCH BELLS

Produces loud clear ring, will overcome most high background noises. UL approved.

95-882 6 inch, 12 Vdc, 82 dB, .06 amps

95-884 6 inch, 24 Vdc, 82 dB, .06 amps

95-888 8 inch, 12 Vdc, 85 dB, .06 amps

95-911 10 inch, 12 Vdc, 85 dB, .06 amps



95-950 RF REMOTE CONTROL SYSTEM

3 channel RF transmitter and receiver system with dry contact relay switching. Receiver requires 12Vdc. Channel 1 & 2 uses 2 amp relays, channel 3 provides neg. transistor output 500mA. 100'-150' range Used for garage door/gate access or interface with Calrad home/commercial security systems. Code encryption with over 1 million code combinations. Operates on 303MHz.




95-900 ELECTRONIC DUAL BEEPER HORN

Produces penetrating continuous or pulsating tone. Will operate on either 6 or 12 Vdc. Used in many alarm warning devices. Small in size, mounts into 1¹/₈" hole. Color: black. Size: 1"(H) x 1.5" (dia).



95-850 ELECTRONIC DOOR RELEASE UNIT

Operates on 10-14Vdc. Current draw 800mA. DC coil resistance 14 ohms. Comes with mounting screws. Mounting plate 6.25" x .99". Coil body 3.5"(H) x 8"(W) x 1.1"(H). Overall depth 1.25".



95-902 ELECTRONIC BEEPER HORN

Highly advanced, small in size, low in power consumption. Used in many alarm warning devices.

Specifications

Voltage..... 2 to 24 Vdc
Power Output..... 93 dB at 12 Vdc
Current..... 20 mA max.....
Size fits into 1¹/₈" hole or mount 1¹/₈" centers
Starting Voltage..... 1.0V max
Color Black
Size..... 1"(H) x 1" (dia).



95-889 ALARM SIREN

Operated from 6 to 12 Vdc. Siren is designed to produce a wobble type sound electrically with amplifier contained in housing. Output is approximately 124 dB ±2 dB, 12 Vdc, with sound pressure meter 10 ft. away. Rated operating current 1 Amp ±0.2 Amp at 12 Vdc. Color: black.



95-890 SELF-CONTAINED SIREN SPEAKER

High-powered, compact siren speaker. Produces loud, ear-piercing warble or steady tone. Operates on either 6 or 12 volts DC and draws only 400 mA of current. Easy-mounting and weather resistant. Color: white. Size: 4"(L) x 4"(W) x 2"(D).

