CALRAD

40 Series - USB PC Video Adapter

40-40AN2420 DVI-D, HDMI TO USB ADAPTER 40-40AN2440 DVI-, HDMI TO USB ADAPTER (SUPPORTS VIDEO UP TO 1680X1050)

This USB Display Adapter enables you to connect one more monitor, LCD or projector to a computer with a USB 2.0 port. For desktop users adding an extra monitor via USB connection is easier than ever without having to open the computer chassis to install an internal video card. Once the installation is done, the USB-attached monitor soon wakes up. No function key hassle to swap a second monitor.

With this handy adapter, you can enjoy many benefits brought by an add-on monitor. The most obvious one is that you get more desktop area to have more applications visible at one time. For example, you may work on one monitor while your family watch video on the other. No more stacking windows within the confines of a single display. Or you may span an application, e.g. spreadsheets, across two displays. What's more, the adapter is hot pluggable. If you are not using the extra monitor, just unplug the adapter at any time; no reboot needed.

Specifications: USB: Ver 2.0

Video Interface: DVI-I

Connectors: Video output: DVI-I 24pin + 5pin Female Connector Host upstream link: USB Mini-B Type Female Connector

Connectivity: Up to 2 adapters on a computer RAM: 8M x 16 DDR Synchronous DRAM (SDRAM)

Power Mode: Bus-powered

Operation System Suppor: Windows 2000 SP4, XP SP2 and Vista 32-bit

Supported Modes: Extended Desktop (Default), Mirrored Desktop, Primary Display Supported Resolutions: 640x480, 800x600, 1024x768, 1280x960, 1280x1024, 1360x768,

 $1366x768,\,1368x768,\,1400x1050,\,1440x900,\,1600x1200,\,1680x1050$

Housing: Plastic

Dimensions: 84.3 (L) x 54 (W) x17.8 (H) mm

USB Cable Separated from the body: Type: USB A -Type Male to 5pin Mini USB B-Type Male

Color: Black Length: 1M

Operating temperature: $10-40^{\circ}C$

Relative Humidity: < 85% non-condensing

EMC FCC Part 15 Class B, IC ICES-003 CE (EN55022, EN61000, EN55024)

RoHS: RoHS compliant



Package Contents

USB Display Adapter x1 Driver CD x1 USB Cable x1 Quick Installation Guide x1 DVI-A male to VGA female Adapter x 1

35-700 DVI-I Male to VGA DB-15 Female Adapter

Allows you to connect VGA display to a DVI-I graphics card. Note, this adapter does not provide a digital to analog signal conversion. It will not work with DVI-D, Included.



