

CALRAD


95 Series - AC Adapters, Power Strips

95-795 AC 3 WIRE GROUND ADAPTER

120 Vac - 20 amp rating. Rubber body.

95-795-UL POLARIZED AC 3 WIRE GROUND ADAPTER

120 Vac - 20 amp rating. Plastic body.



95-793 3-OUTLET SURGE PROTECTOR

270-joules. LED surge and ground fault indicator. UL/CSA listed. 125 Vac, 15 amp rating.



95-794 TRIPLE OUTLET ADAPTER

Converts 1 AC outlet to 3 outlets. 120 Vac - 15 amp rating.



95-783 6 OUTLET ADAPTER WITH SURGE PROTECTION (METAL)

1-mov, 90-joules basic protection. Resettable circuit breaker. Illuminated ON-OFF rocker switch. 4 ft., 14 awg heavy duty cord. Baked enamel ivory finish.



95-783-P (Straight AC Plug)

95-783-P-RT (Right Angle AC Plug)

6 OUTLET ADAPTER WITH SURGE PROTECTION (PLASTIC)

Provides protection against noisy AC power. MOV circuitry for reducing harmful power spikes and surges, reduces, RFI and EMI signals. On/Off power switch with 15A circuit breaker. 3 ft. 14 AWG, 3 prong AC cord. Maximum surge dissipation 59 joules. Maximum surge voltage 6000 volts. Maximum spike current 4500 amps. Response time less than 1 nanosecond. UL/CSA listed. High impact ABS plastic housing.



95-786 9 OUTLET MODEM/TV SURGE PROTECTOR

Child protected slide outlet covers suitable for DSS dish installation. 3 transformer spaced outlets. 6-mov, 840-joules. 3 Line protection. EMI-RFI noise filtered. Built-in resettable circuit breaker. ON-OFF illuminated rocker switch. LED surge and ground fault indicator. Surge fail audible alarm alert. 6 ft. 14 awg heavy duty power cord. UL/CSA listed. High impact ABS plastic housing.



95-788 8 OUTLET DBS SURGE PROTECTOR

TV-DSS surge protector used for DSS satellite installations. 3-class 2 transformer spaced outlets. 5-MOV 1680 joules, 3 line protection EMI-RFI noised filtered up to 60dB from 100KHz to 10MHz. Protects phone/fax/modem, satellite, cable coax connections. Illuminated breaker switch. L.E.D. surge and ground fault indicator. Surge fail audible alarm alert. 6 ft. 14 awg heavy duty power cord. Max surge voltage of 6500. 5-2250Mhz premium 'F' connectors. Child protected slide outlet covers. High impact ABS plastic housing. UL/CSA listed. UL497A, 1993, 1449. Size: 4.5"(W) x 1.74"(H) x 11.5"(D). Color is white.



95-785 6 OUTLET MODEM/FAX SURGE PROTECTOR

Child protected slide outlet covers. 3-mov, 270-joules. 3 Line protection. EMI-RFI noise filtered. Built-in resettable circuit breaker. ON-OFF illuminated rocker switch. LED surge and ground fault indicator. 6 ft. 14 awg heavy duty power cord. UL/CSA listed. High impact ABS plastic housing.



95-780 6 OUTLET HEAVY DUTY SURGE PROTECTOR WITH CORD MANAGEMENT

Comes with 6 outlets, 2 configured for power supplies and 4 standard spaced outlets. Integrated illuminated breaker switch. 14 AWG, 6 ft. grounded power cable. Built in mounting brackets and heavy duty steel housing UL/CSA approved. Color is yellow.



95-781 8 OUTLET HEAVY DUTY SURGE PROTECTOR WITH CORD MANAGEMENT

Comes with 8 outlets, 3 configured for power supplies and 5 standard spaced outlets. Integrated illuminated breaker switch. Built in mounting brackets, heavy duty steel housing. 14 AWG 6 ft. grounded power cable. UL/CSA approved. Color is yellow.



Visit Calrad on the web at: www.calrad.com