CALRAC

55 Series - Video/CCTV Cables

Technical drawings and specifications are available for these cables. Please ask your Calrad sales representative for details.

HIGH QUALITY VIDEO/CCTV RG174 CABLE

Designed for high flexibility and sharp cornered applications, this 75 ohm cable is perfect for areas where a low profile cable is needed. This is modeled after the Belden 8218 cable with comparable specifications. Available in three different configurations. Molded 75 ohm connectors with 95% shielded coax. Cable OD = 0.151".

BNC Male to Male 55-630-3......3 ft.

55-630-6	6 ft.
55-630-12	12 ft.
55-630-25	25 ft.
55-630-50	50 ft.
55-630-75	75 ft.
55-630-6 55-630-12 55-630-25 55-630-50 55-630-75 55-630-100	100 ft.



BNC TO RCA Male to	o Male
55-631-3	3 ft
55-631-6	6 ft

55-631-6	6 ft.
55-631-12	12 ft.
55-631-25	25 ft.
55-631-50	50 ft.
55-631-75	75 ft.
	100.5





RCA Male to Male

55-632-3	3 ft.
55-632-6	6 ft.
55-632-12	12 ft.
55-632-25	25 ft.
55-632-50	50 ft.
55-632-75	75 ft.
55-632-3 55-632-6 55-632-12 55-632-25 55-632-75 55-632-100	100 ft.



75 OHM COAX VIDEO/CCTV CABLE RG-59A/U

These 75-ohm RG59 coax interface cables have been designed for CCTV, broadcast video and any application where signal continuity needs to remain constant. They come with molded 75 Ohm BNC Male connectors with strain relief and a black PVC jacket to enhance wear in high use situations. The wire is 95% copper shielded.

BNC Male to Male

55-640-1.5	1.5 ft.
55-640-3	3 ft.
55-640-6	6 ft.
55-640-12	12 ft.
55-640-25	25 ft.
55-640-50	50 ft.
55-640-75	75 ft.
55-640-100	100 ft.



BNC to RCA Male to Male

55-641-1.5	1.5 ft.
55-641-3	3 ft.
55-641-6	6 ft.
55-641-12	12 ft.
55-641-25	25 ft.
55-641-50	50 ft.
55-641-75	75 ft.
55-641-100	100 ft.



RCA to RCA Male to Male 55-642-1.51.5 ft.

55-642-3	3 ft.
55-642-6	6 ft.
55-642-12	12 ft.
55-642-25	25 ft.
55-642-50	50 ft.
55-642-75	75 ft.
EE 642 100	100 ft



HIGH QUALITY VIDEO/CCTV RG174 CABLE

Designed for high flexibility and sharp cornered applications, this 75 ohm cable and connectors are perfect for areas where a low profile cable is needed. This is also modeled after the Belden 1855A cable with comparable specifications with molded 75 ohm connectors with 95% shielded coax. Cable OD = 0.151" CUL, CL2, CMR RATED





BNC Male to RCA Male 55-634-3.....3 ft. **55-634-6**......6 ft. **55-634-12**......12 ft. **55-634-25**......25 ft.



RCA Male to RCA Male 55-635-3......3 ft. **55-635-6**......6 ft. **55-635-12**......12 ft. **55-635-25**......25 ft.



BNC Male to BNC Male 55-633-3.....3 ft. **55-633-6**......6 ft. **55-633-12**......12 ft. **55-633-25**......25 ft.