



## Company Goal

Our goal is to provide our customers with quality fire extinguishers at a great value. In pursuit of this, we are proud to say that we manufacture all our products in the U.S.A. We mill and blend our own dry chemical agents, machine the component parts, assemble and then test our units to the highest quality standards.

*Third Party Approvals For Peace Of Mind*



## Key Features Of Buckeye Fire Extinguishers

- Manufactured to meet UL/ULC's rigorous standards for commercial hazard protection and backed by our manufacturer's warranty.
- Dry Chemical and Halotron extinguisher cylinders are constructed out of deep drawn and ironed carbon steel. Carbon Dioxide cylinders are constructed out of 6061 TG aluminum.
- Rechargeable.
- Anodized aluminum or plated brass valve assemblies for superior strength and corrosion resistance.
- The extinguisher nameplate incorporates trilingual operating and maintenance instructions, English, Spanish and French.
- Color-coded gauges show operating status at-a-glance.
- Extinguishers have model and serial number bar coding for easy and accurate maintenance history.
- Metal pull pins, vehicle brackets and wall hooks for extended unit service life.





## ABC Dry Chemical

ABC Dry Chemical is a multipurpose extinguishing agent that is suitable for use on Class A, Class B and Class C fires.

**Typical Uses:** For public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not recommended for use on sensitive electronic equipment or aircraft structure.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included.

Model	2.5 ABC V/B	5 ABC	5 ABC V/B	10 TALL ABC	10S ABC	20S ABC	30S ABC
Pt. # Alum. Valve	13315 (13390)	10914 (10990)	25614 (25690)	11340 (11390)	11310 (11320)	12120 (12195)	N/A
Pt. # Brass Valve	N/A	10915 (10995)	25615 (25695)	11341 (11349)	N/A	12121 (12196)	12905 (12915)
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	10 lb. (4.54 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)	30 lb. (13.6 kg)
UL/ULC Rating	1-A:10-B:C	3-A:40-B:C	3-A:40-B:C	4-A:80-B:C	4-A:60-B:C	10-A:120-B:C	10-A:160-B:C
Temperature Range	-65° to 120°F (-54° to 49°C)						
Discharge Time	9 sec	14 sec	14 sec	22 sec	18 sec	27 sec	32 sec
Discharge Range ft (m)	9-15 (2.7-4.6)	12-18 (3.7-5.5)	12-18 (3.7-5.5)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	25-30 (7.6-9.1)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
Mounting Type	Vehicle	Wall	Vehicle	Wall	Wall	Wall	Wall
USCG Approval	Type B:C Size I	Type A Size II Type B:C Size I	Type A Size II Type B:C Size I	Type A Size II Type B:C Size II	Type A Size II Type B:C Size II	Type A Size II Type B:C Size III	Type A Size II Type B:C Size IV
Ship Weight	5.5 lb. (2.5 kg)	10 lb. (4.5 kg)	10.25 lb. (4.7 kg)	18.25 lb. (8.3 kg)	18.75 lb. (8.6 kg)	33.5 lb. (15.2 kg)	52.25 lb. (23.7 kg)
Unit Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	16.75 in (42.5 cm)	21.25 in (53.8 cm)	27.375 in (69.4 cm)
Unit Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.25 in (21 cm)	8.75 in (22.2 cm)	8.75 in (22.2 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	6 in (15.2 cm)	7.5 in (19.1 cm)	7.5 in (19.1 cm)



## Standard Dry Chemical

Standard (BC) Dry Chemical is a sodium bicarbonate based extinguishing agent that is suitable for use on Class B and Class C fires.

**Typical Uses:** For flammable liquid hazards in public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For flammable liquid hazards in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included.

Model	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD	20S STD
Pt. # Alum. Valve	13415 (13490)	11014 (11090)	13514 (13581)	11840 (11890)	12220 (12290)
Agent Capacity	2.5 lb. (1.13 kg)	5.5 lb. (2.5 kg)	5.5 lb. (2.5 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)
UL/ULC Rating	10-B:C	40-B:C	40-B:C	40-B:C	120-B:C
Temperature Range	-65° to 120°F (-54° to 49°C)				
Discharge Time	9 sec	14 sec	14 sec	14 sec	28 sec
Discharge Range ft (m)	9-15 (2.7-4.6)	12-18 (3.7-5.5)	12-18 (3.7-5.5)	15-21 (4.6-6.4)	15-21 (4.6-6.4)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
Mounting Type	Vehicle	Wall	Vehicle	Wall	Wall
USCG Approval	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III
Ship Weight	5.5 lb. (2.5 kg)	10.5 lb. (4.8 kg)	10.75 lb. (4.9 kg)	18.25 lb. (8.3 kg)	33.5 lb. (15.2 kg)
Unit Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	21.25 in (53.8 cm)
Unit Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.75 in (22.2 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)



## Purple K Dry Chemical

Purple K Dry Chemical is a high performance extinguishing agent most effective for dealing with flammable liquid fires. Purple K is suitable for use on Class B and Class C fires.

**Typical Uses:** For flammable liquid hazards in public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For flammable liquid hazards in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included.

Model	2.5 PK V/B	5 PK	5 PK V/B	10 PK	205 PK	305 PK
Pt. # Alum. Valve	13515 (13590)	11214 (11290)	25914 (25915)	11740 (11790)	12620 (12690)	N/A
Pt. # Brass Valve	N/A	N/A	N/A	N/A	12621 (12691)	12805 (12815)
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)	30 lb. (13.6 kg)
UL/ULC Rating	10-B:C	20-B:C	20-B:C	80-B:C	120-B:C	160-B:C
Temperature Range	-65° to 120°F (-54° to 49°C)					
Discharge Time	9 sec	9 sec	9 sec	22 sec	27 sec	32 sec
Discharge Range ft (m)	9-15 (2.7-4.6)	12-18 (3.7-5.5)	12-18 (3.7-5.5)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	25-30 (7.6-9.1)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
Mounting Type	Vehicle	Wall	Vehicle	Wall	Wall	Wall
USCG Approval	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III	Type B:C Size IV
Ship Weight	5.5 lb. (2.5 kg)	10 lb. (4.5 kg)	10.25 lb. (4.7 kg)	18.25 lb. (8.3 kg)	33.5 lb. (15.2 kg)	52.25 lb. (23.7 kg)
Unit Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	21.25 in (53.8 cm)	27.375 in (69.4 cm)
Unit Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.75 in (21 cm)	8.75 in (22.2 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)	7.5 in (19.1 cm)



## Halotron

Halotron is a clean, non conductive gaseous agent that is an excellent replacement for Halon 1211 extinguishers. Halotron is suitable for use on Class A, Class B and Class C fires.

**Typical Uses:** For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included. F = Fixed Nozzle. H = Hose.

Model	2.5F	2.5F V/B	2.5H	2.5H V/B	5F	5F V/B	5H	5H V/B	11	15
Pt. # Alum. Value	70258 (70280)	70251 (70295)	70259 (70260)	70256 (70265)	70510 (70580)	70550 (70590)	75550 (75560)	75555 (75565)	71100 (71180)	71550 (71580)
Pt. # Brass Value	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	71101 (71181)	71551 (71581)
Agent Capacity	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	5.5 lb. (2.49 kg)	5.5 lb. (2.49 kg)	11 lb. (5 kg)	15.5 lb. (7.03 kg)
UL/ULC Rating	2-B:C	2-B:C	2-B:C	2-B:C	5-B:C	5-B:C	5-B:C	5-B:C	1-A-10-B:C	2-A-10-B:C
Temperature Range	-40° to 120°F (-40° to 49°C)									
Discharge Time	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	9 sec	13 sec
Discharge Range ft (m)	6-10 (1.8-3)	6-10 (1.8-3)	6-10 (1.8-3)	6-10 (1.8-3)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	9-15 (2.7-4.5)	12-18 (3.7-5.5)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	100 psi (689 kPa)	125 psi (862 kPa)
Mounting Type	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall	Vehicle	Wall	Wall
USCG Approval	N/A	N/A	N/A	N/A	N/A	Type B:C Size I	N/A	Type B:C Size I	Type B:C Size I	Type B:C Size II
Ship Weight	5.25 lb. (2.4 kg)	5.5 lb. (2.49 kg)	5.5 lb. (2.49 kg)	5.75 lb. (2.6 kg)	9.25 lb. (4.2 kg)	9.5 lb. (4.3 kg)	10.0 lb. (4.5 kg)	10.25 lb. (4.7 kg)	21.25 lb. (9.6 kg)	25.75 lb. (11.75 kg)
Unit Height	13.375 in (34 cm)	13.375 in (34 cm)	13.375 in (34 cm)	13.375 in (34 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	17.5 in (44.5 cm)	17.5 in (44.5 cm)
Unit Width	5.625 in (14.3 cm)	5.625 in (14.3 cm)	6.75 in (17.1 cm)	6.75 in (17.1 cm)	6.5 in (16.5 cm)	7.25 in (18.5 cm)	6.5 in (16.5 cm)	7.25 in (18.5 cm)	8.625 in (21.9 cm)	8.625 in (21.9 cm)
Unit Diameter	3.375 in (8.6 cm)	3.375 in (8.6 cm)	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	7 in (17.8 cm)	7 in (17.8 cm)



## Carbon Dioxide

Carbon Dioxide is the trusted non-conductive clean agent and is most effective for dealing with electronic equipment fires. CO<sub>2</sub> is suitable for use on Class B and Class C fires.

**Typical Uses:** For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Recommended for use on sensitive electronic equipment.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses.

Model	5CD	10CD	15CD	20CD
Pt. #	45100 (45191)	45600 (45691)	46100 (46191)	46600 (46691)
Agent Capacity	5 lb. (2.27 kg)	10 lb. (4.54 kg)	15 lb. (6.8 kg)	20 lb. (9.07 kg)
UL/ULC Rating	5-B:C	10-B:C	10-B:C	10-B:C
Temperature Range	-22° to 120°F (-30° to 49°C)			
Discharge Time	9 sec	9 sec	15 sec	20 sec
Discharge Range ft (m)	4-8 (1.2-2.4)	4-8 (1.2-2.4)	4-8 (1.2-2.4)	4-8 (1.2-2.4)
Mounting Type	Wall	Wall	Wall	Wall
USCG Approval	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II
Ship Weight	13.75 lb. (6.3 kg)	27.75 lb. (12.6 kg)	37.75 lb. (17.1 kg)	49 lb. (22.2 kg)
Unit Height	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in (67 cm)	26.875 in (68.2 cm)
Unit Width	8.25 in (21 cm)	12 in (30.5 cm)	12 in (30.5 cm)	13 in (33 cm)
Unit Diameter	5.25 in (13.3 cm)	6.89 in (17.5 cm)	6.89 in (17.5 cm)	8 in (20.3 cm)



## Water And Water Mist

Our Water and Water Mist units provide effective and economical protection for common combustible fires.

Both the Water and Water Mist extinguishers have Schrader Valves incorporated into the Valve Assemblies for easy recharge.

The Water Mist unit uses deionized water and incorporates a unique spray nozzle. These features make it safe for use on energized electrical equipment. Water Mist is considered to be the #1 extinguisher choice for libraries and hospitals.

Water extinguishers are suitable for use on Class A fires. Water Mist is suitable for use on both Class A and Class C fires.

**Typical Uses:** For common combustible fires in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For common combustible fires in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/ aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.



Model	500	WM250
Part #	50000 (50000 ULC)	51000 (51000 ULC)
Cylinder/Valve Material	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
Agent Capacity	2.5 gallons (9.6 liters)	2.5 gallons (9.6 liters)
UL/ULC Rating	2-A	2-A:C
Temperature Range	40° to 120°F (4.4° to 49°C)	40° to 120°F (4.4° to 49°C)
Discharge Time	50 sec	73 sec
Discharge Range	45 to 55 ft. (13.7 to 16.8m)	5 to 10 ft. (1.5 to 3m)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)
Mounting Type	Wall	Wall
USCG Approval	Type A Size II	N/A
Ship Weight	Empty: 8.3 lb. (3.7 kg)	Full: 30.25 lb. (13.7 kg)
Unit Height	24.5 in (62.2 cm)	28 in (78.1 cm)
Unit Width (Incl. Hose)	9 in (22.9 cm)	14 in (35.6 cm)
Unit Diameter	7 in (17.8 cm)	7 in (17.8 cm)

Third Party Approvals For Peace Of Mind





### Wet Chemical - Class K

Our Wet Chemical extinguishers contain a blend of Potassium Acetate and Potassium Citrate that is extremely effective in suppressing high temperature fires involving cooking oils and grease.

The units incorporate a spray nozzle that ensures the agent is applied gently to the burning oil thus preventing splashing. It's unique cooling properties deliver exceptional heat absorption ensuring the fire remains out.

Wet Chemical is suitable for use on Class A and K fires.

**Typical Uses:** For protecting cooking oil and grease fires in commercial kitchens. This extinguisher is designed to complement existing pre-engineered hood systems.



Canadian Part Number is shown in parentheses.

Model	WC-6 LITER	WC-2.5 Gallon
Part #	50006 (50006ULC)	50025 (50025ULC)
Cylinder/Valve Material	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
UL/ULC Rating	1-A:K	1-A:K
Temperature Range	40° to 120° (4.4° to 49°C)	40° to 120° (4.4° to 49°C)
Discharge Time	54 secs.	74 secs.
Mounting Type	Wall	Wall
Ship Weight	22.75 lb. (10.3 kg)	30 lb. (13.6 kg)
Unit Height	19.25 in (48.9 cm)	24.5 in (62.2 cm)
Unit Width (incl. hose)	9 in (22.9 cm)	9 in (22.9 cm)
Cylinder Diameter	7 in (17.8 cm)	7 in (17.8 cm)



Used in conjunction with Kitchen Mister Fire Suppression System. Page 20 & 21.

Third Party Approvals For Peace Of Mind







<b>Model</b>	<b>30D</b>
<b>Part #</b>	52000
<b>Agent Capacity</b>	30 lb. (13.6 kg)
<b>FM Rating</b>	D
<b>Discharge Time</b>	28 sec
<b>Operating Pressure</b>	195 psi (1344 kPa)
<b>Mounting Type</b>	Wall
<b>USCG Approval</b>	N/A
<b>Ship Weight</b>	55 lb. (24.95 kg)
<b>Unit Height</b>	33 in (83.8 cm)
<b>Unit Width (Incl Hose)</b>	16 in (40.6 cm)
<b>Unit Diameter</b>	8 in (20.3 cm)



## Combustible Metals - Class D

Specifically designed for use on combustible metal fires, this extinguisher features a discharge assembly that keeps the operator at a safe distance while providing accurate application of the agent on the fire.

From the heat of the fire, the sodium chloride based agent forms a crust to exclude air from the burning material. Suitable for use on Class D fires such as those involving magnesium, sodium, potassium and sodium-potassium alloys.

There is data showing that zirconium, uranium, titanium, and powdered aluminum fires can be controlled and extinguished with this unique extinguisher.

**Typical Uses:** Metal production and machining operations.





## Automatic Spot Protection

### Vertical Mini-Guards

Designed for single unit installations, the Buckeye Fire Equipment Mini-Guard automatic spot protection extinguishers provide supplementary fire protection suitable for some local and total flood applications. These units are not intended as a substitute for automatic sprinkler systems, fixed pre-engineered or engineered extinguishing systems and are not intended to be multiple mounted.

The Mini-Guard automatic spot protection extinguishers are designed, constructed, and tested to the same engineering standards as our portable fire extinguishers. Available in horizontal or vertical configurations, the units can be charged with multipurpose (ABC) dry chemical or Halotron agents and are fitted with a detection sprinkler head that is rated at 165° F.

**Typical Uses:** The dedicated protection of specialized equipment used in business or manufacturing processes or for specific fire risk areas such as flammable liquid storage rooms (dry chemical) and small electronic data storage rooms (Halotron).



Model	MULTIPURPOSE (ABC) DRY CHEMICAL				HALOTRON	
Agent Type	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	Halotron I	Halotron I
Part #	80250	80501	81001	82001	87100	87200
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.3 kg)	10 lb. (4.5 kg)	20 lb. (9.1 kg)	18 lb. (8.2 kg)	25 lb. (11.3 kg)
Ship Weight	4 lb. (1.8 kg)	11 lb. (5 kg)	19 lb. (8.6 kg)	36 lb. (16.3 kg)	29 lb. (13.2 kg)	42 lb. (19 kg)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	100 psi (689 kPa)	100 psi (689 kPa)
Unit Length	15.25 in (38.7 cm)	17.25 in (43.8 cm)	17.625 in (44.8 cm)	21.875 in (55.6 cm)	17.875 in (45.4 cm)	21.875 in (55.6 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	6 in (15.2 cm)	7.5 in (19.1 cm)	7 in (17.8 cm)	7.5 in (19.1 cm)
Max Total Flood Volume	120 cu. ft.	180 cu. ft.	1300 cu. ft.	2184 cu. ft.	500 cu. ft.	700 cu. ft.
Max Total Flood Height Above Hazard	7.5 ft.	7.5 ft.	13 ft.	14 ft.	8 ft.	10 ft.
Local Application Coverage Areas	4 ft. x 4 ft.	4 ft. x 6 ft.	10 ft. x 10 ft.	12 ft. x 13 ft.	4 ft. x 4 ft.	6 ft. x 6 ft.

Maximum Local Application - Height Above Hazard = 4 Feet for all Models



## Automatic Spot Protection

### Horizontal Mini-Guards

Designed for single unit installations, the Buckeye Fire Equipment Mini-Guard automatic spot protection extinguishers provide supplementary fire protection suitable for some local and total flood applications. These units are not intended as a substitute for automatic sprinkler systems, fixed pre-engineered or engineered extinguishing systems and are not intended to be multiple mounted.



The Mini-Guard automatic spot protection extinguishers are designed, constructed, and tested to the same engineering standards as our portable fire extinguishers. Available in horizontal or vertical configurations, the units can be charged with multipurpose (ABC) dry chemical or Halotron agents and are fitted with a detection sprinkler head that is rated at 165° F.

**Typical Uses:** The dedicated protection of specialized equipment used in business or manufacturing processes or for specific fire risk areas such as flammable liquid storage rooms (dry chemical) and small electronic data storage rooms (Halotron).

**Note:** Requires a heavy duty bracket for mounting (sold separately, see page 24).

Model	MULTIPURPOSE (ABC) DRY CHEMICAL				HALOTRON	
Agent Type	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	ABC Dry Chemical	Halotron I	Halotron I
Part #	80251	80521	81021	82021	87105	87205
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.3 kg)	10 lb. (4.5 kg)	20 lb. (9.1 kg)	18 lb. (8.2 kg)	25 lb. (11.3 kg)
Ship Weight	4 lb. (1.8 kg)	11 lb. (5 kg)	19 lb. (8.6 kg)	36 lb. (16.3 kg)	29 lb. (13.2 kg)	42 lb. (19 kg)
Operating Pressure	100 psi (689 kPa)	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	100 psi (689 kPa)	100 psi (689 kPa)
Unit Length	14.25 in (36.2 cm)	17.25 in (43.8 cm)	20.875 in (53 cm)	21.875 in (55.6 cm)	17.875 in (45.4 cm)	21.875 in (55.6 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)	7 in (17.8 cm)	7.5 in (19.1 cm)
Max Total Flood Volume	120 cu. ft.	180 cu. ft.	1300 cu. ft.	2184 cu. ft.	500 cu. ft.	700 cu. ft.
Max Total Flood Height Above Hazard	7.5 ft.	7.5 ft.	13 ft.	14 ft.	8 ft.	10 ft.
Local Application Coverage Areas	4 ft. x 4 ft.	4 ft. x 6 ft.	10 ft. x 10 ft.	12 ft. x 13 ft.	4 ft. x 4 ft.	6 ft. x 6 ft.
Mounting Bracket	700287	700270	700226	700229	700228	700229

Maximum Local Application - Height Above Hazard = 4 Feet for all Models



## Wheeled Halotron

Our Wheeled Halotron units are designed to deliver exceptional performance whatever the environment. DOT/TC approved cylinders, rugged frames and semi-pneumatic tires are key features of these UL/ULC approved extinguishers. Tow Loops can be added upon request.

Halotron is a residue-free, non-conductive agent that is suitable for use on Class A, Class B and Class C fires.

**Typical Uses:** For protecting sensitive electronic equipment in research facilities, vehicle/aircraft/marine service centers, and flight lines.

Third Party Approvals For Peace Of Mind



Canadian Part Numbers are shown in parentheses.

Model	W-65	W-150
Part #	76500 (76505)	71500 (71505)
Agent Capacity	65 lb. (29.5 kg)	150 lb. (68 kg)
UL/ULC Rating	4-A:40-B:C	10-A:80-B:C
Discharge Time	17 sec	23 sec
Operating Temperature Range	-40° to 120°F (-40° to 49°C)	-40° to 120°F (-40° to 49°C)
Range	15-25 ft. (4.6-7.6 m)	23-36 ft. (7-10.7 m)
Unit Weight	252 lb. (114 kg)	396 lb. (180 kg)
Unit Height x Width x Depth	50" x 24" x 41.5" (127 x 61 x 105 cm)	62" x 24" x 41.5" (157.5 x 61 x 105 cm)
Hose Diameter & Length	.75 in x 25 ft. (1.9 cm x 7.6 m)	1 in x 40 ft. (2.5 cm x 12.2 m)





### Wheeled Carbon Dioxide

Our Wheeled Carbon Dioxide extinguishers are designed for one-man operation and are constructed with spun steel cylinders and plated brass valve assemblies. DOT/TC approved cylinders, rugged frames and solid rubber tires are key features of these UL/ULC approved units.

Carbon Dioxide is a residue-free agent and is suitable for use on Class B and Class C fires.

**Typical Uses:** For protecting sensitive electronic equipment in refineries, shipboard, laboratories, construction sites, chemical plants and manufacturing facilities.

Third Party Approvals For Peace Of Mind



Model	C-50-SE	C-100-SE
Part #	35050 (35091)	35100 (35191)
Agent Capacity	50 lb. (22.68 kg)	100 lb. (45.36 kg)
UL Rating	20-B:C	20-B:C
USCG Approval	Type B:C Size IV	Type B:C Size V
Operating Temperature Range	-22° to 120°F (-30° to 49°C)	-22° to 120°F (-30° to 49°C)
Discharge Time	40 sec	80 sec
Range	15 ft. (4.6 m)	15 ft. (4.6 m)
Unit Weight	286 lb. (130 kg)	416 lb. (189 kg)
Unit Height x Width x Depth	60" x 31" x 21" (152.4 x 76.2 x 53.3 cm)	65" x 30" x 21" (165.1 x 76.2 x 53.3 cm)
Hose Diameter & Length	.50 in x 15 ft. (1.27 cm x 4.6 m)	.50 in x 40 ft. (1.27 cm x 12.2 m)





## Kitchen Mister - Restaurant Fire Suppression System

### Tested & Listed To UL-300

Open flames, red-hot cooking surfaces, and a heavily grease-laden environment combine to make the modern commercial kitchen a potentially dangerous fire hazard. Kitchen fires spread quickly and have proven to be very difficult to extinguish, making them the leading cause of structural fire damage in the United States.

Protecting the modern commercial kitchen from the ever-present danger of cooking oil and grease fires is the reason we developed The Buckeye Kitchen Mister™ System. Utilizing state of the art misting technology, the Kitchen Mister System has proven to be the most effective fixed kitchen fire extinguishing system ever developed, extinguishing potentially deadly kitchen fires fast, before they can spread

That's why the Kitchen Mister System is quickly becoming the preferred choice of fire protection professionals throughout the world.

So before fire strikes...**Don't Take Chances -Demand The Best!**

See our companion product (Wet Chemical Class K Portable) used in conjunction with our *Kitchen Mister* System. Page 11.



### System Cylinders

The models BFR-5, BFR-10, BFR-15 and BFR-20 cylinders are designated by flow point capacity (so the BFR-5 supports five (5) flow points) instead of the amount of agent they hold. Recharge is available in 5 and 10 flow point containers so there's never a chance of error.



### Buckeye Shielded Cable

The Kitchen Mister Shielded Cable Interface is used to connect Buckeye Shielded Cable to any standard 1/2 inch conduit connection device. The use of Buckeye Shielded Cable instead of conduit and corner pulleys for connecting the gas valve, remote pull station, and fusible link line to the Systems Releasing Module reduces installation time by up to 50%.

### Listings And Approvals


- Listed by Underwriters Laboratories, Inc. (Standard UL-300)
- Listed by Underwriters Laboratories of Canada, Inc.
- Approved by the New York City Fire Department COA #5550
- Complies with NFPA-96 and NFPA-17A Standards

Third Party Approvals For Peace Of Mind





## Kitchen Mister - Protect with the best & install for less.



### Simplicity Of Design

The constant changes and complicated requirements of most restaurant systems have made design and installation errors a concern of fire protection professionals globally.

The uncomplicated design of the *Kitchen Mister™* System all but eliminates design and installation errors by combining common sense features and the elimination of confusing design requirements.

### Faster Installations

By eliminating the labor-intensive task of installing conduit, corner pulleys, and detector brackets, the *Kitchen Mister System* dramatically reduces installation time.

The *Kitchen Mister System* is approved for use with Buckeye Shielded Cable instead of traditional conduit and corner pulleys for all system inputs and outputs. This, combined with the elimination of conduit and fusible link brackets in the plenum area, makes installing the *Kitchen Mister System* quick and easy.

### Discharge Nozzles

All five (5) *Kitchen Mister* nozzles come equipped with a color identification band, red, blue, green, white or yellow. This allows for easy identification of the nozzle even when it's installed in difficult locations such as a duct or plenum area. The nozzle is also stamped with its model number.

- 1 No Conduit Required**  
By using Buckeye Shielded Cable no conduit is required for system inputs/outputs. Buckeye Shielded Cable is Listed for the gas valve, detection line, and pull station.
- 2 No Conduit & Only One Anchor Bracket In Hood**  
The *Kitchen Mister System* eliminates the need for conduit in the plenum and requires only one anchor bracket in the exhaust hood.
- 3 No Corner Pulleys Required**  
Buckeye Shielded Cable eliminates the need for corner pulleys, making installation easy and fast.
- 4 Color-Coded Nozzles**  
All *Kitchen Mister* nozzles have a unique color band for easy identification.

### Dealer Friendly Features

- Uncomplicated system design eliminates design and installation errors.
- Installation time significantly reduced.
- Innovative design eliminates conduit and corner pulleys.
- Advanced detection system installs quickly and easily.
- Color-coded nozzles for easy identification.
- Flexible piping requirements allow for unlimited system configurations.
- Best coverage in the industry.
- Online & face to face training.



## Maximum Protection for Every Application



## Foam Concentrates And Equipment

Buckeye Fire Equipment manufactures a complete line of foam agents and hardware that when used in conjunction with one another make an unbeatable fire-fighting combination.

The selection includes bladder tanks, balanced pressure pump skid paks, eductors, monitors, foam chambers, foam makers, high expansion foam generators, foam carts and handline nozzles.

Many of the components can be customized to provide optimal protection for your unique situation. All foam system components are precision made from rugged materials to provide years of dependable service.

### Buckeye's Foam Team Delivers

- The widest selection of Earth-Friendly fire fighting foam concentrates in the industry. Foam concentrates that independent tests have proven to be superior in quality and performance\*.
- A wide selection of foam proportioning hardware and agents designed to maximize performance.
- Knowledgeable, professional in-house foam system design expertise to assist with your fire suppression equipment choice.

*\* Independent tests conducted by Chevron Petroleum and Dow Chemical. Report available on request.*



Foam Monitors



Foam Bladder Tanks



Hi-Ex Generators



Foam Concentrate Proportioners



Diesel Pump Skids





## Foam Concentrates

### Protecting the Environment

In addition to delivering superior reliability, Buckeye foam concentrates are all manufactured without EPA reportable components, thus reducing environmental impact.

By using only Earth-Friendly components, we relieve you of the major problems and burdensome paperwork that can result from the discharge of other foam concentrates. This environmental commitment in no way dilutes the fire-fighting effectiveness of Buckeye products.

Every foam concentrate we manufacture is subjected to rigorous quality control standards and comprehensive testing to ensure complete reliability and maximum fire fighting performance.



Foam Concentrate	Model Designation	Part Number 5 Gallon	Part Number 55 Gallon	Part Number 275 Gallon	Listing/ Approvals
Platinum 1% AFFF	BFC-1.1	50325	50330	50335	UL/FM Approved
Platinum 3% AFFF	BFC-3.1	50340	50345	50350	UL/FM Approved
6% AFFF	BFC-6.1	50130	50135	50140	UL
Platinum 3% x 3% AR-AFFF	BFC-33.1	50355	50360	50365	UL/FM Approved
Platinum 3% x 6% AR-AFFF	BFC-36.1	50385	50370	50375	UL
3% Low Temp AFFF	BFC-3LT	50115	50120	50125	UL
3%- 6% Low Temp AR-AFFF	BFC-36LT	50205	50210	50215	Buckeye Quality Assurance
Platinum Class A	BFC-CA.1	50190	50195	50200	USDA Forest Service QPL
2.2% High Expansion	BFC-HX	50235	50240	50245	UL
3% Mil Spec AFFF	BFC-3MS	50285	50290	50295	U.S. Navy QPL (Mil-F-24385)/UL
Virtual Foam	BFC-VF	50415	50420	50425	Buckeye Quality Assurance



### Dry Chemical



**Purple K**  
Pt. # 61200



**ABC**  
Pt. # 61000



**Standard (BC)**  
Pt. # 61400

Also Available For Class D  
Pt. # 62000

50 lb Containers

### Recharge Agents

Buckeye Fire Equipment carries a full line of extinguishing agent recharge products. Maintain the UL Listing and ensure optimal performance of your Buckeye Fire Equipment products by recharging with our high quality agents, agents made to the same standards and tested to the same requirements as the originals.

See Page 23 for Foam Agents.

### Wet Chemical Class K



**6 Liter Container**  
Pt. # 600872

### Water Mist




**2.5 Gallon Container**  
Pt. # 600910

### Halotron I



**40 lb. - Pt. # 64040**  
**150 lb. - Pt. # 64150**  
**200 lb. - Pt. # 64200**



**2.5 Gallon Container**  
Pt. # 600871



## Wall Hooks



Pt. # 700202



Pt. # 700203



Pt. # 700204



Pt. # 700247



Pt. # 700249



Pt. # 900935  
Pt. # 900937

Part Number	Suitable for Typical Extinguisher Sizes	Reference Diameter
700202	2.5 lb., 5 lb. & 5.5 lb. Dry Chemical and Halotron	3.25 - 4.25 inches
700203	10 lb. Tall Dry Chemical and 5 lb. CO2	4.75 - 5.5 inches
700204	10 lb. Short Dry Chemical	5.0 - 6.5 inches
700247	20 lb. & 30 lb. Dry Chemical, 10 lb. & 15 lb. CO2, 11 lb. & 15 lb. Halotron	6.75 - 7.5 inches
700249	20 lb. CO2	7.5 - 8.0 inches
900935	Wet Chemical & Water	7.0 inches
900937*	Water Mist	7.0 inches

\*Stainless Steel



## Marine/Vehicle Brackets

Buckeye Fire Equipment manufactures strong and durable mounting hardware for all our portable fire extinguishers.

Whether you are looking for vehicle or marine vessel mounting, or simply to mount on a wall, you can be sure that all our brackets and wall hooks are designed to keep your Buckeye fire extinguisher secure and readily accessible.



Pt. # 700287



Pt. # 700270



Pt. # 700260



Pt. # 700430



Pt. # 700224

Pt. # 700226

Pt. # 700228

Pt. # 700229

Pt. # 700230

Part Number	Model	Suitable for Typical Extinguisher Sizes	Reference Diameter
700287	A-2	2.5 lb. Dry Chemical, Halotron & MiniGuard (horizontal)	3.375 inches
700270	A-6	5 lb. & 5.5 lb. Dry Chemical, Halotron & MiniGuard (horizontal)	4.25 inches
700260	B-6	5 lb. & 5.5 lb. Dry Chemical and Halotron	4.25 inches
700430	B-12	10 lb. Tall Dry Chemical	5.125 inches
700224	5DC	5 lb. & 5.5 lb. Dry Chemical, Halotron & MiniGuard (horizontal)	4.25 inches
700226	809	10 lb. Tall Dry Chemical, MiniGuard (horizontal) and 5 lb. CO2	5.0 - 5.25 inches
700228	810	10 lb. & 15 lb. CO2. 11 lb. & 15 lb. Halotron. 2.5 gal Water, Water Mist and Wet Chemical (6 liter and 2.5 gallon)	6.5 - 7.25 inches
700229	811	20 lb. & 30 lb. Dry Chemical, 30 lb. Class D., 20 lb. CO2 18 lb, 20 lb & 25 lb MiniGuard (horizontal).	7.0 - 8.0 inches
700230	812	10 lb. Short Dry Chemical	6.0 - 6.25 inches