



SFS-O-DI

- For de-icing use
- 1.0" NPSH free swivel base (optional rigid base)
- Selectable flow rates of 10, 20 or 30 gpm (38, 78 or 114 lpm) @ 100 psi (6.89 bar)
- Aluminum/bronze handle construction; tab handle (standard), horseshoe handle (optional)
- Combined chrome-plated brass and Elk-O-Lite® construction
- Usable with de-icing and anti-icing fluids in Type I systems
- Pistol grip available (SFS-OG-DI)



222-1.5

- Wat-R-Wall
- 1.5" free swivel inlet, no outlet
- 100 gpm (380 lpm) @ 100 psi (6.89 bar)
- Brass construction with chrome plating
- Length: 8"
- Width: 10"
- Height: 7.25"
- Weight: 8 lbs.



222-2.5

- Wat-R-Wall
- 2.5" free swivel inlet, 2.5" outlet with cap and chain
- 100 gpm (380 lpm) @ 100 psi (6.89 bar)
- Brass construction with chrome plating
- Length: 8.25"
- Width: 10"
- Height: 8.25"
- Weight: 11.5 lbs.



199

- For sewer use
- 2.5" free swivel base
- 275 gpm (1041 lpm) @ 100 psi (6.89 bar)
- Brass construction
- Includes a replaceable steel cutting blade tool



184

- For street cleaning/flushing use
- 2.5" NPSH base
- 300 gpm (1136 lpm) @ 100 psi (6.89 bar)
- Brass construction
- Available in right, left or center mounting (*specify*)