

Wyes

Used to divide a single flow, usually at a fireground scene, wyes must be both reliable and intuitive to use. Elkhart offers several customizable handle options. All Elkhart wyes give years of dependable service. When necessary, they are easy to field service and re-buildable for continued long-term use.

Both 2-way and 3-way wye options available.



APPLIANCES







WYES

APPLIANCES







4-11

INLET SIZE	OUTLET SIZE (MALE)					TYPE	HANDLE STYLE				MATERIAL/TRIM		DIMENSIONS		MODEL	FIGURE	
	0.75"	1"	1.5"	2.5"			Knob	Short Elk-O-Lite®	Long Elk-O-Lite®	Molded Urethane	Positive Twist Lock	Brass / Chrome	Elk-O-Lite® / Hard Anodized	Length (Inches)			Weight (Lbs.)
	(x2)	(x2)	(x2)	(x2)	(x3)												
1.0" (F) NHT		•				•	o	o	s	o		•	5.5	1.8	B-100-SA	3	
1.5" (F) NHT	•	•				•	o	o	s	o		•	5.5	1.8	B-100-SA	3	
			•			•	o			s	•	•	5.5	8.5	B-100-L	3	
			•			•	o	o	s	o		•	5.5	3.9	B-100-LA	3	
			•			•						•	4.8	1.0	1A	4	
2.5" (F) NHT			•			•	o	o	s	o		•	4.8	2.3	1	4	
			•			•	o				•	•	5.5	4.5	B-100-A*	3	
			•			•	o			s	•	•	5.5	9.0	B-100	3	
			•			•					•	•	4.8	1.2	1A	4	
			•			•					•	•	4.8	4.0	1	4	
			•			•				s	•	•	9.0	14.5	B-97A	2	
			•			•				s	•	•	9.0	31.0	B-97	2	
			•			•					•	•	7.6	2.6	1A	4	
3.0" (F) NHT			•			•					•	•	7.6	8.6	1	4	
			•			•				s	•	•	10.5	21.5	B-95A	1	
			•			•				s	•	•	10.5	46.0	B-95	1	
			•			•					•	•	7.9	3.8	1	4	
3.5" (F) NHT			•			•					•	•	8.8	12.5	1A	4	
			•			•				s	•	•	9.0	14.5	B-97A	2	
			•			•				s	•	•	9.0	31.0	B-97	2	
			•			•				s	•	•	10.5	21.5	B-95A	1	
4.0" (F) NHT			•			•					•	•	10.5	46.0	B-95	1	
			•			•					•	•	7.9	4.4	1A	4	
			•			•				s	•	•	8.8	14.5	1	4	
			•			•				s	•	•	9.0	14.5	B-97A	2	
4.5" (F) NHT			•			•					•	•	9.0	31.0	B-97	2	
			•			•				s	•	•	9.0	14.5	B-97A	2	
			•			•				s	•	•	10.5	21.5	B-95A	1	
			•			•				s	•	•	10.5	46.0	B-95	1	
5.0" STORZ			•		•					•	•	10.5	16.0	B-97A	1		
5.0" (F) NHT			•			•					•	•	12.0	23.0	B-95A	1	
			•			•				s	•	•	9.0	14.5	B-97A	2	
			•			•				s	•	•	9.0	31.0	B-97	2	
			•			•				s	•	•	10.5	21.5	B-95A	1	
6.0" (F) NHT			•			•					•	•	10.5	46.0	B-95	1	
			•			•				s	•	•	9.0	14.5	B-97A	2	
			•			•				s	•	•	9.0	31.0	B-97	2	
			•			•				s	•	•	10.5	21.5	B-95A	1	

KEY s = standard o = option
 * Optional pressure gauge available

<p align="center">FIGURE 1</p>  <p align="center">B95/B95A (3-WAY) – POSITIVE TWIST LOCK <i>Fig. 1</i></p>	<p align="center">FIGURE 2</p>  <p align="center">B97/B97A (2-WAY) – POSITIVE TWIST LOCK <i>Fig. 2</i></p>
<p align="center">FIGURE 3</p>  <p align="center">B-100/B-100A <i>Fig. 3</i></p>	<p align="center">FIGURE 4</p>  <p align="center">1/1A <i>Fig. 4</i></p>

Figures depict general product types only and are not intended to be inclusive of all product features.

OPTIONS				
HANDLES			PRESSURE GAUGE	THREADS
 <p align="center">KNOB</p>	 <p align="center">SHORT (ELK-O-LITE®)</p>	 <p align="center">LONG (ELK-O-LITE®)</p>	 <p align="center">MOLDED URETHANE</p>	 <p align="center">POSITIVE TWIST LOCK</p>
<ul style="list-style-type: none"> • Not all handles available on all models. • All twist-locks feature metal knurled knobs. 				<p><i>All fireground connections are NHT unless otherwise specified. See index T-12 for optional base threads.</i></p>

PSI RATING
<p>While all Elkhart wyes are rated to at least 200 psi (13.79 bar), the products specified below are rated to 300 psi (20.69 bar):</p> <ul style="list-style-type: none"> • B-100-A (2.5" F inlet) • B-100-LA (1.5" F inlet) • B-100-SA (1.0" F or 1.5" F inlet)