

HANDLINE NOZZLES



MYSTERY®

Mystery®

The Mystery® Nozzle incorporates a twist-type shut-off, opening in straight stream and producing a flow from straight stream to wide fog. In combination with a B-375A ball shut-off, the Mystery® Nozzle promotes an extremely convenient method of advancing hoselines. Simply close the ball shut-off, remove the Mystery® tip, attach additional hose, and then reattach the tip at the end of the line. The tip's built-in shut-off allow for the line to be advanced rapidly without bringing in an additional nozzle.

HANDLINE NOZZLES

1-15



Base Size	AVAILABLE STANDARD FLOW RATE GPM (LPM)						BREAK-APART COMPONENTS		GRIP	SHUT- OFF	HANDLE	BASE	TEETH	DIMENSIONS		MODEL	FIGURE										
	60 (227)	95 (360)	125 (473)	170 (644)	200 (757)	250 (946)	Tip	Shut-Off*						Smooth Bore**	Pistol Grip			Twist	Ball	Tab	Horseshoe	Rigid	Swivel	Free Swivel	Cut Metal	Length (Inches)	Weight (Lbs.)
	PSI (BAR)																										
1.5"	•	•	•	•	•	•	L-205-BA	LB-275A	•	•	•	o	s	o	s	o	s	s	4.625	1.375	L-205-BA (Tip Only)	1					
	•	•	•	•	•	•			•	•	•	o	s	o	s	o	s	8.50	3.50	LB-275-AF	2						
	•	•	•	•	•	•	205-BA	B-375AT	•	•	•	o	s	o	s	o	s	7.125	3.25	205-BA (Tip Only)	1						
	•	•	•	•	•	•	205-BA	B-375GAT	•	•	•	o	s	o	s	o	s	12.875	6.25	B-375-ATF	3						
2.5"	•	•	•	•	•	•			•	•	•	o	s	o	s	o	s	13.25	6.75	B-375-GATF	3						
	•	•	•	•	•	•	D-205BA	JB-275A	•	•	•	s		s		s	s	7.50	3.50	D-205-BA (Tip Only)	1						
	•	•	•	•	•	•			•	•	•	s		s		s	s	13.625	7.50	JB-275-LAFD	4						

Key s = standard o = option

* Break-apart nozzles list standard configuration for shut-offs.

** Listed flow rate for break-apart nozzle with integral smooth bore is for Mystery® nozzle tip only.

Smooth bore discharge size may restrict flow of Mystery® tip. 15/16" discharge standard on 1.5" base; 7/8", 1", 1 1/8", 1 1/4" available. 1 1/4" discharge standard on 2.5" base; 7/8", 15/16", 1", 1 1/8" available.

MYSTERY® CONFIGURATIONS

Figure 1	 TIP ONLY <i>Fig. 1</i>	Figure 3	 BREAK-APART WITH INTEGRAL SMOOTH BORE <i>(Shown with optional pistol grip)</i> <i>Fig. 3</i>
Figure 2	 BREAK-APART <i>Fig. 2</i>	Figure 4	 LAFD NOZZLE <i>Fig. 4</i>

OPTIONS	
HANDLES	
TAB	HORSESHOE
	
THREADS	
All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.	
BREAK-APART COMPONENTS	
Ball shut-offs and/or playpipes referenced here may be found on page 1-24.	

Figures depict general product types only and are not intended to be inclusive of all product features.