

HANDLINE NOZZLES



FLEX ATTACK™


HANDLINE NOZZLES

Flex Attack™

A nozzle that lets you go from CAF to H₂O with a click of the tip. From the wet CAF attack setting, click left for a big open waterway and dry foam or click right for a tight 15/16" water only smooth bore. The patented, unobstructed variable orifice waterway won't strip CAF bubbles.


Features include:

- Free swivel inlet
- Hard anodized, Teflon® impregnated aluminum alloy body and pistol grip
- Aluminum/bronze shut-off handle
- Zytel® ST801 polyamide center barrel
- Ultra high molecular weight polyethylene shut-off seats
- 70A urethane compressible bore
- 184 GPM at 50 psi in water setting
- Maximum operating pressure 200 psi



OPTIONS

COLORS



Flex Attack™ nozzle comes standard with chrome handle and natural Elk-O-Lite® pistol grip. Ultra-reflective, durable vinyl color coding bands are supplied with each nozzle. See above for colors.

HANDLES

TAB



HORSESHOE



THREADS

All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.

| BASE SIZE | FLOW RATE* | PRESSURE* | GRIP | HANDLE | | MODEL |
|-----------|------------|-----------|-------------|--------|-----------|---------|
| | GPM (LPM) | PSI (BAR) | Pistol Grip | Tab | Horseshoe | |
| 1.5" | 184 (697) | 50 (3.45) | • | o | s | FLX-20G |

* In water setting