

# HANDLINE NOZZLES



MARINE

## Marine

These handline nozzles are specifically designed and manufactured for the unique firefighting challenges of a marine environment. They utilize military spec, corrosion resistant cast brass construction and are ideal for the application of AFFF. The constant flow technology, combined with their durable construction, make them optimal for use in the shipping industry, in refineries and for off-shore drilling or production rigs, as well as within chemical complexes.

Most models meet the stringent performance requirements of either the U.S. Navy or the U.S. Coast Guard.

HANDLINE NOZZLES




1-21



Base Size	AVAILABLE FLOW RATE GPM (LPM)			GRIP	SHUT-OFF	BASE			TEETH	RATING		DIMENSIONS		MODEL	FIGURE				
	95 (360)	125 (473)	250 (946)			Pistol Grip	Twist	Ball		Rigid	Swivel	Free Swivel	Cut Metal			Complies with MIL*	Complies with USCG**	Length (Inches)	Weight (Lbs.)
1.5"	•	•				•			s	s			7.375	6.50	SFL-N	1			
	•			•		•			s	s	•		7.375	7.625	SFL-GN-95	2			
		•		•		•			s	s	•		7.375	7.625	SFL-GN-125	2			
	•			•		•			s	s			7.375	7.625	SFL-GCG-95	2			
	•					•			s	s		•	7.375	7.625	SFL-CG	1			
2.5"			•			•			s	s	•		12.50	12.80	DSF-N	3			

Key s = standard o = option  
 \* Complies with MIL-N-24408E Type 1  
 \*\* Complies with USCG Approval Number: 162.027/12/0-IAW CFR46 162.027

### MARINE CONFIGURATIONS

<b>Figure 1</b>		<b>STANDARD</b>	<i>Fig. 1</i>
<b>Figure 2</b>		<b>PISTOL GRIP</b>	<i>Fig. 2</i>
<b>Figure 3</b>		<b>DSF-N</b>	<i>Fig. 3</i>

OPTIONS
THREADS
<i>All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.</i>
HANDLES
<ul style="list-style-type: none"> <li>• SFL-GCG-95, SFL-CG and SFL-N feature manganese/bronze shut-off handles</li> <li>• SFL-GN series and DSF-N feature silicon/bronze shut-off handles</li> </ul>

Figures depict general product types only and are not intended to be inclusive of all product features.