

Select-O-Matic®

Pressure-regulating Select-O-Matic® nozzles automatically adjust to fluctuating water flow to maintain effective pressure and a consistent fire stream in all flow ranges. Our patented, completely unobstructed waterway allows more gpm at lower pressures than any competitive brand. All models flush easily without shutting down and provide constant flow on either fog or straight stream, making them ideal for the application of AFFF foam. Corrosion resistant; no lubrication required.



HANDLINE NOZZLES



SELECT-O-MATIC®

HANDLINE NOZZLES

1-9

Base Size	FLOW RANGES		PRESSURE	TYPE	BREAK-APART COMPONENTS		Smooth Bore **	GRIP			BASE					HANDLE				TEETH	MODEL	FIGURE				
	GPM (LPM)	PSI (BAR)			Tip	Shut-Off*		Pistol Grip	Playpipe	Ladderhook	TYPE			LENGTH		Tab	Horseshoe	Spinning	Molded							
			Rigid	Swivel							Free Swivel	Long	Short													
1"	10-75 (38-284)	100 (6.89)	NOZZLE																	SM-3F	1					
			NOZZLE																		SM-3FG	1				
			TIP																		TSM-3F	2				
1.5"	60-125 (227-475)	100 (6.89)	NOZZLE																		SM-10F	1				
			NOZZLE																		SM-10FG	1				
			NOZZLE																			SM-10FB (All Brass)	1			
			TIP																			TSM-10F	2			
			BREAK-APART	TSM-10F	LB-275A																		STSM-10F	3		
			NOZZLE																				SM-20FLP	1		
	60-200 (227-757)	75 (5.17)	100 (6.89)	NOZZLE																			SM-20FLP	1		
				NOZZLE																			SM-20FGLP	1		
				TIP																			TSM-20FLP	2		
				BREAK-APART	TSM-20FLP	B-375AT																		STSM-20FATLP	4	
				BREAK-APART	TSM-20FLP	B-375GAT																		STSM-20FGATLP	4	
				NOZZLE																				SM-20F	1	
	60-200 (227-757)	100 (6.89)	100 (6.89)	NOZZLE																			SM-20F	1		
				TIP																			TSM-20F	2		
				BREAK-APART	TSM-20F	B-275A																		STSM-20F	3	
				BREAK-APART	TSM-20F	B-275GA																		STSM-20FG	3	
				BREAK-APART	TSM-20F	B-375AT																		STSM-20FAT	4	
				BREAK-APART	TSM-20F	B-375GAT																		STSM-20FGAT	4	
	75-325 (284-1230)	75 (5.17)	100 (6.89)	NOZZLE																			SM-30FLP	1		
				NOZZLE																				SM-30FGLP	1	
				TIP																				TSM-30FLP	2	
				BREAK-APART	TSM-30FLP	B-375AT																		STSM-30FATLP	4	
				BREAK-APART	TSM-30FLP	B-375GAT																			STSM-30FGATLP	4
				NOZZLE																					SM-30F	1
75-325 (284-1230)	100 (6.89)	100 (6.89)	NOZZLE																			SM-30FG	1			
			TIP																				TSM-30F	2		
			BREAK-APART	TSM-30F	B-275A																		STSM-30F	3		
			BREAK-APART	TSM-30F	B-275GA																		STSM-30FG	3		
			BREAK-APART	TSM-30F	B-375AT																		STSM-30FAT	4		
			BREAK-APART	TSM-30F	B-375GAT																		STSM-30FGAT	4		
2.5"	75-325 (284-1230)	75 (5.17)	NOZZLE																			DSM-30FLP	1			
			NOZZLE																				DSM-30FGLP	1		
			BREAK-APART	TSM-30FLP	B-278L																		STSM-30BPALP	6		
			BREAK-APART	TSM-30FLP	DB-375GAT																		STDSM-30FGATLP	4		
			TIP																					DTSM-30F	2	
			NOZZLE																					DSM-30FG	1	
	75-325 (284-1230)	100 (6.89)	100 (6.89)	BREAK-APART	SM-30F	279LA																	SM-30PL	5		
				BREAK-APART	TSM-30F	B-278L																		STSM-30BPA	6	
				NOZZLE																				DSM-30F	1	
				BREAK-APART	TSM-30F	DB-275A																		STDSM-30F	3	
				BREAK-APART	TSM-30F	DB-275GA																			STDSM-30FG	3
				BREAK-APART	TSM-30F	B-275A + 279LA																			STSM-30PL	6
75-325 (284-1230)	100 (6.89)	100 (6.89)	BREAK-APART	TSM-30F	DB-375AT																	STDSM-30FAT	4			
			BREAK-APART	TSM-30F	DB-375GAT																		STDSM-30FGAT	4		







Key s = standard o = option

* Break-apart nozzles list standard configuration for shut-offs.

** Listed flow rate for break-apart nozzle with integral smooth bore is for Select-O-Matic® nozzle tip only.

Smooth bore discharge size may restrict flow of Select-O-Matic® tip. 15/16" discharge standard on 1.5" base; 7/8", 1", 1 1/8", 1 1/4" available. 1 1/4" discharge standard on 2.5" base; 7/8", 15/16", 1", 1 1/8" available.

SELECT-O-MATIC® CONFIGURATIONS

<p>Figure 1</p>	 <p>NOZZLE (Shown with optional pistol grip)</p> <p style="text-align: right;"><i>Fig. 1</i></p>
<p>Figure 2</p>	 <p>TIP ONLY</p> <p style="text-align: right;"><i>Fig. 2</i></p>
<p>Figure 3</p>	 <p>BREAK-APART (Shown with optional pistol grip)</p> <p style="text-align: right;"><i>Fig. 3</i></p>
<p>Figure 4</p>	 <p>BREAK-APART WITH INTEGRAL SMOOTH BORE (Shown with optional pistol grip)</p> <p style="text-align: right;"><i>Fig. 4</i></p>
<p>Figure 5</p>	 <p>PLAYPIPE WITH NOZZLE</p> <p style="text-align: right;"><i>Fig. 5</i></p>
<p>Figure 6</p>	 <p>PLAYPIPE WITH TIP</p> <p style="text-align: right;"><i>Fig. 6</i></p>

Figures depict general product types only and are not intended to be inclusive of all product features.

OPTIONS							
HANDLES							
TAB 	HORSESHOE 						
BASES							
LONG 	SHORT 						
THREADS							
<p><i>All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.</i></p>							
BREAK-APART COMPONENTS							
<p><i>Ball shut-offs and/or playpipes referenced here may be found on page 1-24.</i></p>							
MOLDED URETHANE TEETH							
							
COLORS							
black	red	orange	yellow	Glow	green	blue	white
<p><i>Color options available for pistol grip, bumper, and handle. Glow available for bumper only. Retrofit kit available for Glow bumper. White bumper not available.</i></p> <p><i>Select-O-Matic® nozzle comes standard with a yellow bumper, chrome handle, and natural Elk-O-Lite® pistol grip.</i></p>							
ADDITIONAL INFORMATION							
PART NAME				PAGE #			
<i>Thread Information</i>				<i>T-12</i>			
<i>Nozzle Flow Data</i>				<i>T-2</i>			
<i>Hose and Nozzle Accessories</i>				<i>2-1</i>			
<i>Foam Expansion Tubes</i>				<i>1-23</i>			