



S-205-BAF

- For forestry use
- 1.0" rigid base in NHT or NPSH; 0.75" GHT available
- Available in 12 or 23 gpm (45 or 87 lpm)
- Twist shut-off
- For use with pressure of up to 600 psi (41.37 bar)
- Straight stream to fog
- Elk-O-Lite® construction



L-205-BAF

- For forestry use
- 1.5" rigid base
- Dual flows: 20 and 70 gpm (76 and 265 lpm) @ 100 psi (6.89 bar)
- Straight stream to fog
- Twist shut-off
- Elk-O-Lite® construction



S-205-BAD

- For decontamination use
- Connects to 0.75" GHT or 1" NHT
- Available in 12 or 23 gpm (45 or 87 lpm)
- For use with pressure of up to 600 psi (41.37 bar)
- Twist shut-off
- Straight stream to fog
- Elk-O-Lite® construction
- Optional kit includes: NFPA 1961 compliant 1" hose with adapters (0.75" garden hose, 1" NHT, and 2.5" NHT) plus a heavy-duty nylon bag



SFL-O-DI

- For de-icing use
- 1.5" swivel base (optional rigid and free swivel bases)
- Selectable flow rates of 40, 60, 95 or 125 gpm (151, 227, 360 or 473 lpm)
- Aluminum/bronze handle construction; tab handle (standard), horseshoe handle (optional)
- Combined chrome-plate brass and Elk-O-Lite® construction
- Usable with de-icing and anti-icing fluids in Type I systems
- Pistol grip available (SFL-OG-DI)