## EX SAFETY CABINETS

### **W** JUSTRITE®

### **Sure-Grip® EX Safety Cabinet**

# Sturdy, 18-gauge double wall steel with 11/2" of insulating air space Fully welded, not riveted for longer life and greater fire protection Trilingual Warning Durable Powder Paint Finish Continuous piano hinge for smooth closure Dual 2" vents with flame arresters Adjustable leveling feet and grounding connector 2" leakproof sump contains spills Fusible links hold doors wide open and melt at 165° F for automatic closure

#### EXtra Safe

### EXtra Secure





Exclusive Haz-Alert™ reflective labeling for high visibility under fire conditions or power outages.

Firefighter friendly...helps emergency personnel easily isolate volatile liquids



Exclusive U-Loc™ handle includes double key set or can be padlocked (optional) for greater security. Non-protruding, flush design reduces dangerous "catches" from passing traffic. Slip-resistant strip under handle offers greater control and easy fingertip operation.



Reflective Safety Band is zone positioned to alert firefighters when crawling in smoke filled areas (visible as smoke rises)



Patented, concealed selfclose mechanism maximizes available shelf space. Self-indexing doors guarantee they will close in sequence and assure a tight closure from top to bottom.

Self-close door style meets the Uniform Fire Code





SpillSlope™ shelves safely direct leaks to back and bottom. Adjust on 3" centers. Meets ANSI standards with a 350lb. safe allowable load.

Fail-safe closing mechanism ensures 3-point self-latching

system works first time, every time. Three durable









### Sure-Grip® EX Safety Cabinet

- $\bullet$  FM approved cabinets are constructed of sturdy, double-walled 18 ga. steel with 1% of insulating air space for fire resistance.
- Attractive flush-mounted handle -- ideal in tight spaces and less prone to damage in shipping. Reduces "accidental bangs" from passing traffic.

Fingertip control with an exclusive slip resistant textured lining on the inside of handle. U-Loc<sup>TM</sup> handle style accepts optional padlock or can be key locked. Self-latching handle ensures engagement of 3-point latch for protection under fire conditions. Radiused corners on doors for added safety. Haz-Alert<sup>TM</sup> reflective labeling system provides high visibility under fire conditions or power outages. OSHA and NFPA compliant safety cabinets provide safe, secure storage and organization for flammable liquids. They minimize employee exposure, reduce fire risks and add to efficiency when positioned near points-of-use. FOB Shipping Point.



Product No.			Door N Type S	lo. Ad helve	j. Siz s H x W	e 'x D	Wt. (lbs.)	Price Ea.
H893000	2	30	Manual	1	44 x 43	x 18"	231	\$661.95
H893020	2	30	Self-close	-1	$44 \times 43$	x 18"	237	740.68
H893080	1	30	Sliding, self-close	e 1	$44 \times 43$	x 18"	246	1,101.85
H893300	2	30	Manual	1	$35 \times 36$	x 24"	204	769.43
H894500	2		Manual	2				819.91
H894520	2	45	Self-close	2	65 x 43	x 18"	313	900.80
H894580	1		Sliding, self-clos					1,266.78
H896000			Manual	2				987.37
H896020		60		2				1,073.29
H899000			Manual	2	$65 \times 43$	x 34"	480	1,241.46
H899020	* 2	90	Self-close	2	65 x 43	x 34"	480	1,413.83