

CASTERS



Heavy-Duty Casters

- Heavy loads keep on rolling with these rugged cold-forged constructed casters.
- One-piece swivel horn/fork design with no welds distributes loads across the larger portion of the ball race.

One-piece combination lower ball race and king pin improves structure rigidity and easier swiveling. 3/8" king pin is orbital cold formed for superior strength and stability. Swivel casters feature grease seals, keeping dirt out of top raceway and increasing life. Epoxy powder coated finish. Meets ASME B56.11.1 industry standards. FOB Shipping Point.

Wheel Size	Cap. (lbs.)	O.A. Hgt.	Swivel		Rigid	
			Product No. SEMI-STEEL	Price Ea.	Product No.	Price Ea.
4 x 2"	1000	5 3/8"	HW26-4-IRB	\$25.85	HW36-4-IRB	\$20.51
5 x 2"	1000	6 1/2"	HW26-5-IRB	28.96	HW36-5-IRB	23.13
6 x 2"	1200	7 1/4"	HW26-6-IRB	35.25	HW36-6-IRB	30.00
8 x 2"	1200	9 1/2"	HW26-8-IRB	44.45	HW36-8-IRB	39.52
RUBBER MOLD-ON						
4 x 2"	290	5 3/8"	HW26-4-RT	22.48	HW36-4-RT	17.13
5 x 2"	350	6 1/2"	HW26-5-RT	24.90	HW36-5-RT	19.07
6 x 2"	410	7 1/4"	HW26-6-RT	26.51	HW36-6-RT	21.25
8 x 2"	500	9 1/2"	HW26-8-RT	31.28	HW36-8-RT	26.33
POLYURETHANE						
4 x 2"	600	5 3/8"	HW26-4-PO	25.34	HW36-4-PO	20.00
5 x 2"	700	6 1/2"	HW26-5-PO	28.87	HW36-5-PO	23.07
6 x 2"	1000	7 1/4"	HW26-6-PO	30.87	HW36-6-PO	25.61
8 x 2"	1200	9 1/2"	HW26-8-PO	37.88	HW36-8-PO	32.96
PHENOLIC/CANVAS						
4 x 2"	800	5 3/8"	HW26-4-MC	22.72	HW36-4-MC	17.37
5 x 2"	1000	6 1/2"	HW26-5-MC	24.69	HW36-5-MC	18.87
6 x 2"	1200	7 1/4"	HW26-6-MC	26.36	HW36-6-MC	21.10
8 x 2"	1200	9 1/2"	HW26-8-MC	31.73	HW36-8-MC	26.81
THERMOPLASTIC/RUBBER						
4 x 2"	325	5 3/8"	HW26-4TPR	24.99	HW36-4TPR	19.64
5 x 2"	325	6 1/2"	HW26-5TPR	27.28	HW36-5TPR	21.64
6 x 2"	410	7 1/4"	HW26-6TPR	30.15	HW36-6TPR	24.90
8 x 2"	500	9 1/2"	HW26-8TPR	34.87	HW36-8TPR	29.94
POLYURETHANE/ALUMINUM						
4 x 2"	800	5 3/8"	HW26-4POAC	34.87	HW36-4POAC	29.43
5 x 2"	900	6 1/2"	HW26-5POAC	38.18	HW36-5POAC	32.39
6 x 2"	1100	7 1/4"	HW26-6POAC	46.78	HW36-6POAC	41.52
8 x 2"	1200	9 1/2"	HW26-8POAC	55.40	HW36-8POAC	50.54

Top plate size: 4 1/2" x 6 1/4". Bolt hole spacing: 2 1/2" x 3 3/8" slotted to 4 1/4" x 5 1/4". Bolt hole size: 3/8".

Light-Duty Casters

A & F) Regular Duty Casters

Multi-purpose light to regular duty casters has polyolefin type wheels. Features a double ball raceway. Zinc plated.

A) Top Plate: 2 3/8" x 3 3/8". Hole Spacing: 1 3/4" x 2 3/8" to 3".

F) Top Plate: 3 3/8" x 4 3/8". Hole Spacing: 1 1/8" to 2 3/8" x 2 3/8" x 3 3/8".

B) Total Lock Stem Casters

Double braking swivel caster for light duty applications. Foot operated brake will lock both the swivel of the caster and also will lock the wheel from rolling. 1/2" - 13 x 1" threaded stem.

C) Threaded Stem Casters

Light duty cold-forged steel caster has a bright, zinc plated finish to resist corrosion. Featured with double ball bearing raceway and staked king pin. Ideal for office furniture, factories and warehouse use. 1/2" - 13 x 3/8" threaded stem.

D) Total Lock Swivel Casters

Double braking swivel caster for light duty applications. Foot operated brake will lock both the swivel of the caster and also will lock the wheel from rolling. Top Plate: 2 3/8" x 3 3/8". Hole Spacing: 1 3/8" x 2 3/8" to 3".

E) Stainless Steel Casters

Stainless steel construction with stainless steel double ball raceway swivel caster and one piece rigid caster. Furnished with stainless steel axle and axle nut. Ideal for applications in corrosive and wet environments. Top Plate: 2 3/8" x 3 3/8". Hole Spacing: 1 3/8" x 2 3/8" to 3".



Ltr. No.	Product No.	Cap. (lbs.)	Wheel Type	Wt. (lbs.)	Price Ea.
A	HEL23-4-PH	300	4" Polyolefin	1.5	\$5.67
B	HTL-S11-03-5TPR	275	5" Thermoplastic/Rubber	2.2	12.09
C	HS11-02-2HR	100	2" Hard Rubber	0.3	1.55
D	HTL-03-4TPR	225	4" Thermoplastic/Rubber	2.6	10.83
E	HSS-13-5PBB	275	5" Poly/Poly	1.8	21.10
F	HE23-3-PH	250	3" Polyolefin	1.1	4.04



Scaffold Caster

- Strength and durability all rolled into one.
- Stem is orbital cold formed to the American-made caster assembly for extra support.

Toothed top plate for firm rotational lock. Brake arm is integral with fork legs -- no welds. Full tread width wheel lock with exceptional rigidity. Durable epoxy powder coat finish for weather resistance. FOB Shipping Point.

Product No.	Cap. (lbs.)	Wheel	Stem	Wt. (lbs.)	Price Ea.
HE-DB92-X2-8RT	500	8" mold-on	1 1/2"	12.3	\$29.93



Extra Heavy-Duty Casters

- Built from heavy plate steel with hardened bearings and sealed raceways for extra heavy load capacities.
- Equipped with a hardened 1" king bolt welded to the top plate...won't stretch or break loose.

Features precision tapered thrust bearing with dust seal in lower raceway. Bearing seal keeps dirt out, while greasing purges old lube. Green epoxy powder coat finish. FOB Shipping Point.

Wheel Size	Cap. (lbs.)	O.A. Hgt.	Swivel		Rigid	
			Product No. SEMI-STEEL	Price Ea.	Product No.	Price Ea.
6 x 2 1/2"	1500	8 3/8"	H28-6-IRB	\$187.83	H38-6-IRB	\$93.90
8 x 3"	2500	10 1/2"	H28-8-IRB	202.65	H38-8-IRB	110.35
10 x 3"	2700	12 1/2"	H28-10-IRB	224.15	H38-10-IRB	133.70
POLYURETHANE						
6 x 2 1/2"	1300	8 3/8"	H28-6-PO	\$190.68	H38-6-PO	96.75
8 x 3"	2500	10 1/2"	H28-8-PO	212.87	H38-8-PO	120.56
10 x 3"	2800	12 1/2"	H28-10-PO	226.07	H38-10-PO	135.66
12 x 3"	3000	14 1/2"	H28-12-PO	252.80	H38-12-PO	162.45
PHENOLIC/CANVAS						
6 x 2 1/2"	1600	8 3/8"	H28-6-MC	\$184.15	H38-6-MC	90.22
8 x 3"	2500	10 1/2"	H28-8-MC	197.88	H38-8-MC	105.61
10 x 3"	2900	12 1/2"	H28-10-MC	205.14	H38-10-MC	114.69
12 x 3"	3500	14 1/2"	H28-12-MC	216.85	H38-12-MC	126.50

Top plate size: 6 x 7 1/4". Bolt holes spacing: 4 1/2" x 6 1/4". 1/2" bolt hole size.



Medium Heavy-Duty Casters

- Easy, smooth rolling caster with exceptional durability.
- Features top raceway grease seal, keeping dirt and dust out while retaining a larger reservoir of grease for longer life.

No-weld construction on caster horn assures greater stability. Large 3/8" orbital cold formed king pin and lower raceway are one-piece constructed for added strength. Heavy-duty cylindrical formed legs and protected zerk fitting. Epoxy powder coated finish. FOB Shipping Point.

Wheel Size	Cap. (lbs.)	O.A. Hgt.	Swivel		Rigid	
			Product No. MOLD-ON RUBBER	Price Ea.	Product No.	Price Ea.
5 x 2"	350	6.50"	HN22-5-RT	\$20.52	HN32-5-RT	\$14.36
6 x 2"	410	7.25"	HN22-6-RT	22.33	HN32-6-RT	17.12
8 x 2"	500	9.50"	HN22-8-RT	26.65	HN32-8-RT	21.38
POLYURETHANE						
5 x 2"	700	6.50"	HN22-5-PO	24.12	HN32-5-PO	17.96
6 x 2"	1000	7.25"	HN22-6-PO	26.30	HN32-6-PO	21.09
8 x 2"	1200	9.50"	HN22-8-PO	32.67	HN32-8-PO	27.38
PHENOLIC						
5 x 2"	1000	6.50"	HN22-5-MC	20.30	HN32-5-MC	14.17
6 x 2"	1200	7.25"	HN22-6-MC	22.17	HN32-6-MC	16.96
8 x 2"	1200	9.50"	HN22-8-MC	27.08	HN32-8-MC	21.79
SEMI-STEEL						
5 x 2"	1000	6.50"	HN22-5-IRB	24.21	HN32-5-IRB	18.05
6 x 2"	1200	7.25"	HN22-6-IRB	30.28	HN32-6-IRB	25.07
8 x 2"	1200	9.50"	HN22-8-IRB	38.64	HN32-8-IRB	33.35
POLYOLEFIN						
5 x 2"	650	6.50"	HN22-5-PDR	17.31	HN32-5-PDR	11.18
6 x 2"	750	7.25"	HN22-6-PDR	18.26	HN32-6-PDR	13.08
8 x 2"	800	9.50"	HN22-8-PDR	23.45	HN32-8-PDR	18.15
THERMOPLASTIC/RUBBER						
5 x 2"	325	6.50"	HN22-5TPR	22.82	HN32-5TPR	16.69
6 x 2"	410	7.25"	HN22-6TPR	25.64	HN32-6TPR	20.43
8 x 2"	500	9.50"	HN22-8TPR	29.93	HN32-8TPR	24.64
POLYURETHANE/ALUMINUM						
5 x 2"	800	6.50"	HN22-5-POAC	32.51	HN32-5-POAC	27.33
6 x 2"	1100	7.25"	HN22-6-POAC	40.73	HN32-6-POAC	35.55
8 x 2"	1200	9.50"	HN22-8-POAC	48.58	HN32-8-POAC	43.31

4 x 4 1/2" plate size with bolt holes 2 1/2" x 3" center-to-center, slotted to 3 x 3 3/8".

Bolt hole size: 3/8"