



Heavy Duty Winch Operated Stacker

• A compact economical alternative to battery stackers.

Perfect for loading and unloading trucks where docks don't exist. Heavy-duty safety Winch is easy to turn, even with heavy loads. Straddle legs adjust from 34"-50" I.D. 36" adjustable forks. Easily maneuvers in tight areas on 5"swivel casters and 4" front rollers. Floor lock secures the stacker in place. 750 lb. capacity. 60" lift height, 3" lowered height. FOB Shipping Point.

HMW750 Wt. 355 (lbs.) Price Ea. \$1,522.56

THE



• Ideal for facilities without loading docks.

Rugged heavy-duty all welded design for superior performance. Designed for all types of applications including lifting and transporting skids, bales, baskets, etc. Also for loading and unloading trucks, stocking shelves, die and mold handling and will handle all sizes of pallets. Maneuvers easily in congested areas. 1,500 lb. capacity. Straddle legs adjust from 41"-50" I.D. Adjustable 42" forks. 4" front rollers and 6" rear swivel casters. Includes battery and onboard charger with 6-8 hours on full charge. Floor lock secures stacker in place. FOB Shipping Point.

HEAVY DUTY ELECTRIC HYDRAULIC STACKER							
Product No.	Cap. (lbs.)	Lowered Height	Raised Height	Wt. (lbs.)	Price Ea.		
HB60CSA	1500	3"	60"	625	\$2,964.69		
HB70CSA	1500	3"	70"	635	3,081.17		
HB80CSA	1500	3"	80"	645	3,271.15		

MANUAL PUSH STACKERS

Telescopic Electric Hydraulic Stacker

 Precision engineered for smooth performance and exceptional durability.

Lift and move loads up to 1500 lbs. easily and safely. Rugged formed steel frame for extra strength. Precision built heavy-duty hydraulic system with relief valve for overload protection. Durable cylinder has chrome plated ram. Roller style dual lifting chains exceed a 6:1 safety factor. Hand control lever provides feather control load positioning. 12V/125A battery with 12V/10A safety charger that plugs into any 110V outlet. Hand lever floor brake. 5th wheel features 7" steer wheels. 4" front rollers. Straddle legs adjust from 36"-50" I.D. Adjustable 42" forks. FOB Shipping Point.

	TELESCOPIC ELECTRIC HYDRAULIC STACKER					
Product No.	Cap. (lbs.)	Lowered Height	Raised Height	Wt. (lbs.)	Price Ea.	
HFTAFC96	1500	3"	96"	1020	\$3,893.76	
HFTAFC120	1500	3"	120"	1050	4,006.08	
HFTAFC132	1500	3"	132"	1080	4,216.85	
HFTAFC144	1500	3"	144"	1120	4.602.35	

SELF-PROPELLED STACKERS

APS-A Self-Propelled "All-Purpose" Stacker

• Versatile heavy duty unit.

Combines maximum safety and operator comfort.

Standard features include panic stop button, emergency power disconnect button, horn, key switch and "soft start-soft stop" operation. Throttle, lift and lower are located on the ergonomically designed handle. Straddle legs adjust 36"-50" ID. AC Motor. 24 Volt system. Lowered Height: 2.5". Raised Heights: 63"-138". Turning Radius: 69". Adjustable 42" Forks. Internal charger plugs into any regular 110 volt outlet. FOB Shipping Point.

Produ No.	ıct	SELF-P Cap. (lbs.)	ROPELLEI Raised Height	O STACI Wt. (lbs.)	KER Price Ea.
HAPS22 HAPS22		2200 2200	63" 118"	2060 2190	\$10,536.36 11,180.80
HAPS22	2-138-A	2200	138"	2270	11,492.84
HAPS33		3300 3300	63" 118"	2090 2390	11,851.23 12,397.25
HAPS33		3300 4400	138" 63"	2450 2110	12,682.17 14,321.31
HAP\$44	I-118-A	4400	118"	2430	15,292.15
HAPS44	I-138-A	4400	138"	2490	15,777.61

HLS-A "Hi-Lift" Self-Propelled Stackers

• Ideal for high-lift applications.

Offers the same features as the APS-A "All-Purpose" stackers with higher lifting capabilities.

Ideal for stacking on high racks and mezannines. Heavy duty triple stage mast. AC Motor. 24 Volt system.

Internal charger plugs into a regular 110 volt outlet.

Lowered Height: 2.5". Fork Length: 42" Travel Speed: (empty) 2.5 mph / (full) 3.5 mph. Adjustable Straddle Legs: 46"-61" I.D.Turning Radius: 64".

FOB Shipping Point.

HLS-A "HI Product		LF-PROPEL Raised	LED STA Wt.	CKERS Price
No.	Cap. (lbs.)	Height	(lbs.)	Ea.
HHLS33-177-A	3300	177"	2980	\$14,469.97
HHLS33-209-A	3300	209"		15,580.17
HHLS33-228-A	3300	228"	3165	16,529.84



SELF-PROPELLED STACKERS

RTS-A Reach Trucks

•Lift, Transport & Reach capabilities.

Able to lift loads up to 2,200 or 3,300 lbs. to a maximum height ranging from 98" or 216", these state-of-the-art stackers also extends loads to a maximum of 19.5". Mast tilts 2° forward / 5° backward. Standard features include panic stop button, emergency power disconnect button, horn, key switch and "soft start-soft stop" operation. Heavy duty double or triple stage mast. 24 Volt AC electrical system. Fixed Straddle Leg ID: 35". Adjustable

Forks: 42". Lowered Height: 3".

External charger plugs into any regular
110 volt outlet. Travel Speed: 2.8 mph (full) / 3.1 mph
(empty). Turning Radius: 70". Polyurethane Wheels
and Rollers. FOB Shipping Point.

	RTS-A	A REACH TRUC	CK	
Product No.	Cap. (lbs.)	Raised Height	Wt. (lbs.)	Price Ea.
HRTS22-98-A	2200	98"	3420	\$15,409.57
HRTS22-118-A	2200	118"	3495	15,718.45
IRT\$22-196-A	2200	196"	4299	20,366.08
IRTS22-216-A	2200	216"	4519	20,460.57
IRTS33-98-A	3300	98"	3790	18,741.35
IRTS33-118-A	3300	118"	3890	19,108.36
IRTS33-177-A	3300	177"	4350	22,691.09
HRTS33-196-A	3300	196"	4570	23,342.41
IRTS33-216-A	3300	216"	4790	24,078.68

HRST22-98-A Shown Raised