

The difference is... your margin of safety.

## Durattack 1000™

## **Durattack 1000™ Features**

- Exclusive **DURA-CORD**® advanced air-textured Nylon 6-6 continuous filament warp yarns, resulting in superior "toughness", abrasion resis tance, cut resistance, tear strength and heat resistance when compared to competitive nylon, spun polyester or filament polyester warp constructions
- Unique Ultra-Shield™ high-performance polyurethane coating seals each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification
- Superior "fit" between inner hose and outer jacket eliminates bunching, wrinkling and snagging of outer jacket

- Increased thickness of nitrile rubber inner hose eliminates leaking and/ or "soaker hose" problems encountered with competitive products
- Very low hydraulic friction loss encountered during pumping operations
- Unsurpassed kink resistance at low pressure, making it the perfect choice for low pressure nozzle applications
- Anti-Burst technology significantly reduces potential for catastrophic burst failure while hose is charged

Applications include: Attack, CAFS, High Rise Available in 50 and 100 foot lengths





HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
13/4"	DURATTACK	1000 PSI	500 PSI	21/8"	20 lbs.
2½"	DURATTACK	1000 PSI	500 PSI	3"	27 lbs.

**DURA-CORD**® is a registered trade mark of North American Fire Hose Corporation. All rights reserved.

Durattack 1000™, DURATTACK ™, Ultra-Shield™, are trade marks of North American Fire Hose Corporation. All rights reserved.

Copyright © 2013 North American Fire Hose Corporation. All rights reserved.

Revision 2013A

## **North American Fire Hose Corporation**

910 East Noble Way · Santa Maria, CA 93454
Phone 805 922-7076 · Fax 805 922-0086
www.nafhc.com