

HYDRONIC & STEAM HEATING

Hydronic Heating Specialties

EXT (16-XT) SERIES



EXPANSION TANKS FOR HYDRONIC SYSTEMS

Conbraco non-potable expansion tanks help maintain balanced pressure throughout a hot water heating system by absorbing thermal expansion. Pre-pressurized, they're designed to prevent system damage and unnecessary discharges by relief valves and ensure long, trouble-free system life.

FEATURES

- Welded steel construction
- Rugged flexible diaphragm
- Pre-charged at 12 psig
- Compact design saves energy and space
- Glycol compatible
- Maximum working pressure: 100 psig
- Maximum temperature: 240°F
- Chlorobutyl diaphragm
- Ideal for peak use systems such as car washes, processing plants, and hotels
- **Made in USA**

Series Number	Capacity (gal.)	Exp. Vol. (gal.)	Connection	Dimensions (in.)		Net Wt. (lbs.)
				Height	Diameter	
16-XT1-03	2	1.9	1/2 NPT	12.5	8.25	5
16-XT3-03	5	4.8	1/2 NPT	14.75	11	8
16-XT5-03	7	7.3	1/2 NPT	21.12	11	12
16-XT7-03	14	14.68	1 NPT	21.62	15.37	22

RAV (27-200) SERIES



RADIATOR AIR VALVE – APOLLO INTERNATIONAL™

Manual air purge valves for hot water radiators/heating systems.

Series Number	Size (in.)	Net Wt. (lbs.)
27-202-02	1/8	2.0
H-2404-00	Key only	0.9

FF (35) SERIES



BRONZE FEED WATER PRESSURE REGULATORS

Available in 1/2" union threaded, threaded and solder union configurations. Purge lever/fast fill feature. Cartridge is replaceable inline.

FEATURES

- No cage screws
- Factory pre-set to 15 psig - adjustable 10 to 25 psig
- Max temperature 210°F, Max supply pressure 100 psi
- High capacity
- Integral check and Stainless Steel strainer
- Rugged high temperature Nitrile elastomers

Series Number	Size (in.)	Height (in.)	Length (in.)	Net Wt. (lbs.)
35-503-01	1/2 Union Threaded	5.25	4.31	2.5
35-603-01	1/2 Threaded	5.25	3.50	2.2
35-703-01	1/2 Solder Union	5.25	3.18	2.3