

20-410 SERIES



SIDE MOUNTED HANDWHEEL WATER GAUGES

Side-mounted handwheels allow water gauge operation in hard-to-reach places; with all the 20 Series design features.

FEATURES

- Ideal for concealed jacketed type boilers
- EPDM standard gauge glass gasket
- Standard 1/4" needle drain valve
- Rated: 125 psig @ 350°F, 300 psig @ 100°F (See note)
- 1-1/4" Extended shank length
- Chrome plate option
- Guard rod glass protection
- CRN OF6616.5C

Part Number	Side	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)	Shank Length (in.)	Wheel Type
20-410-00	LH	1/2	5/8 x 12	180	1.25	ALUMINUM

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.

20-600/20-800 SERIES



BRONZE EXPANSION TANK GAUGES

Bottom shut-off valve allows for glass maintenance without complete drainage.

FEATURES

- Automatic ball check
- EPDM standard gauge glass gasket
- 20-800 models: 1/4" NPT port in upper body for pressure gauge
- Rated: 200 psig @ 400°F, 400 psig @ 100°F (See note)
- Guard rod glass protection
- CRN OF6616.5C

Part Number	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)	Wheel Type
20-604-00*	1/2	5/8 x 12	155	ALUMINUM
20-605-00*	1/2	5/8 x 12	175	COMPOSITION
20-804-00*	1/2	5/8 x 12	160	ALUMINUM
20-805-00*	1/2	5/8 x 12	160	COMPOSITION

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.

Note: Not for use on boiler systems

* Automatic ball checks