

Cast Iron Drainage Fittings

FIGURE 726* 90° Short Turn Y-Branch Tee Pattern		Size		A		B		C		Unit Weight			
		NPS	DN	in	mm	in	mm	in	mm	Black		Galv.	
										lbs	kg	lbs	kg
	1½	40	4¼	108	2½	64	2½	64	3.09	1.40	3.09	1.40	
	2	50	5 ³ / ₁₆	132	3 ¹ / ₁₆	78	3 ¹ / ₁₆	78	5.08	2.30	5.08	2.30	
	3	80	7¼	184	4¼	108	4¼	108	11.77	5.34	11.77	5.34	
	4	100	8¾	222	5 ³ / ₁₆	132	5 ³ / ₁₆	132	21.25	9.64	21.25	9.64	

FIGURE 727* 90° Reducing Short Turn Y-Branch Tee Pattern		Size		A		B		C		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	Black	
										lbs	kg
	2 x 2 x 1½	50 x 50 x 40	4 ⁵ / ₈	117	2 ¹⁵ / ₁₆	75	2 ¹¹ / ₁₆	68	4.16	1.89	
	2 x 1½ x 1½	50 x 40 x 40	4 ⁵ / ₈	117	2 ¹⁵ / ₁₆	75	2 ¹¹ / ₁₆	68	4.33	1.96	

FIGURE 729* Reducing Double Short Turn Tee		Size		A		B		C		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	Black	
										lbs	kg
	2 x 1½	50 x 40	4 ⁵ / ₈	117	5 ⁷ / ₈	149	2 ¹¹ / ₁₆	68	5.82	2.64	

FIGURE 730* 90° Long Turn Y-Branch Tee Pattern		Size		A		B		C		Unit Weight			
		NPS	DN	in	mm	in	mm	in	mm	Black		Galv.	
										lbs	kg	lbs	kg
	1½	40	5 ³ / ₈	137	4 ¹ / ₈	105	1¼	32	4.43	2.01	-	-	
	2	50	7	178	5¼	133	1¾	44	6.69	3.03	6.69	3.03	

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.