

Oil Country Fittings

Tubing Swages & Casing Swages



Malleable Iron

Cast Iron

Small Steel Fittings


Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvilets

Catawissa

J.B. Smith Products

Swage Nipples Oil Country Tubing & Casing non EUE ends	Size						Length	Standard Weight	XS/XH Weight	XXS/XXH Weight				
	Pipe		O.D.		Reduced to									
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1	25	1.315	33	¼ - ¾	8 - 20	3½	89	0.66	0.30	0.66	0.30	1.00	0.45
	1¼	32	1.660	42	¼ - ½	8 - 15	4	102	1.00	0.45	1.00	0.45	1.5	0.68
					¾ & 1	20 & 25	4	102	1.00	0.45	1.00	0.45	1.5	0.68
	1½	40	1.900	48	¼ - ¾	8 - 20	4½	114	1.2	0.53	-	-	2.0	0.91
					1 & 1¼	25 & 32	4½	114	1.2	0.53	1.00	0.45	2.0	0.91
	2	50	2¾	60	¼ - ¾	8 - 20	6½	165	2.5	1.1	3.0	1.4	4.3	1.9
					1 - 2 O.D.	25 - 50 O.D.	6½	165	2.0	0.91	2.3	1.1	4.3	1.9
	2½	65	2¾	73	¼ - ¾	8 - .75	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					1 - 1½	25 - 40	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					2 & 2½	50 - 52	7	178	3.0	1.4	3.5	1.6	8.0	3.6
	3	80	3½	89	1 - 1½	25 - 40	8	203	4.5	2.0	6.0	2.7	11	5.0
					2 & 2½	50 - 65	8	203	4.5	2.0	6.0	2.7	11	5.0
					1 - 1½	25 - 40	9	229	7.0	3.2	10.0	4.5	18	8.2
	4	100	4½	114	2 - 4 O.D.	50 - 100 O.D.	9	229	7.5	3.4	10.0	4.5	18	8.2
					1 - 1½	25 - 40	10	254	9.5	4.3	15	6.8	24	11
	5	127	5	127	2 - 4½ O.D.	50 - 100 O.D.	10	254	9.5	4.3	15	6.8	24	11
					1 - 1½	25 - 40	11	279	13	5.7	17	7.7	33	15
	5½	140	5½	140	2 & 2½	50 & 65	11	279	13	5.7	17	7.7	33	15
					3 - 50.D.	80 - 125 O.D.	11	279	13	5.7	17	7.7	33	15
					1 - 1½	25 - 40	12	305	17	7.7	25	11	46	21
	6¾	168	6¾	168	2 & 2½	50 & 65	12	305	17	7.7	25	11	46	21
					3 - 4 O.D.	80 - 100 O.D.	12	305	17	7.7	25	11	46	21
					4 - 6 O.D.	100 - 150 O.D.	12	305	17	7.7	25	11	46	21
	7	178	7	178	1 - 1½	25 - 40	12	305	17	7.7	25	11	-	-
					2 - 2½	50 - 65	12	305	17	7.7	25	11	-	-
					3 - 5 O.D.	80 - 125 O.D.	12	305	17	7.7	25	11	-	-
	7½	194	7½	194	5½ O.D. & 6 O.D.	140 O.D. & 150 O.D.	12	305	17	7.7	25	11	-	-
					2 - 3	5 - 750	13	330	24	11	32	15	-	-
					4 O.D. - 6 O.D.	100 O.D. - 150 O.D.	13	330	24	11	32	15	-	-
	8	219	8	219	6½ O.D. - 7 O.D.	168 O.D. - 175 O.D.	13	330	24	11	32	15	-	-
					2 - 3	50 - 75	13	330	29	13	44	20	-	-
					4 - 6 O.D.	100 - 150 O.D.	13	330	29	13	44	20	-	-
9	244	9	244	6½ O.D. & 7½ O.D.	168 O.D. - 194 O.D.	13	330	29	13	44	20	-	-	
				2 - 3	50 - 75	14	356	38	17	48	22	-	-	
				4 - 6 O.D.	100 - 150 O.D.	14	356	38	17	48	22	-	-	
10¾	273	10¾	273	6½ O.D. & 8½ O.D.	168 O.D. - 219 O.D.	14	356	38	17	48	22	-	-	
				2 - 3	50 - 75	15	381	48	22	68	31	-	-	
				4 - 6 O.D.	100 - 150 O.D.	15	381	48	22	68	31	-	-	
				8½ O.D. & 9½ O.D.	219 O.D. - 245 O.D.	15	381	48	22	68	31	-	-	

All swage nipples on this page are made from J-55, K-55, N-80 or the most appropriate material available. Casing threads (8 Rd.) on one end with any thread or finish (beveled) on the other end. Also includes casing sizes where no thread is specified

