BRETFORD BASICS™ ADJUSTABLE MULTIMEDIA CART WITH CABINET

 $\left|\right>$

CA2642DNS

Adjusting to multiple heights is as simple as resetting four screws and dual pull out shelves provide room for a laptop, projector, and document camera. Lower cabinet stores additional equipment.

| •.• | | | | |
|---------|-----|---|-----|--|
| • | | | ÷. | |
| • • | e : | | | |
| •••• | | | | |
| <u></u> | | | ••• | |
| _ | _ | _ | _ | |
| - | | | | |
| _ | | | | |

Made In The USA



FEATURES

 $\left|\right\rangle$

- Affordable multimedia presentation cart incorporates your laptop, data projector, document camera, DVD player, scanner and more all on one compact platform.
- Features a 3-height capability, from 34"-42"h in 4" increments and is easily adjusted by resetting four leg screws.
- Two large 14"d shelves pull out from opposite sides on smooth rolling glides and allows you to easily integrate your notebook computer with projectors and other equipment.
- Pull out shelf supports are arc welded to the leg supports for a strong and secure platform to support equipment.
- Durable all-steel construction with black powder paint finish feature legs welded to the shelves so minimal assembly time is required.
- Includes a roomy lockable storage cabinet with two keys and a rear grommet hole for cord management.
- Rolls smoothly on 4" "Quiet Glide" casters, 2 locking.
- Die-pressed shelves have a 1/4" lip to prevent equipment from accidentally sliding off while in transport.
- Top shelf includes a ribbed rubber mat.
- Recommended for use with a projector, document camera and notebook computer.
- 6-outlet electrical unit available with built-in cord winder and 20' extension cord lets you set up anywhere in the room and still reach an electrical outlet. Electrical units are standard on CA2642DNS "E" models.
- CA2642DNS series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle.
- Made in the USA.



5

7

DIMENSIONS

Overall: 24"w x 18"d x 34-42"h Top Shelf: 24"w x 18"d Pull Out Shelves: 20"w x 14"d, supports up to 15 lbs. Pull Out Shelf Height Clearance: 2-1/2"h Middle to Notebook Shelf: 1-3/4"-9-3/4"h Cabinet Interior: 23-1/2"w x 17-1/2"d x 15-1/2"h

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 15 lbs.

NOTE: The pull out shelves are designed for use with a notebook computer, projector and like items. Objects greater than 15 lbs should not be used on the pull out shelf as it may cause a tip hazard when the shelf is extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (BK) powder paint

STANDARD EQUIPMENT

24"w x 18"d Shelves (1) 20"w x 14"d Pull Out Shelves (2) Lower cabinet section (1) 14" Glides (2 sets) 1" round plastic caster insert (4) 4" diameter casters (4) 18" x 24" Rubber Mat (1) Keys for cabinet lock (2) 6-outlet electrical unit (1) [CA2642DNS "E" models only]

WEIGHT AND FREIGHT CLASS 94 lbs.

CA2642DNS: CA2642DNSE:



96 lbs. Freight class 85. All available to ship via UPS Ships ready to assemble in one (1) carton pack

ACCESSORIES

E6 Electrical assembly with 6-outlets, on/off surge switch, 20 ft. grounded extension cord, and cord winder. [Standard on CA2642DNS "E" models.]

4" CASTER CART CARTON DIMS & UPC CODE

26"w x 20"d x 32"h CA2642DNS: 0 96633 34387 4 CA2642DNSE: 0 96633 34388 1

5" CASTER CART CARTON DIMS & UPC CODE

26"w x 20"d x 32"h CA2642DNS-P5: 0 96633 34389 8 CA2642DNS-E5: 0 96633 34390 4

MADE IN THE USA

The CA2642DNS adjustable cart is made at Bretford's Chicago area manufacturing facility using union labor.



ENVIRONMENTAL SPECIFICATIONS

The CA2642DNS adjustable carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. CA2642DNS series carts are pending certification to GREENGUARD Children & Schools Indoor Air Quality standards.

SUGGESTED SPECIFICATIONS

CA2642DNS series adjustable cabinet carts have three (3) 20-gauge steel 18" x 24" shelves. Shelves are press formed with a 1/4" lip bordering the top surface on all four sides. The top shelf has a 20gauge steel stiffener electrically welded underneath the surface front to back. A Black rubber mat 18" x 24" is placed on the top shelf. Two 14"D x 20"W pull out shelves pulls out from opposite sides under the top shelf on 14" glides. The pull out shelves mount to two steel plates that are arc welded between the leg posts on the upper portion of the cart and each supports up to 15 lbs. of equipment. Top shelf has two (2) 3/16" diameter holes centered on the right side, left side and rear to accept an optional electrical assembly. Table has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs 21-1/4" long welded to the shelf at each corner. Each leg has two (2) 1/4" diameter holes near the bottom of the section and in the center of the leg that will accept a 1/4-20 machine screw. The holes are spaced 4" apart to permit height adjustments of 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by the machine screw. The bottom section of the adjustable table consists of a 20-gauge steel cabinet of interior dimensions 23"W x 15-1/2"H x 17"D. There are four (4) 14-gauge steel 19" legs welded to the cabinet at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg that will accept a 1/4-20 machine screw. Holes are 4" apart to permit table height adjustments (as noted above). Cabinet has one (1) 20-gauge steel stiffener spot welded top to bottom. Model has a black powder paint finish. A hard plastic caster insert is mounted to each leg. Casters are mar-resistant Black hard rubber and 4" in diameter. Each caster assembly has ball bearing swivel capabilities and steel construction. Two (2) have locking brakes. Optional electrical assembly provides six (6) grounded outlets with surge suppression. Includes 20 ft. 3-wire cord, cord winder, and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. CA2642DNS "E" models come standard with the 6-outlet electrical assembly. CA2642DNS Projector Cart ships ready to assemble in one (1) carton and is able to ship via UPS.

5

11000 SEYMOUR AVENUE FRANKLIN PARK, ILLINOIS 60131 USA TOLL FREE PHONE 800-521-9614 PHONE 847-678-2545 TOLL FREE FAX 800-343-1779 FAX 847-678-0852 WWW.BRETFORD.COM