



The CIS Series is comprised of compact twoway flush-mount loudspeakers designed for fixed installation into typical ceiling plenum spaces. Using a HF waveguide originally developed for studio monitors and an optimized woofer, the CIS Series delivers superior dispersion and pattern control.

Operating Range (-10 dB, Hz) 70 - 22k (varies per model)

Calculated Maximum Output Peak (dB SPL) Full-range: 108 to 113

Subsystems

LF: 4 to 6.5-in cone, sealed

HF: 1-in dome tweeter

Models & Coverage (deg, H x V) CIS300 (140 x 124)

CIS400 (110 x 110)

Versions

White



## SMS1000, 2000 & 4000 Series

The SMS1000, SMS2000 and SMS4000 Series advance the state of the art for small loudspeaker technology, providing superior quality sound, excellent directivity control, and practical installation options in a variety of fidelity and speech intelligibility, combined sizes and scales.

Operating Range (-10 dB, Hz) Full-range: 82 - 20k (varies per model)

Calculated Maximum Output Peak (dB SPL) Full-range: 111 to 122

Subsystems

LF: 2x 3-in to 4x 4-in cones

HF: 1x 1-in to 3x 2-in dome tweeters, horn-loaded

Models & Coverage (deg, H x V) SMS1990 (90 x 90)

SMS2124 (120 x 40)

SMS2990 (90 x 90) SMS4124 (120 x 40)

SMS4940 (90 x 40) SMS4990 (90 x 90)

Versions Black or White



## SMS3, SMS4 & SMS5

The SMS3, 4 and 5 are two-way constant directivity compact loudspeakers in easilyinstalled enclosures. The result of careful acoustic design and the use of advanced materials, they provide exceptional music with scalable output levels.

Operating Range (-10 dB, Hz)

Full-range: 55 - 25k (varies per model)

Calculated Maximum Output Peak (dB SPL) Full-range: 111 to 116

Nominal Coverage (degrees)

Horizontal: 110 / Vertical: 110 Subsystems

LF: 5-in cone

HF: 0.75-in dome tweeter, horn-loaded

Models SMS3 SMS4

SMS5

Versions Black or White









