

BRETFORD BASICS™

PRE-ASSEMBLED NOTEBOOK STORAGE CARTS

LAP18EFR-GM, LAP18EBA-GM, LAP18ERBFR-GM & LAP18ERBBA-GM



Made In The USA

LAP18EFR & LAP18EBA Series Carts have been tested by TUV to UL 60950 Safety of Informational Technology Standards for the United States and Canadian markets.

LAP18EULFR-GM & LAP18EULBA-GM



LAP18EULFR & LAP18EULBA Carts have been tested by TUV & UL to UL 60950 Safety of Informational Technology Standards for the United States and Canadian markets.



FEATURES

- Welded and fully assembled at the factory, simply uncrate and use.
- Stores and charges up to 18 laptop computers in individual compartments and provides room on the top shelf for a work surface or for use with printers.
- Top shelf comes with a non-slip rubber mat and features two grommet holes at the back for cord management and access to electrical units.
- Laptops lay flat, not on their side, when storing and charging.
- Includes two UL listed, 9 outlet electrical units with overload protection, on/off switch and 20' power cord for charging laptops and powering other equipment. Note: electrical units must be plugged into separate circuits to prevent tripping breaker when all outlets are in use.
- Electrical units can be ordered installed inside the front or the back of the cart.
- Optional automatic timer/charger unit available providing ability to charge all laptops using one circuit. Timer is included in the UL Listed version of the cart. In either case, the timer is installed inside the rear of the cart with access through cut outs in the back panel.
- Also includes an additional three-outlet electrical unit that attaches to the back for power equipment.
- Rear grommet holes and cord winders on the back panel allow the extra electrical power cord to be neatly wound up out of the way when moving the cart from one place to another.
- Bolting doors and a re-programmable padlock helps to deter theft, padlock included. Doors, rear and side panels are perforated to allow the ventilation of equipment when charging and built in handles aid in moving the cart.
- Standard 5" casters provide easy mobility over carpet or 8" soft rubber casters for transporting over rough surfaces or between buildings.
- Constructed using an average 30% post-consumer recycled steel content and finished in environmentally friendly powder paint. Steel components are 100% recyclable at the end of the product life cycle. Laptop computer carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.
- Made in the USA.

A HIGHER FORM OF FUNCTION



BRETFORD

DIMENSIONS

LAP18EULFR-GM, LAP18EULBA, LAP18EFR-GM & LAP18EBA Overall:

36-1/2" w x 24" d x 43-15/16" h

LAP18ERBFR-GM & LAP18ERBBA-GM Overall:

36-1/2" w x 24" d x 47-5/16" h

Space Available for Each Laptop:

14-11/16" w x 17" d x 3" h

COLOR & FINISH

Grey Mist (-GM) powder paint

STANDARD EQUIPMENT

36-1/4" w x 24-1/4" d Top Shelf (1)

36-1/4" w x 24-1/4" d Bottom Shelf (1)

34-1/4" w x 17" d Interior Shelves (7)

9 Outlet Electrical Units (2)

3 Outlet Electrical Unit (1)

Leg Supports (4)

5" Plate Casters (4) or 8" Soft Rubber Casters (4)

Handle (1)

Three Dial Combination Padlock (1)

Rubber Mat (1)

WEIGHT AND FREIGHT CLASS

LAP18EULFR-GM & LAP18EULBA-GM: 232 lbs., Freight class 125

Ships assembled in one (1) carton

LAP18EFR-GM & LAP18EBA-GM: 224 lbs., Freight class 125

Ships assembled in one (1) carton

LAP18ERBFR-GM & LAP18ERBBA-GM: 242 lbs., Freight class 125

Ships assembled in one (1) carton

CARTON DIMENSIONS & UPC CODE

LAP18EULFR-GM - Front Electrical Units, Timer - 0 96633 22933

LAP18EULBA-GM - Rear Electrical Units, Timer - 0 96633 22932

Box Dims: 40-1/2"W x 25-1/2"D x 44-3/4"H / 232 lbs.

LAP18EFR-GM - Front Electrical Units, 5" Casters - 0 96633 22748 8

LAP18EBA-GM - Rear Electrical Units, 5" Casters - 0 96633 22747 1

Box Dims: 40-1/2"W x 25-1/2"D x 44-3/4"H / 224 lbs.

LAP18ERBFR-GM - Front Electrical Units, 8" Casters - 0 96633 22754 9

LAP18ERBBA-GM - Rear Electrical Units, 8" Casters - 0 96633 22753 2

Box Dims: 43" w x 25-1/2" d x 48-1/2" h / 242 lbs.

Note: All computer carts are secured to a 42" w x 30" d skid at the time of shipping. Carriers are instructed not to remove the product from the skid to prevent damage.

ENVIRONMENTAL SPECIFICATIONS


Laptop computer carts are constructed with "prime" steel which has a 25% to 35% post-consumer recycled content. All steel components are recyclable at the end of the product life cycle. Laptop carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

MADE IN THE USA

LAP series laptop storage carts are made at Bretford's Chicago area manufacturing facility using union labor.



SHELF DIMENSIONS FOR LAPTOP COMPUTERS



SUGGESTED SPECIFICATIONS

Pre-Assembled Notebook Storage Cart shall have one (1) 36-1/4" w x 24" d, 18-gauge steel work surface shelf which shall have two (2) 2" diameter grommet holes in rear of shelf. The underside of the work surface shall have one (1) 18-gauge stiffener with two 28.5mm holes for optional security cable. Work surface shall be covered with black rubber mat. Cart shall also have one (1) 36-1/4" w x 24" d, 18-gauge steel bottom shelf, eight (8) 34-1/4" w x 17" d, 18-gauge interior shelves, two (2) 30-7/8" h x 18-1/2" w, 20-gauge outer and inside panels, one (1) 34-1/2" w x 30-7/8" d, 20-gauge back panel and two (2) 30-7/8" w x 17-1/8" d, 20-gauge doors. Doors shall have multiple-point locking system with re-programmable, three-dial combination padlock. Interior shelves shall have 2 x 2 cut-outs in rear corners. Back panel has two (2) 2" diameter grommet holes located at the bottom rear and on outside back panel there are two (2) cord winders for cord management. Back panel also has two cut outs to accommodate the automatic timer near the bottom of the cart. All panels shall have ventilation holes throughout. Unit shall have two (2) UL listed, nine (9) outlet electrical units which shall be attached inside the cart to top and bottom shelves. Electrical units must be ordered installed inside the front or back of the cart. Unit also shall have one three (3) outlet electrical unit which attaches to the back of the unit. Unit has four (4) 5" plate casters, two rigid and two swivel, or four (4) 8" rubber casters, two rigid and two swivel, with locking brakes. Cart shall have two (2) push handles. Each model is painted in grey powder coated paint and constructed from "prime" steel which contains 25% to 35% post-consumer materials. Ships pre-assembled by truck only. UL Listed carts shall also include an automatic timer installed inside the rear of the cart with access through holes cut in the back panel (see photograph below).

ELECTRICAL UNIT SPECIFICATIONS

Electrical units are UL listed, overload protected, includes a 20' power cord, and has an on/off switch located at the base. When using both electrical units at the same time, each unit must be plugged into outlets on separate electrical circuits. This is to prevent the overload and tripping of the circuit breaker. The electrical units are rated for a maximum of 15 amps usage each, however, to prevent nuisance tripping of the breaker you should not exceed 13 amps of usage each for an extended period of time.

11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM