



LCD Lift

Bomb bay doors and a slim cross-section distinguish the LCD Lift. Most popular projectors fit easily inside this unit, which is available in two sizes—Model A and Model B. Choose between bomb bay style closure doors or flat ceiling closure panel.

Environmental Airspace Housing is standard. Contains internal switched duplex receptacle, 115V AC, which is powered when the unit is fully down. The LCD Lift contains an innovative current sensor that delays closing of the unit until the projector lamp has shut off. Lifting capacity 65 lbs.

System Options

- **Ceiling Closure Panel**—Ceiling closure is standard with lift; choose between bomb bay style or flat ceiling closure panel.
- **Ceiling Access Door**—A 2' x 2' hinged door to access lift above a finished ceiling for cleaning, maintenance or repairs without having to damage the ceiling. Available with a white painted finish or recessed to accept ceiling tile.
- **Factory installed cables**—for Video and Projector Control. Draper will install cables on the lift to save installation time in the field.
- **Controls**—Includes 1 wall switch. Visit website for other control options.

Dimensions, drawings and specifications available at:
www.draperinc.com/go/LCDLift.htm

Manitowoc Beverage Equipment, Sellersburg, IN. Installation by ISSG and photography © Kenneth Hayden, both of Louisville, KY.



AeroLifts

Three models to lift up to 25, 50 or 150 lbs. With a simplified design, AeroLifts install in even the tightest spots. They offer a different look than the mechanical one of scissor lifts.

All three models are powered by strong tubular motors for a simplified design, and feature a stabilizing arm which can be used for cable management. Built-in adjustability allows you to deal with job site conditions quickly and easily, like slightly out of square or irregularly spaced joists. Projector can be mounted flush to bottom pan.

Note: The AeroLift 25, 50 and 150 can also be used to recess speakers, security cameras, videoconferencing cameras or document cameras.

System Options

- **Environmental Airspace Housing**—Aluminum housing isolates projector and lift from environmental airspace above the ceiling.
- **Ceiling closure panel**—Universal steel ceiling closure in a white finish or recessed to accept ceiling tile.
Shown in photo at right.
- **Ceiling finish kit**—Ceiling closure panel and ceiling trim ring to finish ceiling opening.
- **Control Options**—Operated by one 115V rocker switch. For more options, visit our website.

Dimensions, drawings and specifications available at:
www.draperinc.com/go/AeroLift.htm



	AeroLift 25	AeroLift 50	AeroLift 150
Height of lift in closed position ¹	4"	6¼"	6¼"
Max. overall lift dims (w x l)	22¼" x 14"	28¼" x 15"	31¼" x 15¾"
Max. down travel	20"	32"	32"
Approx. travel time to lowest position	14 sec.	23 sec.	23 sec.
Total Capacity (lbs.)	25	50	150
Net weight of lift (lbs.)	20	28	32

¹ Only height of AeroLift in closed position. Overall height of projector, plus mount, plus optional ceiling closure, plus optional plenum housing adds to overall height of equipment installed above ceiling.