



CLOUD12 Baffle



C12BB3 backbox with C12SQGL grille

APPLICATIONS

- Convention centers
- Exhibit halls
- Corporate training rooms
- Ballrooms
- Swimming pools
- Sports facilities and health clubs
- Houses of worship
- Shopping malls
- Airports

FEATURES

- Rugged 12-inch cast frame LF driver
- Tuned, ported bass reflex design
- Powerful 200W continuous, 500W program power handling
- Precise pattern control HF horn
- Built-in protection circuitry
- Selectable midband attenuation
- Smooth, uniform frequency response
- 60° x 60° and 90° x 90° dispersion patterns
- Fast and easy installation
- Optional backbox, grille and tile rails
- ETL listed

Both the CLOUD12 and CLOUD12SUB are designed to easily match with industry standard 12-inch ceiling backboxes, grilles and tile bridges. To make installation even easier, Community offers complete accessories. The optional, optimally-tuned 3.0 cubic foot C12BB3 is the stiffest and longest backbox available with 23 welded-in steel reinforcing ribs. Painted in low luster black, the C12BB3 backbox also includes knockouts for hard pipe or flex conduit and four rear-mounted ¼-20 welded-in nuts so that each enclosure can be flown from forged eyebolts. An attractive square perforated painted steel grille is also available, together with 24-inch, 30-inch and 48-inch channel rails.

Model	Drivers	Operating Range	Sensitivity (free space)	Power Handling (PGM)	Impedance	Dispersion (conical)	Dimensions H x W x D
CLOUD1266	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	97 dB	500W	8 ohms	60°	6.9 x 14.6 x 14.6 in. (176 x 371 x 371 mm)
CLOUD1266T	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	96 dB	200W (70W/100V)	Varies by tap	60°	6.9 x 14.6 x 14.6 in. (176 x 371 x 371 mm)
CLOUD1299	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	95 dB	500W	8 ohms	90°	6.9 x 14.6 x 14.6 in. (178 x 371 x 371 mm)
CLOUD1299T	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	94 dB	200W (70W/100V)	Varies by tap	90°	6.9 x 14.6 x 14.6 in. (176 x 371 x 371 mm)
CLOUD12SUB	LF 1 x 12"	45 Hz - 150 Hz	89 dB	500W	8 ohms	360° x 180°	8.5 x 14.6 x 14.6 in. (216 x 371 x 371 mm)
CLOUD12SUB-T	LF 1 x 12"	45 Hz - 150 Hz	89 dB	200W (70W/100V)	Varies by tap	360° x 180°	8.5 x 14.6 x 14.6 in. (216 x 371 x 371 mm)