



Each Commercial Design model is a true coaxial loudspeaker, with a compression driver concentrically located so that the high frequencies emerge through the center of the low-frequency driver's magnetic structure and cone via a precisely contoured Tru-Phase™ HF Waveguide. This special construction provides consistent, wide dispersion up to 16 kHz.

APPLICATIONS

- Convention centers, exhibit halls
- Corporate training rooms
- Hotels, ballrooms
- Athletic venues, sports facilities, health clubs
- Houses of worship
- Malls, airports
- Retail environments, shopping malls
- Nightclubs, bars, restaurants

FEATURES

- Comprehensive family, featuring similar components and uniform voicing
- Coaxial HF compression drivers
- High intelligibility, uniform coverage
- High efficiency, high output
- Selectable 8 ohm or 70V/100V operation

Thanks to the internally reinforced, paintable ABS enclosures, zinc-rich epoxy dual-layer powder coated grilles and brackets, weather-treated drivers, and the included IP56 sealed wiring cover, all standard surface mount models are equally suited for indoor or Continuous Outdoor Direct Exposure applications.

Finally, the CP6 is a 6.5-inch full-range pendant loudspeaker utilizing the same components as the C6 ceiling model and CS6 surface mount model, including the built-in, full output autoformer. An easy-access 8 ohm or 70V/100V operation selector switch is conveniently located on the face of the loudspeaker, while an integrated rear cover hides all wiring and hanging hardware for an aesthetically pleasing installation.

All of the Commercial Design ceiling and pendant loudspeakers are ETL listed.

Model	Drivers	Operating Range	Sensitivity (1W/1m)	Power Handling (PGM)	Impedance	Dispersion (conical)	Dimensions H x W x D
C4LP	LF 1 x 4.5" HF 1 x 3/4"	90 Hz - 13.5 kHz	91 dB	150W	8 ohm or 70V/100V	130°	8.3 x 8.3 x 3.6 in. (211 x 211 x 92 mm)
C4	LF 1 x 4.5" HF 1 x 3/4"	75 Hz - 13.5 kHz	91 dB	150W	8 ohm or 70V/100V	130°	8.3 x 8.3 x 5.5 in. (211 x 211 x 140 mm)
C6	LF 1 x 6.5" HF 1 x 3/4"	70 Hz - 13.5 kHz	91 dB	150W	8 ohm or 70V/100V	120°	9.8 x 9.8 x 6.5 in. (249 x 249 x 165 mm)
C8	LF 1 x 8" HF 1 x 3/4"	65 Hz - 13.5 kHz	91 dB	150W	8 ohm or 70V/100V	120°	11.3 x 11.3 x 7.6 in. (287 x 287 x 192 mm)
CS4	LF 1 x 4.5" HF 1 x 3/4"	70 Hz - 13.5 kHz	90 dB	150W	8 ohm or 70V/100V	140°	6.4 x 9.6 x 6.5 in. (162 x 243 x 164 mm)
CS6	LF 1 x 6.5" HF 1 x 3/4"	65 Hz - 13.5 kHz	90 dB	150W	8 ohm or 70V/100V	120°	7 x 11.8 x 10.7 in. (177 x 300 x 272 mm)
CS8	LF 1 x 8" HF 1 x 3/4"	45 Hz - 13.5 Hz	89 dB	150W	8 ohm or 70V/100V	110°	9.7 x 13.8 x 12.4 in. (247 x 350 x 315 mm)
CP6	LF 1 x 6.5" HF 1 x 3/4"	70 Hz - 13.5 kHz	91 dB	150W	8 ohm or 70V/100V	120°	13.6 x 10 x 10 in. (346 x 254 x 254 mm)