

BRETFORD BASICS™

MULTIMEDIA HEIGHT ADJUSTABLE CABINET CART

ECILS3

Designed for computer projection in the classroom, training room, or anywhere a laptop drives the presentation. Height adjustable pull out laptop shelf with positions between 29" and 37" high is wide enough for both a laptop computer and a mouse pad. Large locking cabinet secures equipment and includes perforated holes to ventilate electronic equipment.



FEATURES

- Top shelf adjusts from 31" to 39"H in 1" increments and supports an overhead or data projector for presentations or up to 24" flat panel monitor which sits on the top shelf.
- Pull out notebook shelf is 29" to 37"H in 1" increments and can be set to seated or standing heights at time of assembly. Pull out shelf is 29"W x 13"D and always 2" lower than the top shelf.
- Cord management system includes grommet holes to feed power and data cables through the cabinet.
- Heavy-duty 1" square tubular legs with "W" bracket shelf design and all steel construction with die pressed shelves for maximum strength.
- Features 30% post-consumer recycled steel content and an environmentally friendly powder paint finish.
- Moves on 4" Quiet-Glide stem casters, two with locking brakes. Each caster is load rated to 115 lbs.
- Locking lower cabinet provides safe storage of electronics and equipment and includes grommet holes for cord management and is 23-3/4"D by 32"W; cabinet doors are 14"H. Cabinet may be equipped with a 6-outlet or 12-outlet electrical unit. 12-outlet electrical unit is included on ECILS3FF model.
- ECILS3 series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. ECILS3 series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Proudly made in the U.S.A. using union labor.

DIMENSIONS

Top Shelf/Overall Dims: 32-1/2" w x 24-1/4" d x 31" to 39" h
Pull Out Shelf: 29" w x 13" d x 29" to 37" h
Top Shelf & Work Surface Adjustment Increments: 1"
Storage Cabinet: 32" w x 23-3/4" d x 15-7/8" h
Storage Cabinet Doors: 14" h

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 20 lbs.

NOTE: The pull out shelf has been designed for use with a notebook computer and like items. Objects greater than 20 lbs should not be used on the pull out shelf as it may cause a tip hazard when the shelf is extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (-BK) powder paint

WEIGHT, FREIGHT CLASS AND UPC CODE

ECILS3-BK:	104 lbs.
	Freight class 70 UPS
	0 96633 25693 8
ECILS3FF-BK:	108 lbs.
	Freight class 70 UPS
	0 96633 25694 5



CARTON DIMENSIONS

ECILS3-BK:	35" l x 26-1/2" w x 8" d, 104 lbs.
ECILS3FF-BK:	35" l x 26-1/2" w x 8" d, 108 lbs.

ACCESSORIES

ECF6 - 6 Outlet Electrical Unit - 0 96633 33683 8
E12 - 12 Outlet Electrical Unit - 0 96633 33685 2

MADE IN THE USA

ECILS series carts are made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The ECILS3 series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. ECILS3 series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

CART ASSEMBLY SPECIFICATIONS

ECILS3 Height Adjustable Carts have one (1) 32-1/2" w x 24-1/4" d, 18-gauge steel top shelf with 20-gauge steel stiffener and open corners so the sides of the shelf do not connect. The upper leg assembly fits flush to the top shelf and attach with a 13-gauge steel "W" bracket design that interlocks the legs and shelves for maximum strength and stability. Upper leg assemblies are 1-1/2" square tubular 18-gauge steel and fit over the lower 1" square tubular 18-gauge steel leg assemblies for height adjustability of the top shelf. Lower leg assemblies form the corners of the lower cabinet and attach to the upper and lower shelves with a 13-gauge steel "W" mounting bracket with 1/4" square head bolts and hex nuts that hold leg securely to table. Perforated 20-gauge steel cabinet side panels mount using the square head bolts that secure the shelves to the legs. Cabinet interior is 32" w x 23-3/4" d x 15-7/8" h, cabinet doors are 14" h. Each lower leg has a hard plastic caster insert mounted in the bottom of the tube. Carts have one (1) 29" w x 13" d, 18-gauge steel pull-out shelf that extend off the front side. Shelf is height adjustable with the top shelf and may be set from 26-1/2" to 34-1/2" h in 1" increments. There is 2" clearance under the top shelf when pull out shelf is pushed in. Model ECILS3FF includes a surge and overload protected 12-outlet electrical assembly with on/off switch and 20' 3-wire cord and two (2) 3/16" diameter machine screws with nuts for attaching unit to the back panel of the cabinet. Stem casters are mar-resistant, hard black rubber, 4" in diameter. Each caster assembly has ball bearing swivel capabilities, steel construction and is load rated for 115 lbs each. Two (2) have locking brakes. Finished in Black (-BK) powder paint. Ships knocked down (KD) via truck LTL class 70 or via UPS.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETFORD.COM