

EXPLORE™ 4-LEG SERIES

TEAMING TABLE WITH FLUID POWER

Affordable collaboration tables feature a monitor mount and cord management to support sharing of data between three or five people.



Made In The USA



CarbonNeutral.com



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/CG
UL2818
GOLD



Tables include a Fluid Up power unit, Fluid Up power version must be specified at the time of order



FEATURES

- Mount recommended for up to 42" diagonal flat panel monitor, maximum of 40 lbs., to enable sharing of data and information from a mobile device with up to five people. Monitor features left and right as well as up and down swivel positioning.
- Work surface includes a Fluid Up power unit to provide easy power above the work surface to laptop, tablets, smart phones, and other devices. Power unit include two power outlets and two USB power jacks and is designed for stand alone use or to daisy chain multiple tables from a single outlet.
- Lower cord management bin may be equipped with a power strip or Fluid Down power unit. Fluid Down may be daisy chained to the Fluid Up unit, Power In-Feed and Jumper cables for daisy chain units are sold separately. All versions of Fluid Power work off a standard 15 amp electrical outlet.
- A center cable grommet provides simple user access to connect with the monitor and stores cables inside when not in use. Cables run from the back of the monitor under the table and up from the cable grommet and are accessed by simply pulling them out for use. Data cables are not included and need to be 10-feet or 3m in length.
- Center cable grommet includes a steel cable that may be used to secure devices to the table by the use of a micro-slot lock.
- Tables are available with 2.5" twin wheel casters, all with a locking brake, or with leveling glides for stationary configurations.
- Work surface is height adjustable from 22" to 32" in height in 1" increments on tables with casters. Tables with glides are height adjustable from 20" to 30".
- Monitor mount supports VESA mounting hole patterns of 75mm, 100mm, and 200mm square, or 200mm x 100mm.
- Work surface includes metal threaded inserts to mount the leg assemblies for a metal to metal connection that adds strength and greatly reduces the possibility screws will strip or fall out over time.
- Proudly made in the U.S.A. using union labor.



BRETFORD®

STANDARD FINISH OPTIONS

Work surface is available in Grey Mist laminate with matching Quartz trim or Natural Maple laminate with Aluminum trim. Powder paint steel bases and monitor mount are Aluminum. Monitor pole is natural aluminum only and Fluid Up power unit is always stand alone DPAUSB9-P.



-ALGM
Grey Mist top and
Aluminum base



-ALMP
Natural Maple top and
Aluminum base

PREMIUM FINISH OPTIONS

EDU 2.0 products are available to order in any paint, trim and laminate offered by Bretford. Work surfaces may be specified with a 3mm thermoplastic (TPE) t-mold (Edge 01), a 2mm polypropylene (PP) edge with 45° sealed MDF bevel (Edge 17), or a rounded edge sealed MDF with 22^{1/2}° bevel (Edge 08). To order product in premium finish specify paint, laminate, edge detail, and trim color for edges 01 and 17. Fluid Up power unit may be daisy chain or stand alone and is chosen by specifying the model at time of order.

Example:

EDUSDPT72⁽¹⁾-AN⁽²⁾-905⁽³⁾-01⁽⁴⁾-A⁽⁵⁾-DPAUSB9-P⁽⁶⁾

- ⁽¹⁾ = Base Model Number
- ⁽²⁾ = Anthracite Paint
- ⁽³⁾ = Recon Oak Laminate
- ⁽⁴⁾ = 3mm Thermoplastic Elastomer (TPE) Edge
- ⁽⁵⁾ = Anthracite Edge Finish
- ⁽⁶⁾ = Fluid Up Stand Alone Power Unit with USB Power

ELECTRICAL ACCESSORIES

EDU 2.0 4-Leg Teaming Tables include the Fluid Up power unit with the table, when applicable the power in-feed cables and jumper cables are sold separately.

Daisy Chain Fluid Up & Down Power System - Fluid Up 2-outlet power with USB power in a pop up door to provide power above the table top. Fluid Down has 4-outlets and mounts inside the cord management bin. Fluid uses a power in-feed and jumper cables to daisy chain tables off a single 15 amp circuit. UL Recognized system features overload protection.

Stand Alone Fluid Up Power System - 2-outlet power with USB power in a pop up door to provide power above the table top. UL Listed system features a 9-foot power cord with standard 3-prong plug.

Stand Alone Power Strip - 6-outlet power strip ECF6 may be mounted inside the cord bin. UL Listed strip features a 20-foot power cord with standard 3-prong plug.



The security grommet includes a vinyl coated aircraft cable that serves as a security point for devices using a micro-slot lock.

TABLE ACCESSORIES

EDUHMC Snap On Cord Minder Clip - Steel leg EDU 2.0 tables support the use of the snap on cord management clip that holds cords to the table leg from the cord bin to the floor.



OVERALL DIMENSIONS

42"d Tables with Glides:

- EDUSDPT60- - 60"w x 42"d x 20"-30"h
- EDUSDPT72- - 72"w x 42"d x 20"-30"h
- EDUSDPT84- - 84"w x 42"d x 20"-30"h

42"d Tables with Casters:

- EDUSDPT60C- - 60"w x 42"d x 22"-32"h
- EDUSDPT72C- - 72"w x 42"d x 22"-32"h
- EDUSDPT84C- - 84"w x 42"d x 22"-32"h

Cord Bin/Modesty:

- 60"L Table - 4^{1/2}"d x 5"h x 32"l
- 72"L Table - 4^{1/2}"d x 5"h x 44"l
- 84"L Table - 4^{1/2}"d x 5"h x 56"l

Table Edge to Cord Bin: 18^{3/4}" sides; 14" end, ADA Compliant

Fluid Up Power Cut Out: 8"w x 4"d

Monitor Mounting Pole: 22"h

Monitor VESA Mounting Hole Dimensions:

- 75mm, 100mm and 200mm square; 200mm x 100mm

SHIPPING INFORMATION

Tables with Glides:

- EDUSDPT60- - 174 lbs.
- EDUSDPT72- - 204 lbs.
- EDUSDPT84- - 233 lbs.

Tables with Casters:

- EDUSDPT60C- - 176 lbs.
- EDUSDPT72C- - 206 lbs.
- EDUSDPT84C- - 235 lbs.

Standard Finish Model Carton Dims:

- EDUSDPT60 & EDUSDPT60C - 63^{3/4}"l x 44^{1/2}"d x 9^{1/4}"h
- EDUSDPT72 & EDUSDPT72C - 72^{3/4}"l x 44^{1/2}"d x 9^{1/4}"h
- EDUSDPT84 & EDUSDPT84C - 87^{3/4}"l x 44^{1/2}"d x 9^{1/4}"h

Models ship ready to assemble in one carton pack.

UPC CODES STANDARD FINISH MODELS

SKU	Tables with Glides	
	ALGM	ALMP
EDUSDPT60-	0 96633 36950 8	0 96633 36956 0
EDUSDPT72-	0 96633 36951 5	0 96633 36957 7
EDUSDPT84-	0 96633 36952 2	0 96633 36958 4
SKU	Tables with Casters	
	ALGM	ALMP
EDUSDPT60C-	0 96633 36953 9	0 96633 36959 1
EDUSDPT72C-	0 96633 36954 6	0 96633 36960 7
EDUSDPT84C-	0 96633 36955 3	0 96633 36961 4



Each table features a center security grommet that allows data cables to be removed for use with a laptop, tablet, or other mobile device, and stored inside the table when not in use.

ENVIRONMENTAL & SAFETY SPECIFICATIONS

EDGE TRIM OPTIONS

Edge is constructed from thermoplastic elastomer (TPE), polypropylene (PP), or sealed MDF which, unlike PVC, are non-toxic, generates low pollution during manufacturing, are additive and phthalate free, and recyclable at the end of the product life cycle. TPE and MDF will break down in landfill conditions and not release harmful components and PP will remain inert.

POWDER COAT PAINT

All steel components are finished using a powder coat paint that greatly reduces VOCs while providing superior durability.

RECYCLED CONTENT

The work surface uses a MDF substrate that contains an average of 70% recycled content. Steel components are constructed with prime steel and feature a 25% to 35% post-consumer recycled content. Steel components are 100% recyclable at the end of the product life cycle.

ANSI-BIFMA TESTED

Tables are tested to and meet or exceed the ANSI-BIFMA x5.5-2008 standards for tables.

FOUR LOCKING CASTERS

Mobile EDU2.0 tables feature all four casters with locking brakes for stable configurations.

CARBON NEUTRAL

Bretford has achieved CarbonNeutral[®] company certification by reducing carbon footprint to net zero in accordance with the CarbonNeutral protocol. The EDU 2.0 line of EXPLORE tables have achieved Carbon-Neutral product certification.

GREENGUARD GOLD CERTIFIED

EXPLORE tables are certified to Underwriter Laboratories GREENGUARD GOLD air quality standards. GREENGUARD GOLD is referenced by both the Collaborative for High Performance Schools (CHPS) and the Leadership in Energy and Environmental Design (LEED) Building Rating System.

CONSTRUCTION SPECIFICATIONS

BASE

Upper and lower leg assemblies are constructed with 14-gauge flat oval tubing, which is formed using a CNC tube bender, and features arc welded connections to the mounting plate with two 3/16" gussets added for strength and support. The upper leg assembly mounts to the underside of the work surface with seven screws through a 3/16" thick steel plate. Each leg screw threads into metal inserts in the underside of the work surface for a strong fit. The lower leg assembly telescopes inside the upper assembly, allowing for height adjustability from 20" to 30" on tables with glides and 22" to 32" on tables with casters. Legs adjust in 1" increments. The lower leg is available with the choice of 2.5" diameter twin wheel casters, all with locking brakes, or with 1" adjustable leveling glides.

WORK SURFACE

Work surfaces on base models feature a 1" thick, 45 lb. density melamine top and premium finish models feature a 1" thick, 45 lb. density MDF core with .03" high-pressure laminate top and .03" backer. Table tops include a power cut out that is 8"W x 4"D with 1/8" corner radii, to accommodate a Fluid Up power unit. Fluid Up power units are included, daisy chain jumper cables and power in-feed cables are sold separately. The underside of the work surface includes 28 metal inserts that align with the leg mounting plates.

WORK SURFACE EDGE OPTIONS

Tables have a 3mm thermoplastic elastomer (TPE) t-mold edge, 2mm polypropylene (PP) bumper and sealed MDF bevel cut away at a reverse 45° angle, or a sealed MDF with rounded edge and cut away at a reverse 22.5° angle.

CORD MANAGEMENT

Tables include a cord management raceway constructed from 18-gauge steel and mounted to the center underside of the table top. Access to power and cord management is available from the underside of the work surface through a pair of 12"W x 4"H cut outs. A grommet hole is placed at the base of the mounting pole and a security grommet is placed at the center of the table. Cords run from the monitor under the table and up through the security grommet. Cords need to be 10-ft or 3m in length and are not included.

MONITOR MOUNT

A monitor mount attaches to one edge of the work surface and is intended for use with monitors up to 42" diagonal and no more than 40 lbs. Mount includes a 22" long extruded aluminum pole that includes cord management channels and multiple mounting holes spaced 1" apart. The monitor mount is a low profile mount that features left or right positioning and up or down rotation. For use with monitors with a 75mm and 100mm square mounting pattern or a 200mm x 100mm or 200mm x 200mm mounting pattern.

ADA COMPLIANCE

Teaming Tables meet table requirements for the Americans with Disability Act.

WARRANTY

Bretford warranties EDU2.0 Explore Series Tables for 12-years, at date of shipment, against defects from materials or workmanship. Electrical and data components, gas shocks, and fabric feature a 1-year warranty.

MADE IN THE USA

EXPLORE tables are made at Bretford's Chicago area manufacturing facility.



Teaming Tables can be combined with Explore Student Chairs to easily accommodate three or five students for group projects.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 660131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM