distribution amplifiers distribution amplifiers

Atlona 1 x 4 and 1 x 2 HDMI Distribution Amplifiers

This distribution amplifier supports Ultra HD (4Kx2K), advanced-EDID managemet and audio deembedding. For added reliability use an Atlona optional redundant power supply.

Atlona Advantages

PASSES ULTRA HD (4Kx2K)

LINK STATUS LED for source and outputs

ADVANCED EDID MANAGEMENT Learns reference EDID from first output device connected

CASCADE up to 8 distribution amplifiers (@1080p) for large systems

SUPPORTS 3D up to 48-bit Deep Color

PASSES DOLBY TRUE HD, DTS-HD MASTER AUDIO

LOCKING HDMI and power connectors

UPDATE IN THE FIELD via USB port

DUAL PURPOSE WALL MOUNT/RACK brackets

HDCAT-4 includes dual purpose wall mount/rack brackets

HDCAT-2 integrates via Velcro strips and captive screw power termination





[model no. AT-HDDA-4]

[model no. AT-HDDA-2]



Atlona 1 x 4 VGA Distribution Amplifier w/Audio

AT-VGA14A

The distribution amplifier with audio featuring high resolution support for four VGA outputs. Self-powered—at lower resolutions and with most computers no external power is necessary.

Atlona Advantages

HIGH RESOLUTION VIDEO SUPPORT Distributes VGA up to 2048x1536 @ 60/70/85Hz

STEREO AUDIO SUPPORT with 3.5 mm stereo audio jacks
SELF-POWERED can be powered via VGA input from a compatible PC

SELL FOVERED can be powered via Var impat from a compatible f

(5V DC power supply is included)



Atlona 1 x 2 VGA Distribution Amplifier w/Audio

AT-VGA12A

The affordable amplifier with audio featuring high resolution support for two VGA outputs. Self-powered—at lower resolutions and with most computers no external power is necessary.

Atlona Advantages

HIGH RESOLUTION VIDEO SUPPORT Distributes VGA up to 2048x1536 @ 60/70/85Hz

STEREO AUDIO SUPPORT with 3.5 mm stereo audio jacks

SELF-POWERED can be powered via VGA input from a compatible PC (5V DC power supply is included)

AUX USB POWER PORT offers additional option to power unit via compatible USB connection

