

BRETFORD BASICS™

WELDED CABINET PRESENTATION CART WITH 19" RACK MOUNT

MOBILE 19" RACK MOUNT WELDED PRESENTATION CART

TC15SA has a welded frame for easier assembly and features a locking lower cabinet with 19" rack mount and front and rear door for easy access to cords. Supports a projector, laptop, document camera and other equipment for presentations.



TC15SA-BK

FEATURES

- Welded frame ships with the lower cabinet and doors fully assembled, greatly reducing the amount of time required for installation.
- Lower cabinet features a 19" rack mount for DVD players and other electronics while top shelf and two pull out shelves support a data projector, notebook computer, and document camera. Ideal for use during multimedia presentations.
- Pull-out shelves located on both the left and right sides nearly double the work surface! Each shelf is 14"d x 20-3/4"w and have 3-1/4" clearance below the top shelf. Pull out at a 37" standing height.
- Locking lower cabinet includes a 19" rack mount system with 16 unit spacing and two rack mounted accessory shelves. Front and rear locking doors provide easy access to cords and controls. Cabinet may be equipped with a 12-outlet electrical unit, electrical unit, standard on TC15SAFF models.
- Heavy-duty 1" square tubular legs with "W" bracket shelf design for maximum strength.
- All-steel construction with die pressed shelves.
- 4" Quiet-Glide stem casters, two are locking. Each caster is load rated to 115 lbs.
- TC15SAFF includes a surge protected, 12-outlet electrical assembly with on/off switch and 20' grounded power cord. Electrical unit mounts inside the lower cabinet.
- TC15SA series carts feature a steel content with 25% to 35% post-consumer recycled steel and are recyclable at the end of the product life cycle. TC15SA series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.

DIMENSIONS

TC15SA Overall: 32" w x 24" d x 42" h
Storage Cabinet: 30" w x 23" d x 27" h
Storage Cabinet Doors: 21-3/4" w x 25" h
Pull Out Shelves: 14" w x 20-3/4" d
Pull Out Shelves to Floor: 37" h
Pull Out Shelves Clearance to Top Shelf: 3-1/4" h

PULL OUT SHELF WEIGHT CAPACITY

Shelf Load: 20 lbs.

NOTE: The pull out shelves are designed for use with a notebook computer, projector and like items. Objects over than 20 lbs should not be used on the pull out shelves as it may cause a tip hazard when shelves are extended and potentially cause deformation of the glides.

COLOR & FINISH

Black (-BK) powder paint

WEIGHT, FREIGHT CLASS AND UPC CODE

TC15SA-BK: 154 lbs., Freight class 70
0 96633 30509 4
TC15SAFF-BK: 158 lbs., Freight class 70
0 96633 30510 0

Both ship ready to assemble in one (1) carton pack and are available to ship via LTL Truck.

CARTON DIMENSIONS

TC15SA & TC15SAFF: 37" l x 29" w x 41" d

ACCESSORIES

ECF6 - 6 Outlet Elec. Unit (incl. on FF models) - 0 96633 33683 8
E12 - 12 Outlet Electrical Unit - 0 96633 33685 2

MADE IN THE USA

TC series carts are made at Bretford's Chicago area manufacturing facility using union labor.



Locking front and rear doors provide easy access to 19" rack mounted equipment. Shown with 19" rack mounted drawer, not sold by Bretford.



ENVIRONMENTAL SPECIFICATIONS

The TC15SA series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and is recyclable at the end of the product life cycle. TC15SA series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

CART ASSEMBLY SPECIFICATIONS

TC15SA 19" Rack Mount Technology Carts feature a welded cabinet assembly and has one (1) 32" w x 24" d, 18-gauge steel top shelf with 20-gauge steel stiffener. Top shelf has open corners so the sides of the shelf do not connect. The cabinet leg assembly fits flush to the top shelf and attach with a 13-gauge steel "W" bracket design that interlocks the legs and shelves for maximum strength and stability. Leg assemblies are 1" square tubular 18-gauge steel and run the height of the cart and form the corners of the lower cabinet. The lower cabinet shelves and side panels are welded to the leg assemblies. Door assemblies allow access to both sides of the cabinet and lock using a key lock, four (4) keys included. Cabinet side panels and doors are perforated 20-gauge steel to ventilate equipment. Cabinet interior is 23" w x 30" d, cabinet doors are 21-3/4" w x 25" h. A 19" rack mount assembly is installed inside the cabinet with 16 unit spacing for rack mount equipment. Two (2) 19" rack compatible accessory shelves are included. Each lower leg has a hard plastic caster insert mounted in the bottom of the tube. Includes two (2) 14" d x 20-3/4" w, 18-gauge steel pull-out shelves that extend off the left and right sides. Shelves are set at 37" standing height and there is 3-1/4" clearance under the top shelf when shelves are pushed in. Model TC15SAFF includes a surge protected 12-outlet electrical assembly with on/off switch and 20' 3-wire cord and two (2) 3/16" diameter machine screws with nuts for attaching unit to the inner cabinet. Stem casters are mar-resistant, hard black rubber, 4" in diameter. Each caster assembly has ball bearing swivel capabilities, steel construction and is load rated for 115 lbs each. Two (2) have locking brakes. Finished in Black (-BK) powder paint. Ships knocked down (KD) via LTL truck class 70.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM