



The compact V2-6, V2-8, V2-26 and V2-28, as well as the three-way V2-32 and V2-35, feature rotatable horns for horizontal installation.

APPLICATIONS

- Houses of worship
- Meeting rooms, board rooms
- Bars and restaurants
- Nightclubs and dance clubs
- Retail environments, fitness centers
- Auditoria

FEATURES

- High intelligibility and musicality
- High sensitivity, high output
- Versatile and scalable, front-of-house, fill and distributed applications
- Attractive trapezoidal enclosures
- Rotatable horns on compact and three-way models
- Multiple horn patterns available on full-size models
- All models available in black or white
- Included multi-angle vertical/horizontal yoke with compact models
- Optional 70V/100V autoformers available on compact models
- Multiple cost-effective bracket kits

Model	Drivers	Operating Range	Sensitivity	Power Handling (PGM)	Impedance	Dispersion (H x V)	Dimensions H x W x D
V2-6 (V2-6T)	LF 1 x 6" HF 1 x 1"	90 Hz - 18 kHz	92 dB	250W (100W)	8 ohms (Various)	90°x 70°	15.5 x 9.8 x 10.15 in. (395 x 249 x 258 mm)
V2-8 (V2-8T)	LF 1 x 8" HF 1 x 1"	70 Hz - 18 kHz	92 dB	375W (100W)	8 ohms (Various)	90°x 70°	17 x 11.3 x 11.7 in. (433 x 287 x 298 mm)
V2-26 (V2-26T)	LF 2 x 6" HF 1 x 1"	70 Hz - 18 kHz	92 dB	500W (200W)	4 ohms (Various)	90°x 70°	22.5 x 9.8 x 10.1 in. (573 x 249 x 258 mm)
V2-28 (V2-28T)	LF 2 x 8" HF 1 x 1"	60 Hz - 18 kHz	94 dB	750W (200W)	4 ohms (Various)	90°x 70°	25.5 x 11.3 x 11.7 in. (649 x 287 x 298 mm)
V2-1264	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	98 dB	500W	8 ohms	60°x 40°	23.9 x 15.4 x 14.3 in. (608 x 390 x 362 mm)
V2-1296	LF 1 x 12" HF 1 x 1"	60 Hz - 18 kHz	98 dB	500W	8 ohms	90°x 60°	23.9 x 15.4 x 14.3 in. (608 x 390 x 362 mm)
V2-1564	LF 1 x 15" HF 1 x 1"	60 Hz - 18 kHz	99 dB	500W	8 ohms	60°x 40°	27.2 x 18.4 x 15.9 in. (690 x 467 x 404 mm)
V2-1596	LF 1 x 15" HF 1 x 1"	60 Hz - 18 kHz	98 dB	500W	8 ohms	90°x 60°	27.2 x 18.4 x 15.9 in. (690 x 467 x 404 mm)
V2-3264	LF 1 x 12" MF 1 x 6.5" HF 1 x 1"	60 Hz - 18 kHz	100 dB	500W	8 ohms	60°x 40°	29.3 x 17.4 x 15.4 in. (744 x 441 x 390 mm)
V2-3294	LF 1 x 12" MF 1 x 6.5" HF 1 x 1"	60 Hz - 18 kHz	99 dB	500W	8 ohms	90°x 40°	29.3 x 17.4 x 15.4 in. (744 x 441 x 390 mm)
V2-3564	LF 1 x 15" MF 1 x 6.5" HF 1 x 1"	55 Hz - 18 kHz	100 dB	500W	8 ohms	60°x 40°	32.4 x 18.4 x 15.9 in. (824 x 467 x 404 mm)
V2-3594	LF 1 x 15" MF 1 x 6.5" HF 1 x 1"	55 Hz - 18 kHz	99 dB	500W	8 ohms	90°x 40°	32.4 x 18.4 x 15.9 in. (824 x 467 x 404 mm)
V2-210S	LF 2 x 10"	40 Hz - 500 Hz	96 dB	750W	4 ohms	360°x 180°	11.9 x 32.7 x 15.9 in. (303 x 830 x 404 mm)
V2-212S	LF 2 x 12"	37 Hz - 500 Hz	98 dB	750W	4 ohms	360°x 180°	13.9 x 35.9 x 17.9 in. (354 x 912 x 455 mm)
V2-215S	LF 2 x 15"	37 Hz - 2 kHz	97 dB	1000W	4 ohms	360°x 180°	18.4 x 37.4 x 20.4 in. (468 x 950 x 518 mm)