



**R.5-MAX**  
12-inch 2-way



**R2-MAX**  
Dual 12-inch 3-way



**R6-51**  
3-Way Multi-Driver Vertical Array

delivering high fidelity sound reinforcement over long distances with ease. Its very high output, wide range, smooth frequency response, and exceptional efficiency ensure both high fidelity music reproduction and superb projection of clear intelligible speech with very low distortion. The R6-51 is an extremely capable system using an innovative all horn loaded design of multiple driver vertical arrays. The resulting output and coverage pattern is ideal for applications requiring high impact, long throw full-range performance.

Compact R-Series models are available in standard grey, black and white finishes, while configure-to-order options are available for the full-size R2-MAX including custom color exterior paint finish based on an RAL number or a color sample, and custom length black or white cable. Each R.15, R.35 and R-MAX loudspeaker includes a weather-resistant mounting bracket for convenient installation.

Model	Drivers	Operating Range	Sensitivity 1W/1m	Power Handling (PGM)	Impedance	Dispersion (H x V)	Dimensions H x W x D
R.15COAX	LF 1 x 6.5" HF 1 x 1.25"	90 Hz - 16 kHz	94 dB	300W	8 ohm or 70V/100V	100° x 100°	9 x 10.15 x 10.2 in. (229 x 258 x 259 mm)
R.35COAX	LF 1 x 10" HF 1 x 1.25"	70 Hz - 16 kHz	97 dB	400W	8 ohm or 70V/100V	90° x 90°	11 x 13 x 13.5 in. (279 x 330 x 343 mm)
R.5COAX66	LF 1 x 12" HF 1 x 1"	80 Hz - 18 kHz	98 dB	500W (70V/100V)	8 ohm	60° x 60°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5COAX66T	LF 1 x 12" HF 1 x 1"	80 Hz - 18 kHz	97 dB	200W (70V/100V)	Varies by tap	60° x 60°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5COAX99	LF 1 x 12" HF 1 x 1"	80 Hz - 18 kHz	96 dB	500W	8 ohm	90° x 90°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5COAX99T	LF 1 x 12" HF 1 x 1"	80 Hz - 18 kHz	95 dB	200W	Varies by tap	90° x 90°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.35-3896	LF 1 x 8" MF 2 x 2.35" 1 x 1"	80 Hz - 16 kHz	98 dB	800W	8 ohm	90° x 60°	11 x 13 x 13.5 in. (279 x 330 x 343 mm)
R.5-66MAX	LF 1 x 12" HF 1 x 1.4"	70 Hz - 20 kHz	103 dB	1200W	8 ohm	60° x 60°	16 x 16 x 16.2 in. (406 x 406 x 411 mm)
R.5-96MAX	LF 1 x 12" HF 1 x 1.4"	70 Hz - 20 kHz	102 dB	1200W	8 ohm	90° x 60°	16 x 16 x 16.2 in. (406 x 406 x 411 mm)
R2-64MAX	LF 2 x 12" MF 1 x 2" HF 1 x 1.4"	70 Hz - 22 kHz	103 dB MF/HF: 108 dB	LF:2400W HF:300W	LF:8 ohm HF:8 ohm	60° x 40°	24.8 x 24.8 x 30.8 in. (629 x 629 x 781 mm)
R2-66MAX	LF 2 x 12" MF 1 x 2" HF 1 x 1.4"	70 Hz - 22 kHz	103 dB MF/HF: 108 dB	LF:2400W HF:350W	LF:8 ohm HF:8 ohm	60° x 60°	24.8 x 24.8 x 30.8 in. (629 x 629 x 781 mm)
R2-94MAX	LF 2 x 12" MF 1 x 2" HF 1 x 1.4"	70 Hz - 22 kHz	LF: 103 dB MF/HF: 107 dB	LF:2400W HF:300W	LF:8 ohm HF:8 ohm	90° x 40°	24.8 x 24.8 x 30.8 in. (629 x 629 x 781 mm)
R6-51BIAMP	LF 6 x 12" MF 6 x 2" HF 6 x 1"	50 Hz - 16 kHz	LF:109 dB MF/HF: 113 dB	LF:3000W HF:1100W	LF:4 ohm HF:8 ohm	50° x 10°	49 x 37 x 43.5 in. (1245 x 940 x 1105mm)