

LED L-PANEL

New, low profile, LED troffers are energy efficient and dimmable!

LED L-PANEL

Add dimmable 4100K LED light to offices, kitchens, studies, retail areas, work areas, and general/hospitality areas. L-Panels last up to 50,000 hours with no ballast service or lamp replacements required.



FEATURES

- Choose between surface mounted 1' x 4' with standoff hardware and recess mounted 2' x 2' fixtures
- Opaque frosted acrylic lens diffuses LED light evenly, eliminating any 'hot spots'
- Each panel utilizes 576 high performance 3528 type LEDs
- Long life LEDs last up to 50,000 hours eliminating frequent lamp replacements
- 4100K LED light with 80+ CRI offers a multi-purpose lighting tool in sleek, low profile housing
- Dimmable with Lutron LG-603PG wall dimmer (10-100% lighting control)
- 2 year warranty

FIXTURES

PK-1X4-41-S

1' x 4' Surface Mount
L-Panel

PK-2X2-41-R

2' x 2' Recess Mount
L-Panel

TECHNICAL SPECIFICATIONS

Voltage	120V AC, 60Hz operation
Construction	PC board in aluminum housing with frosted acrylic lens
Mounting	Surface mount with included standoff hardware (1'x4') or recess mount in grid ceiling (2'x2')
Dimensions	PK-1X4-41-R = 47-3/4" x 11-3/4" x 3-3/8", PK-2X2-41-R = 23-7/8" x 23-7/8" x 3-3/8"
Knockouts	Built-in wiring compartment with 1/2" knockout and WEGO quick connectors (installation requires one 1/2" standard cable connector/strain relief clamp, not included)
Light output	2700 lumens
Wattage	44 watts
Maximum run	N/A
LED Specs	50,000 hour rated life, 3528 LEDs, 4100K, 110° beam angle
Dimmers	For best results (10%-100% control) dim with Lutron LG-603PG wall dimmer
Diffuser	Frosted acrylic
Packaging	White box



H

