



AUTOMATED PROJECTOR MOUNTS

AUTOMATED PROJECTOR MOUNTS FEATURES



QUIET OPERATION

Provides exceptionally smooth and quiet movement, making it a great option for homes and corporate offices.



MULTIPLE CONTROL OPTIONS

Choose from single momentary push-button, low-voltage controller and IR options. Also accepts 5-30V AC/DC for triggering commands. AMX/Crestron control compatibility.



SAFE & SUSTAINABLE

CE, UL, TUV, FC and WEEE certifications recognize safe design and environmentally friendly construction.



MULTIPLE INSTALLATION OPTIONS

Multiple mounting options for finished and suspended ceilings including 1 1/2" NPT threaded extension columns, threaded rods and suspension cables.

SL220 SMART-LIFT



Simple 3-step installation process requires only one person. Designed to fit 2 x 2' (600 x 600 mm) suspended ceiling systems.

Weight Capacity	Extension	Max Projector Size (HxWxD)	Ceiling Opening (HxWxD)	Ceiling Closure (WxD)
30 lbs (13.6 kg)	8.5" (216 mm)	9.5 x 16.5 x 18.5" (241 x 419 x 470 mm)	11.2 x 23.5 x 23.5" (284 x 597 x 597 mm)	19.3 x 20.7" (489 x 526 mm)



SL236 SMART-LIFT



Provides 36" (914 mm) of downward travel with three stopping positions. Includes adjustments for precise positioning.

Weight Capacity	Extension	Max Projector Size (HxWxD)	Ceiling Opening (HxWxD)	Ceiling Closure (WxD)
35 lbs (15.9 kg)	36" (914 mm)	9.3 x 20.5 x 22.8" (235 x 521 x 578 mm)	11.1 x 25.5 x 28.5" (282 x 648 x 724 mm)	23.9 x 23.9" (607 x 607 mm)



SL151 SMART-LIFT



Provides exceptionally smooth and quiet movement. Great for suspended and finished ceilings in homes and corporate offices.

Weight Capacity	Extension	Max Projector Size (HxWxD)	Ceiling Opening (HxWxD)	Ceiling Closure (WxD)
35 lbs (15.9 kg)	8.3" (211 mm)	8.4 x 18.3 x 18.3" (213 x 464 x 464 mm)	11.2 x 23.5 x 23.5" (284 x 597 x 597 mm)	20.2 x 20.3" (514 x 515 mm)



AUTOMATED PROJECTOR MOUNT ACCESSORIES



IR10	Compatibility
Infrared Remote Control	SL151, SL236 and SL220



RC10	Compatibility
RF Remote Control	SL151 and SL236



ASP401	Compatibility
Individual Control System	SL151, SL236 and SL220



SMA602	Compatibility
Smart-Lift Single Column Mounting Plate	SL151 and SL236



SMA620	Compatibility
Suspended Ceiling Installation and Track Clip Kit	SL236



SMA651	Compatibility
Threaded Rod Adapter	SL236

UPB1	Compatibility
Smart-Lift Upright Projector Interface Bracket	SL151