



R1
12-inch 2-way



R2
Dual 12-inch 3-way

Finally, the powerful three-way R2 system features exceptional pattern control and vocal projection, delivering very high sensitivity and output levels. Community's M200 midrange compression driver and the deep, low flare rate midrange horn produce legendary long distance vocal projection with vocal clarity and extremely low distortion. Wide bandwidth directivity control makes it the ideal choice for taming difficult acoustic environments or achieving precision coverage over long distances. The R2 is available in three symmetric and two asymmetric coverage patterns.

Model	Drivers	Operating Range	Sensitivity	Power Handling (PGM)	Impedance	Dispersion (H x V)	Dimensions H x W x D
R.25-94Z	LF 1 x 8" HF 1 x 3/4"	100 Hz - 16 kHz	97 dB	500W	8 ohms	90°x 40°	11.3 x 11.3 x 13.3 in. (287 x 287 x 338 mm)
R.25-94TZ	LF 1 x 8" HF 1 x 3/4"	100 Hz - 16 kHz	96 dB	200W (70V/100V)	Varies by tap	90°x 40°	11.3 x 11.3 x 13.3 in. (287 x 287 x 338 mm)
R.5-66Z	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	103 dB	500W	8 ohms	60°x 60°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5-66TZ	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	102 dB	200W (70V/100V)	Varies by tap	60°x 60°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5-94Z	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	101 dB	500W	8 ohms	90°x 40°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5-94TZ	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	100 dB	200W (70V/100V)	Varies by tap	90°x 40°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5-99Z	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	101 dB	500W	8 ohms	90°x 90°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5-99TZ	LF 1 x 12" HF 1 x 1"	85 Hz - 16 kHz	100 dB	200W (70V/100V)	Varies by tap	90°x 90°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5HP	LF 1 x 12" MF 1 x 2" HF 1 x 1"	85 Hz - 16 kHz	106 dB	500W	6 ohms	60°x 40°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R.5HPT	LF 1 x 12" MF 1 x 2" HF 1 x 1"	90 Hz - 16 kHz	105 dB	200W (70V/100V)	Varies by tap	60°x 40°	16 x 16 x 16 in. (406 x 406 x 406 mm)
R1-64Z	LF 1 x 12" HF 1 x 1"	90 Hz - 16 kHz	105 dB	500W	8 ohms	60°x 40°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R1-66Z	LF 1 x 12" HF 1 x 1"	90 Hz - 16 kHz	105 dB	500W	8 ohms	60°x 60°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R1-94Z	LF 1 x 12" HF 1 x 1"	90 Hz - 16 kHz	104 dB	500W	8 ohms	90°x 40°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R2-52Z	LF 2 x 12" MF 2 x 2" HF 1 x 1"	70 Hz - 16 kHz	107 dB	1000W	4 ohms	50°x 20°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R2-77Z	LF 2 x 12" MF 1 x 2" HF 1 x 1"	70 Hz - 16 kHz	104 dB	1000W	4 ohms	70°x 70°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R2-94Z	LF 2 x 12" MF 1 x 2" HF 1 x 1"	70 Hz - 16 kHz	105 dB	1000W	4 ohms	90°x 40°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R2-474Z	LF 2 x 12" MF 1 x 2" HF 1 x 1"	70 Hz - 16 kHz	106 dB	1000W	4 ohms	40-70°x 40°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)
R2-694Z	LF 2 x 12" MF 1 x 2" HF 1 x 1"	70 Hz - 16 kHz	104 dB	1000W	4 ohms	60-90°x 40°	24.75 x 24.75 x 29 in. (629 x 629 x 737 mm)