MOTIV[™] FREESTANDING SERIES SOFT SEATING STOOLS

1>

_ _ _ ____

MOTIV[™] Soft Seating Stools

feature stylish, comfortable, cushioned seating. They are offered in two different heights and are available with either casters or glides.





20" STOOL WITH CASTERS - EDUMSKHC

15" STOOL WITH CASTERS - EDUMSKLC

- The MOTIV[™] Soft Seating Stool features a uniquely designed and structurally sound frame that is constructed with 14-gauge flat oval steel tubing, which is formed using a CNC tube bender and includes arc welded connections for strength.
- MOTIV[™] Soft Seating Stools are stackable and are available with casters or glides.
- Thick foam cushion covers stool seat for comfort. Seat is available in fabric or leather.
- All Bretford seating meets CAL 117 requirements. Certification for CAL 133 is available for an additional up-charge.

STOOL DIMENSIONS

- EDUMSKL 15" Stool with Glides: Overall Footprint: 18.75" Height: 15"
- EDUMSKLC 15" Stool with Casters: Overall Footprint: 21.5" Height: 15"
- EDUMSKH 20" Stool with Glides: Overall Footprint: 19.25" Height: 20"
- EDUMSKHC 20" Stool with Casters: Overall Footprint: 22" Height: 20"

Seat Diameter for All Models: 14.5"

SHIPPING DIMENSIONS

Carton Dimensions: 20"w x 20"d x 23"h Stools ship assembled in one (1) or two (2) carton packs; just install casters.

A HIGHER FORM OF FUNCTION



- EDUMSKL and EDUMSKLC 15" Stool: One (1) Unit Pack - 14 lbs. Freight Class 250 UPS Two (2) Unit Pack - 26 lbs. Freight Class 150 UPS
- EDUMSKH and EDUMSKHC 20" Stool: One (1) Unit Pack - 16 lbs. Freight Class 250 UPS Two (2) Unit Pack - 30 lbs. Freight Class 150 UPS

COLOR / FINISH

BRETFORD

Choose any grade of Bretford fabric or leather. A complete list is available at www.bretford.com.

Steel frame can be powder coated in any Bretford standard paint finish. A complete list is available at www.bretford.com.

11000 SEYMOUR AVENUE

FRANKLIN PARK, ILLINOIS 660131 USA

ථ

TOLL FREE PHONE 800-521-9614 PHONE 847-678-2545 TOLL FREE FAX 800-343-1779 FAX 847-678-0852 WWW.BRETFORD.COM ۲|