# EQUIPMENT



## A) JET J Series 5,000 Lb. Pallet Truck

 Easy-to-use with single hand operation, fingertip controls and 180° turning radius.

Features high quality welded steel construction with a durable powder coat finish. 2½" low profile design for smaller size pallet openings. 5,000 lb. capacity. FOB Shipping Point.

## B) JET PTX Series 5,500 Lb. Pallet Truck

• Rugged 5,500 lb. capacity with 210° turning radius.

Features rounded fork tips with nylon guide rollers for trouble-free pallet entry and exit. One piece cast iron pump features high quality seals, hardened and chrome plated ram and piston, top-of-stroke and overload bypass valves. 2½" lowered height. FOB Shipping Point.

## C) JET PTW Series 6,000 Lb. Premium Pallet Truck

- $\bullet$  200° turning radius allows room to maneuver in tight quarters.
- Tough 6,000 lb. lifting capacity.

Solid steel push rods never need adjustment. One piece cast pump features high quality seals, hardened and chrome-plated ram and piston, top-of-stroke and overload safety bypass valves. FOB Shipping Point.

Ltr.	Product No.	Cap. (lbs.)	Fork Size L x W	JET <sup>®</sup> PALLET <sup>*</sup> Min. Lift Hgt.	TRUCKS Max. Lift Hat.	Wheels Steer	Wheels Load	Wt. (lbs.)	Price Ea.
Α	H151009	5000	27 x 48"	2½"	61/4"	6¼"	2½"	204	\$397.73
В	H140093	5500	27 x 48"	2½"	61/4"	7	2½"	220	411.67
С	H140175	6000	27 x 48"	27/6"	73/,"	7	27/8"	210	424 33

# fr Wheels Wheels Steer Load (lbs.) Ec. Ec. 6½" 2½" 204 \$397.73 7 2½" 220 411.67 7 2½" 210 424.33

# **JET Hydraulic Scissor Lift Tables**

• Rugged steel construction to handle heavy transporting, lifting and positioning work. Table is easily raised by hydraulic foot pedal. Rolls on 2 fixed and 2 swivel casters for pinpoint positioning. Foot operated locks on swivel casters. FOB Shipping Point.

Product No.	Description	Cap. (lbs.)	JET® HYD Table Size W x L	RAULIC SCI Max. Lift Hat.	Min. Lift	Overall	Handle	No. Strokes	Wt.	Price Ea.
H140777 H140778		660	19% x 32½" 20% x 35%"	32%" 51%"	10%" 13%	40½" 45¾"	37½" 37½"	13 21		\$563.21 780.36







Features adjustable width forks and outrigger legs.
Two-stage hydraulic pump features top-of-stroke and safety overload bypass system. FOB Shipping Point.

