



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



Floor Door, Fire Rated, Flush Diamond Plate FRFD

Application

- Maintains the fire rating of a 2 hour floor ceiling assembly
- Designed for interior applications

Product Features

- Flush aluminum diamond plate cover
- Warnock Hersey International 2 hour fire rating
- Tested to NFPA 288 ; ASTM E 119



FRFD Floor Door Specifications:

Material: Aluminum door & top frame ; Stainless steel bottom frame, hinges & hardware

Door: 1/4" aluminum diamond plate reinforced for live load of 150 pounds/per sq. ft.

Frame: 3" x 3" x 1/4" aluminum top frame with thermal break 3 1/2" x 2" x 11gauge stainless steel bottom frame

Insulation: Two - 1" thick layers of ceramic blanket insulation attached to bottom frame

Hinge: Type 316 stainless steel continuous piano hinge

Opening Device: Door panel opens to 90 degrees. Automatic hold open arm with red vinyl grip keeps door in open position to ensure safe egress. Stainless steel compression springs provide lift assistance. U.L. listed 165 degree fusible link is provided for automatic closing and latching in the event of smoke or fire.

Latch: Stainless steel slam latch assembly with interior release

AVAILABLE SIZES (Special sizes available upon request)

FRAME I.D. SIZE W X H	WEIGHT PER DOOR		
	inches	mm	lbs.
24 x 24	609 x 609	80	36
24 x 36	609 x 914	140	63
24 x 48	609 x 1219	160	73
30 x 30	762 x 762	130	59
30 x 36	762 x 914	160	73
36 x 36	914 x 914	190	86
36 x 48	914 x 1219	240	109
42 x 42	1067 x 1067	250	113
48 x 48	1219 x 1219	280	127

For detailed specifications see submittal sheet

