INSTALL

PORTABLE PA

LOUDSPEAKERS



Designed for top-notch quality with amazing versatility, the ZX/ZXA series sets a new standard of performance and practicality in sound reinforcement loudspeakers. Featuring high-end components and lightweight molded enclosures, the ZX/ZXA line is at home in any installed or portable application, from commercial sound to clubs, houses of worship, stages, arenas and stadiums. Newly-designed high-power woofers and drivers ensure full-range sound

with awesome richness and clarity. Sleek contemporary styling fits in anywhere. Lightweight makes transport easy while enabling a multitude of flying and mounting options that are each supported by innovative mechanical solutions. Whether for portable use or permanent installation, the ZX/ZXA series represents the next level in advanced loudspeaker technology.

ZX1

8" TWO-WAY FULL-RANGE COMPOSITE LOUDSPEAKER

- Smooth, wide frequency response
- Ideal for mains, fills or monitors
- Velocity-compensated port for exceptional LF
- Long-excursion weather-treated EV8L woofer
- 1.25" DH2005 titanium HF compression driver
- Rotatable 90° x 50° waveguide for flexible coverage
- Passive crossover with full-band overload protection
- High sensitivity, 123 dB maximum SPL
- Power handling: 200 W continuous, 800 W peak
- High-impact polypropylene enclosure
- Compact monitor-friendly wedge shape
- Integrated pole mount adapter and pocket handle
- Four Metric mounting inserts
- Available in black or white

ZX1i

8" TWO-WAY FULL-RANGE INDOOR/OUTDOOR LOUDSPEAKER



- Install version of the ZX1
- Indoor/outdoor design
- Ideal for installed mains, fills or distributed sound
- Velocity-compensated port for exceptional LF
- Long-excursion weather-treated EV8L woofer
- 1.25" DH2005 titanium HF compression driver
- Choice of 90° x 50° or 100° x 100° rotatable waveguide
- Passive crossover with full-band overload protection
- Also available in 70/100 volt transformer

- version with Electro-Voice patented ASC (Automatic Saturation Compensation)
 - High sensitivity, 123 dB maximum SPL
 - Power handling: 200 W continuous, 800 W peak
 - Compact high-impact polypropylene enclosure
 - Integrated QuickSAM heavy-duty Strong-Arm Mounting bracket
 - Paintable black or white finish

ZX1-SUB

12" POWERED SUBWOOFER



- 15 mm plywood enclosure, internally braced, with textured paint
- EVS-12S 12" woofer for powerful, engaging bass response

Pole mount for full-range systems


ZX3

12" TWO-WAY FULL-RANGE LOUDSPEAKER

- Versatile performance for mains, fills or monitors
- DVX3121A woofer with forced-air cooling
- 2" ND2 titanium/neodymium HF driver
- Passive crossover
- Choice of 90° x 50° or 60° x 60° coverage waveguide
- High sensitivity, 131 dB maximum SPL
- Power handling: 600 W continuous, 2400 W peak
- High-impact polypropylene enclosure
- Compact monitor-friendly wedge shape Up to four anchor-plate attachments
- Seven M8 mounting inserts
- Integrated handle
- · Available in black and white

ZX4

15" TWO-WAY FULL-RANGE LOUDSPEAKER



- 1.25" DH3/2010A titanium HF driver
- Passive crossover
- 90° x 50° coverage waveguide High sensitivity, 132 dB maximum SPL
- Power handling: 400 W continuous, 1600 W peak
- Lightweight high-impact polypropylene enclosure
- Wedge shape for monitors at 45° or 55°
- Integrated pole mount adapter and pocket handle
- Mounting via attachment plates or eyebolts
- Black finish

ZX5

ALL-WEATHER 15" TWO-WAY FULL-RANGE LOUDSPEAKER

- Versatile performance for mains, fills or monitors
- DVX3150A woofer with forced-air cooling
- 2" ND2 titanium/neodymium HF driver
- Switchable biamp or passive crossover operation
- Choice of 90° x 50° or 60° x 60° coverage waveguide
- High sensitivity, 132 dB maximum SPL
- Power handling: 600 W continuous, 2400 W peak
- High-impact polypropylene enclosure
- Wedge shape for monitors at 45° or 55°
 - Up to five anchor-plate attachments
 - Ten M8 mounting inserts
 - Integrated handle
- Available in black or white

ZXA1

POWERED 8" TWO-WAY FULL-RANGE LOUDSPEAKER



- Powered ZX1, ideal for portable and monitor use
- Integrated 800 W 2-channel (biamp) amplifier Long-excursion weather-treated EV8L woofer
- 1.25" DH2005 titanium HF compression driver
- Rotatable 90° x 50° waveguide for flexible coverage
- Steep crossover slopes and transducer protection
- 123 dB maximum SPL

- Microphone and line level inputs
- Switchable high-pass filter for use with subwoofer
- Compact wedge-shape enclosure of lightweight impact-resistant polystyrene
- Integrated pole mount adapter and pocket handle
- Four #8-32 suspension points for installation
- Available in black or white

ZXA1-SUB

12" POWERED SUBWOOFER



- 15 mm plywood enclosure, internally braced, with textured paint
- EVS-12S 12" woofer for powerful, engaging bass response
- Class D lightweight amplifier

- Pole mount for full-range systems
- Dual XLR inputs and outputs
- Switchable EQ modes for different applications
- · LED indicators for power on and limit

ZXA5

POWERED 15" TWO-WAY FULL-RANGE LOUDSPEAKER



- Ideal for both portable and installation use
- Integrated 2-channel amplifier, 1000 W LF, 250 W HF
- DVX3150A woofer with forced-air cooling
- 2" ND2 titanium/neodymium HF driver 90° x 50° coverage waveguide
- High sensitivity, 133 dB maximum SPL
- · Switchable high-pass filter for use with subwoofer
- PowerCon connector with slave through
- Compact enclosure of high-impact polypropylene
- Wedge shape for monitors at 45° or 55°
- Integrated handle
- Up to five anchor-plate attachments
- Ten M8 mounting inserts
- Available in black or white

See page 51 for ZX/ZXA Rigging and Accessories and page 50 for ZXA1 and ZXA1-Sub Covers.

32