






BONNEY FORGE

Thredolet® Reducing, Size on Size and Flat

CL 3000

CL 6000



SIZE ON SIZE

REDUCING SIZES

	Outlet Size Inches	Dimensions			Appx. Weight Pounds
		A	B	C	
CL 3000	1/8	3/4	1	5/8	.10
	1/4	3/4	1	5/8	.10
	3/8	13/16	1-1/4	3/4	.20
	1/2	1	1-13/32	15/16	.25
	3/4	1-1/16	1-23/32	1-5/32	.35
	1	1-5/16	2	1-7/16	.60
	1-1/4	1-5/16	2-9/16	1-3/4	.90
	1-1/2	1-3/8	2-27/32	2	1.00
	2	1-1/2	3-15/32	2-9/16	1.75
	2-1/2	1-13/16	4-1/16	3	3.00
	3	2	4-13/16	3-11/16	4.35
	3-1/2	2-1/8	5-7/32	4	5.75
	4	2-1/4	5-31/32	4-3/4	7.10
	5	2-5/8	7-5/16	5-9/16	12.00
	6	2-3/4	8-5/8	6-11/16	15.30
CL 6000	1/4	1-1/8	1-11/32	9/16	.30
	3/8	1-1/8	1-11/32	9/16	.30
	1/2	1-1/4	1-23/32	3/4	.45
	3/4	1-7/16	1-61/64	1	.75
	1	1-9/16	2-7/16	1-5/16	1.25
	1-1/4	1-5/8	2-23/32	1-1/2	1.60
	1-1/2	1-11/16	3-1/4	1-15/16	1.95
	2	2-1/16	4-1/32	2-3/4	5.00

SIZE ON SIZE

	Outlet Size Inches	Dimensions				Appx. Weight Pounds
		A	B	C	D	
CL 3000	1/2	1	1-3/8	15/16	5/8	.15
	3/4	1-1/16	1-5/8	1-3/16	13/16	.25
	1	1-5/16	2	1-7/16	1-1/16	.45
	1-1/4	1-5/16	2-3/8	1-3/4	1-3/8	.70
	1-1/2	1-3/8	2-7/8	2	1-5/8	.90
	2	1-1/2	3-1/2	2-9/16	2-1/16	1.40
	2-1/2	1-29/32	4-1/16	3	2-1/2	2.50
	3	2	4-13/16	3-11/16	3-1/16	4.30
	3-1/2	2-1/8	5-3/8	4-7/16	3-9/16	4.50
	4	2-1/4	6-1/16	4-3/4	4-1/16	6.80
	5	2-7/16	7-1/4	5-1/4	5-1/4	9.20
	6	2-3/4	8-11/16	5-3/4	5-3/4	15.70

Each outlet size listed is available to fit any run curvature. Threaded ends are in accordance with ANSI/ASME B1.20.1

Design per MSS-SP-97

RUN PIPE SIZES

Outlet sizes noted above fit a number of run pipe sizes, and the fittings are marked accordingly.

See page 38 for run pipe size combination table(s).

FLATS

A flat Thredolet for use on welding caps, elliptical heads and flat surfaces is available.

ORDERING

When ordering a Thredolet fitting, see page 7.